



**Document Library**  
**TS Data Sheet 09034**  
**09035**

Rev:2

Status: Active

Effective: 05/02/2001

## **3M™ Marine Multi-Purpose Boat Soap**



<b>3M Part No.(s)</b>	<b>3M Part Descriptor(s)</b>
09034	16 fl. oz. liquid
09035	32 fl. oz. liquid

---

### **Description**

Concentrated formula designed to clean anything from dirty decks to soiled fabrics to degreasing engines. Mix concentrate with water for desired cleaning strength. Cleans grease, oil, grime, algae, fish blood dirt, etc. on hulls, decks, upholstery, canvas, carpet, and engines. For example: Mix 2 oz. of 3M™ Marine Multi-Purpose Boat Soap with 1 gallon of water for effective hull and deck cleaning.

---

### **Features**

- Removes algae
- Removes fish blood
- Low-suds formulation
- Concentrated formula allows flexibility

---

### **Typical Physical Properties**

Color	Clear
Consistency	Concentrated liquid
Odor	slight odor

---

### **Performance Properties**

## **Application Information**

---

### **Directions for Use**

1. Mix soap and water to desired solution (see table below).
2. Spray or sponge soap dilution onto the surface to be cleaned.
3. Scrub with 3M™ Doodlebug Pads, Scotch-Brite™ Scrubbers or O-Cel-O™ Sponges for fast cleaning action.
4. Rinse thoroughly.

#### **Dilution Table**

Windows (Glass,	1 oz. per gallon of	1/4 oz. per quart of
-----------------	---------------------	----------------------

plastic)	water	water
<b>Light Duty</b> (To clean loose dirt, sand, and grime from hull, deck, and non-skid surfaces)	<b>2 oz. per gallon of water</b>	<b>1/2 oz. per quart of water</b>
<b>Medium Duty</b> (To clean soiled canvas, upholstery, vinyl, carpet and other marine fabrics)	<b>8 oz. per gallon of water</b>	<b>2 oz. per quart of water</b>
<b>Heavy Duty</b> (To degrease engines)	<b>32 oz. per gallon of water</b>	<b>8 oz. per quart of water</b>

---

## Applications

see description and features

---

## Storage and Handling

**Recommended Storage Temperature Range : 60F to 80F**

**Expected Shelf Life at Recommended Storage Temperature : 36 months**

---

## Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

## Country

US

**This document is public. It may be distributed.**

---

## Important Notice to Purchaser

**Technical Data:** All physical properties, statements and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. 3M recommends each user determine the suitability of the products for the intended use.

\* If 'Directions for Use' reference P.N.'s 08984, 08986, or 08987, please read. Federal and local air quality regulations may regulate or prohibit the use of surface preparation and cleanup solvents based on VOC content. Consult your local and Federal air quality regulations for information. When using solvents, use in a well ventilated area. Extinguish all sources of ignition in the work area and observe precautionary measures for handling these materials. Refer to product label and MSDS for P.N. 8984, 8986, or 8987 for detailed precautionary information.

**Warranty and Limited Remedy:** 3M warrants this product will be free from defects in materials and manufacture. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE** . If the product is proved to be defective your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

**Limitation of Liability:** 3M and seller will not be liable for any loss or damage arising from this product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

---

## For Additional Health and Safety Information

3M Marine

3M Center, Building 223-6S-06  
Saint Paul, MN 55144-1000  
1-877-366-2746 ( 1-877-3M MARINE)