



Concrete Maintenance and Repair

DP-600

Fast, convenient application and rapid cure for increased productivity



Crack repair, expansion joints, custom threading and anchoring, spall repair, and more.



3M™ Concrete Repair DP-600 is a self-leveling, gray, rapid setting, two-component polyurethane. It is packaged as 1:1 ratio liquids in a duo-pak 12 oz. cartridge. With the squeeze of a trigger, the components are automatically mixed and easily dispensed as a bubble-free self-leveling liquid.



3M™ Concrete Repair DP-600* Gray, Self-Leveling



Size	Work life	Handling time	Cure time
12 oz.	70 seg.	5 min.	1 hr.

Application ideas	Benefits
<ul style="list-style-type: none"> • Repair of cracks or spalls on floors or horizontal surfaces. • Anchoring and mounting. Setting anchors in floors or horizontal surfaces. • Control joints filling. • Anchoring bolts to stabilize large equipment and repairs. • Securing railings or posts in concrete, wood or other substrates. 	<ul style="list-style-type: none"> • Easy to use and convenient system. With the squeeze of a trigger, the self-leveling formulation flows smoothly into cleaned cracks and gaps. • Hardens in as little as 5 minutes. • Concrete area can be put into use immediately. • Reduce down-time for maintenance • Hardens without cracking or shrinking. • 3M urethane technology hardens to any depth. • Flexible enough to resist expansion and contraction.

*DP-600 is also available in Non Sag version (12 oz. Cartridges) for vertical surfaces. Ask your 3M Representative for more information.

Dispensing Equipment



Pneumatic applicator for large area cracks and other high volume jobs with 12 fl. oz. Duo-Pak cartridges.



Heavy duty manual applicator for lengthy control joints and other large jobs with 12 fl. oz. Duo-Pak cartridges.



3M DP-600 Self-Leveling Concrete Repair Starter Kit

- Four 12 oz. Cartridges of DP-600 Self-Leveling
- Twelve mixing nozzles
- One manual applicator
- One plastic spreader/smoothing tool

Approximate coverage in half round bead

Bead Size Dimension	Linear ft. per 12 fl. oz.	Crack Width	Crack Depth	Linear ft. per 12 fl. oz.
1/2	9	1/4"	1/4"	28
3/8	33	1/2"	1/4"	14
1/4	75	3/4"	1/4"	9
1/8	298	1"	1/4"	7
1/16	1182	1/4"	1/2"	14
		1/2"	1/2"	7
		3/4"	1/2"	4
		1"	1/2"	3

NOTE: The technical information and data provided above is a general guide only and should be considered representative or typical only and should not be used for specification purposes.

Product Use: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application. Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price. Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Adhesives Systems Division
3M Canada

Post Office Box 5757
London, Ontario N6A 4T1

3M is a trademark of 3M used under license in Canada.
0407-CP-20292