Technical Data Sheet Revision B, March 2018

Product Description

Scotchgard[™] Bonnet Cleaner Concentrate 11L is a concentrated product intended to be diluted and dispensed using the 3M[™] Twist 'n Fill[™] Cleaning Chemical Management System.

This product is an effective surface cleaner designed to be used with the 3M[™] Carpet Bonnet Pad. Scotchgard[™] Bonnet Cleaner is formulated for use with Scotchgard[™] Carpet Protector and is an important part of the 3M carpet care system.

Special Features

- Excellent surface cleaner for interim carpet maintenance
- Easy-to-use cleaning process
- Fast drying cleaning process minimizes carpet down time
- Extends the time between restorative extraction cleanings
- Low foaming
- Effectively removes spots that wick to the carpet surface after extraction cleaning

Applications

- Commercial grade carpets
- Low profile loop or cut-pile construction
- Traffic lanes

Packaging

- 2 liter bottles
- 6 bottles per case

General Use Directions

Note: Test the Scotchgard[™] Bonnet Cleaner in an inconspicuous area to make sure the carpet is colorfast. Apply ready-to-use solution to a small area. After several minutes, blot the carpet with a clean white cloth or paper towel. If color from the carpet transfers to the cloth or towel, discontinue use.

- 1. Vacuum the carpet area thoroughly.
- 2. Use a 3M[™] All Purpose Sprayer (Model AP-1) or a bulk pressurized sprayer to apply the bonnet cleaner.
- 3. Dispense the Scotchgard[™] Bonnet Cleaner using the 3M[™] Twist 'n Fill[™] Dispenser directly into the solution tank of your sprayer.
- 4. Apply the ready-to-use solution at a rate of 200-300 ft² per gallon.
- 5. Allow 1-2 minutes dwell time for the cleaner to penetrate the fiber.
- 6. Clean using a 175 rpm floor machine with a 3M[™] Carpet Bonnet Pad or carpet brush.
- 7. Do not over-wet the carpet bonnet pad by soaking it, however spray the pad with Scotchgard[™] Bonnet Cleaner before starting to reduce the drag of the machine on the carpet.
- 8. Bonnet the area until the light foam generated is worked into the carpet.
- 9. When the pad becomes heavily soiled, turn the pad over and continue.
- 10. Change to a clean pad when necessary.
- 11. Vacuum the area when the carpet is completely dry.

Quick Links

<u>Resource Library</u> Safety Data Sheets (SDS) Video Library

Some of these links lead to web-based resources that are not product-specific.

Note: Personal Protective Equipment (PPE) Recommendation:

Refer to SDS for specific PPE guidance. Refer to product Safety Data Sheets for specific physical properties, health hazard, first aid and precautionary information.

Concentrate SDS #: 19-0058-8

RTU SDS#: 19-0060-4

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to <u>3M.com/SDS</u>, or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501. When using any equipment, always follow the manufacturers' instructions for safe operation.

Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the **Customer Service Department at 1-800-852-9722.**

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.



Warranty

3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PAR-TICULAR PURPOSE.

Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

Commercial Solutions Division 3M Center, Building 220-12E-04 St. Paul, MN 55144 © 3M 2018. All rights reserved. 3M and Scotchgard are trademarks of 3M. Used under license in Canada. All other trademarks are property of their respective owners. Revision B, March 2018. Please recycle.

