

3M

Sealing Tape

8777

Technical Data

June, 2011

Product Description 3M™ Sealing Tape 8777 is a self-adhered, waterproof membrane designed for sealing on difficult to stick to surfaces. This product has a unique acrylic pressure sensitive adhesive that aggressively sticks and stays stuck both at lower and higher application temperatures. The proprietary backing seals around hand driven nails and staples to prevent moisture intrusion. This backing is tough, resists punctures and tears, yet it is thin and conformable to fit conveniently into corners.

Product Construction	Backing	Adhesive	Liner	Color	Standard Roll Length
	Proprietary film	Acrylic	Heavy paper, split	Tan	75 feet (22.8m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		Test Method
Adhesion to Polyethylene:	60 oz./in. width (66 N/100 mm)	ASTM D-3330
Adhesion to OSB:	60 oz./in. width (66 N/100 mm)	ASTM D-3330
Adhesion to Housewrap*:	50 oz./in. width (55 N/100 mm)	ASTM D-3330
Adhesion to Anodized: Aluminum:		
After 7 days at 176°F:	70 oz./in. width (77 N/100 mm)	ASTM D-3330
After 7 days in water:	65 oz./in. width (71 N/100 mm)	ASTM D-3330
After Thermal Cycling:	75 oz./in. width (82 N/100 mm)	ASTM D-3330
After UV Exposure:	60 oz./in. width (66 N/100 mm)	ASTM D-3330
Nail Sealability:		ASTM E331/547 as modified per AAMA 711-07 Annex 1
Initial:	Pass	
After Thermal Cycling:	Pass	
Permeability:	0.17 perms	ASTM E-96 (dessicant method)
Tape Thickness:	9.9 mils (0.25 mm)	ASTM D-3652
Service Temp. Range:	-40 to 176°F (-40 to 80°C)	Tested per AAMA 711-05
Application Temp. Range:	0 to 120°F (-18 to 49°C)	

*Spun bonded polyethylene.

3M™ Sealing Tape

8777

Features

- Nail Sealability: Passes ASTM E331/547 (per AAMA 711-07, Annex 1) both before and after thermal cycling.
- Meets the criteria to contribute to the Environmental Quality (“EQ”) Credit 4.1: Low-Emitting Materials: Adhesives & Sealants under the United States Green Building Council’s Rating System for New Construction & Major Renovations (LEED-NC), Version 2.2, Core and Shell (LEED-CS), Version 2.0, and Commercial Interiors (LEED-CI), Version 2.0.
- High tack adhesive sticks and stays stuck to many difficult to stick to surfaces.
- Unique adhesive adheres to damp surfaces.
- Adhesive provides an unique combination of both cold temperature and hot temperature adhesion to most substrates.
- No adhesive melting or staining in summer heat.
- Proprietary backing seals around nails and staples to prevent moisture intrusion.
- Unique backing is thin and conformable to conveniently fit into corners.
- Tough backing resists punctures and tears during application.
- Resists UV exposure for up to 6 months.
- Can be installed at temperatures as low as 0°F (-18°C) and as warm as 120°F (49°C).
- Compatible with many building sealants: No adverse reaction with synthetic rubber, butyl, polyurethane, silicone and silane terminated hybrid sealants.
- Split release liner provides fast application with easy and accurate positioning of the tape.

3M™ Sealing Tape

8777

Storage Store under normal conditions of 60-80°F (16-27°C) and 40-60% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within 24 months from date of manufacture.

Technical Information The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2008

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2011 70071616158 (6/11)