

3M

Polyester Tape

8902

Technical Data

January, 2004

Product Description 3M™ Polyester Tape 8902 is a high temperature tape with a silicone adhesive for use as a maskant in powder coat painting and is designed to provide clean removal during masking operations involving high temperatures and pressure.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Polyester	Silicone	Blue	72 yds. (66 m)

Typical Physical Properties **Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	40 oz./in. width (44 N/100 mm)	D-3330
Tensile Strength at Break:	53 lbs./in. width (928 N/100 mm)	D-3759
Elongation at Break:	130%	D-3759
Backing Thickness:	2 mils (0.5 mm)	D-3652
Total Tape Thickness:	3.4 mils (0.09 mm)	D-3652
Temperature Use Range:	Up to 400°F (204°C)	

Features

- Polyester film that retains flexibility and thermal resistance and is abrasion, chemical and thermal resistant to help reduce failures due to cracking and backing deterioration.
- Silicone adhesive for higher heat resistance than many other adhesives to help reduce failure due to softening, oozing and adhesive transfer.

Application Ideas

- Composite and metal bonding as it removes cleanly from stainless steel, anodized aluminum and glass after a 5 hour bake cycle at 350°F (177°C).
- Masking edges of overlap seams in metal bonding process where excess epoxy (“flash”) flows onto tape as clean-up is complete upon tape removal.
- Holding parts or vacuum bags during bonding process.
- Masking parts for powder coat painting.
- Splicing silicone treated materials.
- Composite bagging operations or to remove flashing after bonding.

3M™ Polyester Tape

8902

Storage Store under normal conditions of 60° to 80°F (15° to 27°C) and 40-50% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within 18 months from date of manufacture.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/industrialtape. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Product Use All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001

This product was manufactured under a quality system registered to ISO 9001 standards.

3M

**Industrial Business
Industrial Adhesives and Tapes Division**
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2004 70-0709-0968-7 (1/04)