



Public

Rev:1

Effective: 06/27/99

Status: Active

Fuel Injector Cleaner Tank Additive

Data Sheet

3M Part No.(s) **3M Part Descriptor(s)**
08812 16 Oz. Bottle

3M Fax on Demand Identification Number:

Description

3M™ Fuel Injector Cleaner Tank Additive is designed to be added to the fuel tank to facilitate the cleaning of fuel injectors.

Features, Advantages, Benefits

Features ● Cleans fuel injection deposits
 ● Restores power and fuel economy
 ● One bottle per tank of gas helps to eliminate stalling, hesitation, and poor performance due to dirty fuel injector deposits

Advantages

Benefits

Typical Physical Properties

Container	16 Oz. Bottle
Base	Solvents
Color	Amber Liquid
Flash Point - °F	143 TCC ASTM D56
Consistency	Thin Liquid
Solvent	Hydrotreated Light Napthenic Petroleum Distillates, Xylene, Ethylbenzene, Isopropyl Alcohol

Product Uses

Performance Properties

Handling and Application Information

Directions for Use

1. Remove the cap and seal from the top of the bottle.
2. Remove the vehicles fuel cap and pour the entire contents of the bottle into a full tank of gas - treats 12 to 16 gallons of gasoline. NOTE: On fuel tanks 26 gallons and larger, use two bottles.
3. 3M™ Fuel Injector Cleaner Tank Additive can be added to every other tank full of fuel but should not exceed six additions per oil change.

Applications

- Gasoline engines ONLY!
- Each bottle treats 12 to 16 gallons of gasoline
- Do not exceed six additions per oil change

Storage and Handling

Store at room temperature. Rotate stock on a "first-in, first-out" basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 12 months.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

Country

US

This document is public. It may be distributed.

Important Notice to Purchaser

The statements and technical information contained in this technical data sheet are based on tests and data which 3M believes to be reliable, but the accuracy or completeness of such statements and technical information is not guaranteed. **3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application.

* If 'Directions for Use' reference P.N.'s 8984, 8986, or 8987, please read below.

Federal and local air quality regulations may regulate or prohibit the use of surface preparation and cleanup solvents based on VOC content. Consult your local and Federal air quality regulations for information. When using solvents, use in a well ventilated area. Extinguish all sources of ignition in the work area and observe precautionary measures for handling these materials. Refer to product label and MSDS for P.N. 8984, 8986, or 8987 for detailed precautionary information.

LIMITATION OF REMEDIES AND LIABILITY: If the 3M product is proved to be defective, **THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT.**

3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

For Additional Health and Safety Information

See Material Safety Data Sheet (Fax on Demand 1-800-305-0419), or call: **3M Automotive Aftermarket Division** 3M Center, Building 223-6N-01
Phone: 877-MMM-CARS (877-666-2277)

3M Fax on Demand Identification Number

Reference: Goto Ref

Author:

Duane C. Richardson/US-Corporate/3M/US

Tonya L. Frisle/IM-IndMktsGp/3M/US

This is the last page