



Spray Buff Cleaner and Polish

Technical Data

June 2004

Description:

3M Spray Buff Cleaner and Polish is a ready-to-use, milky-white emulsion that is composed of a special blend of polymers, waxes and solvents. It is designed for use with 3M finishes and other high quality synthetic floor finishes to clean and polish floors to a high luster when used in spray buff operations.

Special Features:

- Immediate high gloss and luster
- Excellent cleaning
- Excellent mark and scuff resistance (after use)
- Pleasant scent
- Floor finish recoatability (after use)
- Compatible with 3M floor finishes and most high quality synthetic floor finishes

Applications:

- Use on all floors protected with 3M floor finishes or other high quality floor finishes. To assure the best possible results, floor should have 3-4 coats of finish.
- Can be used with standard speed, high speed or super high-speed equipment and pads.
- Can be used with ultra high-speed burnishers and pads.

Packaging:

4 – 1 gallon bottles per case

Note: Protect from freezing and keep away from heat and sparks.

General Use Directions:

1. Read precautionary information prior to use.
2. 3M Spray Buff Cleaner and Polish is ready-to-use. Shake container vigorously and pour desired amount into trigger spray bottle.
3. Dust mop floor with 3M Doodleduster™ Cloth and Holder. Remove gum or other sticky substances.
4. Shake the trigger spray bottle prior to spray buffing and occasionally during use. Spray onto floor machine – two (2) sprays per 20 square feet is sufficient.
5. Clean and buff floor to high gloss using appropriate pad.
6. Dust mop floor with Doodleduster cloth to remove any residue.

Product Specifications:

(Typical Values)

1. pH: 9.0
2. Flash Point: 122° F C.C
3. Specific Gravity: 96
4. Appearance: Milky-white liquid
5. Coverage: One gallon will buff approximately 25,000 sq. ft.

Precautionary Summary:

Eye Contact: Moderate eye irritant

Skin Contact: Mild skin irritant after prolonged or repeated exposure

Inhalation: Irritating to nose and throat

Note:

Refer to product Material Safety Data Sheet (MSDS: 10-9283-2) for specific health hazard, first aid and precautionary information

3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle
Anchorage, AK 99515
Telephone: 907/522-5200
Facsimile 907/522-1645

CONTINENTAL UNITED STATES

Customer Service Department
3M Center Building 223-5S-07
St. Paul, MN 55144-1000
Order Entry 1-800-852-9722
Facsimile 1-800-447-0408

HONOLULU

4443 Malaai Street
Honolulu, HI 96818
Mail to: P.O. Box 30048
Honolulu, HI 96820
Telephone: 808/422-2721
Facsimile 808/422-9557

CANADA

1840 Oxford Street East
London, Ontario, Canada
N5V 3G2
Mail to: P.O. Box 5757
London, Ontario, Canada
N6A 4T1
Telephone: 800/364-3577
Facsimile: 800/479-4453

Important:

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

3M
Building and Commercial Services Division
St. Paul, MN 55144-1000
1-800-852-9722
www.3M.com/commcare

3M is a trademark of 3M Company.

Copyright © 2004, 3M IPC. All rights reserved.