



Floor Stripper LO Concentrate

Technical Data

Description:

3M™ Floor Stripper LO Concentrate is a concentrated floor stripper requiring dilution before use.

The diluted 3M floor stripper LO is formulated to be a low odor, high performance floor stripper for burnished or built-up finishes on hard floors. This stripper is designed to quickly and effectively remove floor finishes and sealers.

Special Features:

- Superior performance in removing multiple layers of floor finish
- Two to five minute dwell time
- Low foam
- Low odor
- Mild fragrance
- Non-damaging to vinyl
- Low pH
- Non-butyl formula

Where and When to Use:

This product is designed to remove sealers, floor finish build-up and finishes hardened by frequent burnishing. Follow directions to properly prepare floor for recoating.

Note: Do not use on wood floors.

Packaging:

1 quart plastic bottle, 6 per case
1 gallon plastic bottle, 4 per case
2.5 gallon plastic bottle, 2 per case
55 gallon drum

Directions for Use:

1. Mix one part 3M floor stripper LO with 19 parts water (one quart stripper together with enough water to make five gallons of ready-to-use stripper). With the mop, agitate the solution for 30 seconds in the bucket.
2. Sweep or dust the floor.
3. Properly locate caution signs for wet floor conditions.
4. Liberally apply diluted stripper solution to the floor with a mop, leaving the floor uniformly wet.
5. Allow stripper solution to remain on the floor for two to five minutes.
6. Use a floor machine and an appropriate 3M™ stripping pad to thoroughly strip the old finish from the floor.
7. Pick up dissolved finish, soil and stripper with a designated mop or a wet vacuum.
8. Rinse the floor at least once with clean water.
9. Let the floor dry completely before applying new finish.

Note: When using an automatic scrubber equipped with appropriate 3M stripping pads, remember to allow the stripping solution to remain wet on the floor for two to five minutes before agitation and pickup.

Product Specifications:

(Typical Values)

1. pH: ca. 11 (5% in water)
2. Flash Point: >200°F
3. Solubility in Water: ca. 6% by weight
4. Specific Gravity: 1.04
5. Viscosity: <10 Centipoise
6. Appearance: Dark green liquid
7. Fragrance: Floral

Precaution Summary:

Eye Contact: Corrosive to eyes.
Skin Contact: Corrosive to skin.
Inhalation: Irritating to nose and throat.

Note:

Refer to product Material Safety Data Sheet (MSDS: 08-4515-6) for specific health hazard, first aid and precautionary information.

3M Branch Sales Offices

Anchorage

11151 Calaska Circle
Anchorage, AK 99515
Area Code 907 Tel. 522-5200
Facsimile 907-522-1645

Continental United States

Customer Service Department
3M Center Building 223-5S-07
St. Paul, MN 55144-1000
Order Entry 1-800-852-9722
Facsimile 1-800-447-0408

Honolulu

4443 Malaai Street
Honolulu, HI 96818
Mail to: P.O. Box 30048
Honolulu, HI 96820
Area Code 808 Tel. 422-2721
Facsimile 808-422-9557

Canada

1840 Oxford Street East
London, Ontario, Canada
N5V 3G2
Mail to: P. O. Box 5757
London, Ontario, Canada
N6A 4T1
800-364-3577
Fax: 800-479-4453

Distributed by:

Important Notice:

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.



Commercial Care Division

3M Center, Building 223-3N-05
St. Paul, MN 55144-1000

70-0707-8241-5

© 3M 1998