



# Carry Handle Tape

## 8347

Technical Data

January, 2014

**Product Description** 3M™ Carry Handle Tape 8347 is a high-performance tape featuring a durable 3M™ Scotchpro™ Film backing that is longitudinal direction and an aggressive rubber resin adhesive especially suited for high shear performance carrying handles that allows for items up to 20 lbs. to be carried easily.

Construction	Backing	Adhesive	Colors
	Monoaxially oriented 3M™ Scotchpro™ Film	Pressure sensitive rubber resin. Requires no heat, moisture, or solvent activation prior to use.	Transparent

### Typical Physical Properties

**Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**

Adhesion to Polyethylene:	22 oz./in. width (24.5 N/100 mm width)	
Tensile Strength:	108 lbs./in. width (1900 N/100 mm width)	AFERA 4004
Elongation at Break:	40%	AFERA 4005
Thickness - Backing:	2.0 mil (50 micron)	AFERA 4006
Total:	2.9 mil (73 micron)	

### Features

- Excellent adhesion to most shrink film over wraps that helps assure good attachment of handle
- No dwell time necessary, adheres immediately and fast to apply.
- Efficient application on automated handle application equipment and good handling properties.
- Fewer roll changes on application equipment which increases production rate for lower unit cost.
- Designed for use on automatic carry handle application equipment with packages weighing 20 lbs. (9.0 kg) or less.

# 3M™ Carry Handle Tape

8347

---

<b>Available Sizes</b>	Standard Width:	0.98 in. (25 mm) Standard
	Length:	5468 yds. (5000 m) - level wound
	Core Size (ID):	6 in. (152 mm)

---

## **Application Techniques**

### Recommended Surfaces

- Paperboard printed and unprinted.
- Corrugated cardboard.
- Polyethylene and polypropylene (strong shrink film/poly bags).
- Polyester film.
- Polyvinyl chloride (PVC) film.

### Surfaces That Should Be Reviewed For Suitability

- Wax coated/siliconized surfaces.
- Wet surfaces (moisture condensation).
- Cold surfaces (< 50°F [10°C]).
- Some lacquer coated board.
- Rough textured surfaces on which tape surface contact is significantly reduced.

### Application Instructions

- Select appropriate carry handle to meet package weight limit.
- Remove a single handle from pad and apply one end to side of package. Press full length of adhesive tape leg firmly onto package side with hand pressure.
- Lay handle across top of package using hand to form a snug loop; press full length of remaining adhesive tape leg firmly onto the opposite side with hand pressure.
- Use only one carry handle per package.
- When applying handle to a box with over-lapped flaps which are not sealed down, the adhesive portion of the handle must be applied to the side and bottom of box.
- Do **not** apply the majority of or the entire adhesive portion of the handle to top of box. Adhesive legs must be positioned on the package sides (vertical dimension) to insure application success.

---

<b>Storage Conditions</b>	Storage of handle at 70°F (21°C) and 40-50% relative humidity is recommended.
---------------------------	---

---

<b>Shelf Life</b>	To obtain best performance, use this product within 18 months from date of manufacture.
-------------------	---

# 3M™ Carry Handle Tape

8347

---

## For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit [www.3M.com/packaging](http://www.3M.com/packaging). Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 225-3S-06, St. Paul, MN 55144-1000. Our fax number is 877-369-2923. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

---

## Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

---

## Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

---

## Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

---

**ISO 9001**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

**3M**

### Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
[www.3M.com/industrial](http://www.3M.com/industrial)



Recycled Paper 40%  
pre-consumer  
10% post-consumer

3M is a trademark of 3M.  
Printed in U.S.A.  
©3M 2014 (1/14)