



# Fillers, putties, compounds and primers

## Product Selector Guide



3M now offers newly engineered putties, fillers, compounds & primers designed specifically for the Composites industry. These products are designed from marine grade, semi-flexible polyester resins that have high-bonding capabilities and a low exothermic reaction to reduce shrinkage.

We offer lightweight bonding and filling putties, reinforced bonding putties, pumpable putties, fairing compounds, lightweight pourable putties, & polyester primers for prototype work. These products are engineered to meet specific application needs in the Marine, RV and Composites industries.

For application or technical information,  
call 1-800-421-2663 or (404) 696-2730.



# Product Selector Guide

	Part Number	Package Size	Package Type	Application
<b>Reinforced Bonding Gel</b>	16116	5 Gallon	Plastic Pail	<b>For Bonding Liners, Decks, and Hulls</b> <i>Features: High Strength Structural Bonding Excellent Vertical Hang Fast Set</i>
	16119	50 Gallon	Drum	
<b>General Purpose Bonding Putty</b>	16105	5 Gallon	Metal Pail	<b>For Bonding Inner Liners and Small Parts</b> <i>Features: Suitable for Bond Lines under 1/2 inch Excellent Vertical Hang Easy Spreading and Troweling</i>
<b>Structural Bonding Putty</b>	16215	5 Gallon	Metal Pail	<b>For Bonding of Hulls, Decks, and Bulk Heads</b> <i>Features: Thick Bond Line Capability Fiberglass Reinforced Long Work Time</i>
	16220	50 Gallon	Drum	
<b>Pumpable Bonding Putty</b>	16435	5 Gallon	Plastic Pail	<b>For Bonding Hulls, Decks &amp; Filling Strakes</b> <i>Features: Excellent for high volume applications Great Vertical hang and Stackability Lightweight &amp; Long Work Time</i>
	16439	50 Gallon	Drum	
<b>Lightweight Bonding Putty</b>	16015	5 Gallon	Plastic Pail	<b>For All Lightweight Bonding/Filling Strakes</b> <i>Features: 1" - 2" Bond Line Capability Highly Thixotropic with good vertical hang Extra Lightweight - 5.8 lbs/gallon Strake Filling</i>
<b>Lightweight Fairing Compound</b>	16055	5 Gallon	Plastic Pail	<b>For Final Finishing and Fairing of Plugs and Tooling</b> <i>Features: Easy Sanding Long Work Time Creamy Formulation</i>
<b>Fillet Putty</b>	16035	5 Gallon	Plastic Pail	<b>For Gelcoat Backup, Radius Forming, and Core Bonding</b> <i>Features: Fiberglass Reinforced, Brushable, Trowelable, and Pumpable Crack and Impact Damage Resistant</i>
	16037	5 Gallon	Metal Dispenser	
	16039	50 Gallon	Drum	
<b>Lightweight Pourable Filler</b>	16778	5 Gallon	Metal Pail	<b>For Filling Large Voids</b> <i>Features: Extremely Lightweight and Self-Leveling Extra Low Exotherms Water and Impact Resistant</i>
	16777	50 Gallon	Drum	
<b>Quick Set Fairing Compound</b>	16097	5 Gallon	Metal Dispenser	<b>For Final Finishing and Fairing of Plugs and Prototypes</b> <i>Features: Quick Set-Up Time Easy Spreading and Sanding Low Exotherm and Shrinkage</i>
<b>Polyester Primer</b>	16433	1 Gallon	Can	<b>For Priming and Finishing of Plugs and Prototypes</b> <i>Features: Long Shelf and Pot Life High-Build and Self-Leveling Capabilities Easy Sanding and Buffs to High Gloss</i>



## 3M Marine & Industrial Composites

3M Center, Building 223-IN-13  
St. Paul, MN 55144-1000

1-877-366-2746

[www.3m.com/marine](http://www.3m.com/marine)

[www.3m.com/composites](http://www.3m.com/composites)

3M is a trademark of 3M.

Please recycle. Printed in U.S.A.

© 3M 2008. All rights reserved.

60-4401-7450-0

**Product Use:** All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

**Warranty and Limited Remedy:** Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

**Limitation of Liability:** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.