

Safety Data Sheet

Copyright,2022, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	16-5619-8	Version number:	8.00
Issue Date:	28/11/2022	Supersedes date:	13/03/2022

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M[™] Foam Fast 74 Spray Adhesive Orange

 Product Identification Numbers

 62-4935-4921-6
 62-4935-4950-5
 AS-0194-6117-2

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Aerosol foam adhesive

For Industrial or Professional use only.

1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1. Serious Eye Damage/Irritation: Category 1. Reproductive Toxicity: Category 1. Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (single exposure): Category 3

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

Symbols

Flame |Corrosion |Exclamation mark |Health Hazard |

Pictograms



Hazard statements			
H222	Extremely flammable aerosol.		
H229	Pressurised container: may burst if heated.		
H318	Causes serious eye damage.		
H360	May damage fertility or the unborn child.		
H336	May cause drowsiness or dizziness.		
H370	Causes damage to organs: cardiovascular system.		
Precautionary statements General:			
P101	If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.		
Prevention:			
P201	Obtain special instructions before use.		
P202	Do not handle until all safety precautions have been read and understood.		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P211	Do not spray on an open flame or other ignition source.		
P251	Do not pierce or burn, even after use.		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.		
P264	Wash thoroughly after handling.		
P270	Do not eat, drink or smoke when using this product.		
P271	Use only outdoors or in a well-ventilated area.		
P280K	Wear protective gloves and respiratory protection.		
Response:			
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P310	Immediately call a POISON CENTRE or doctor/physician.		
Storage:			
P405	Store locked up.		
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.		

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

3M Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. Aspiration classification does not apply as this product is sold in sealed, self-pressurized containers with nozzles designed to prevent formation of a stream during usage. A similar mixture has been tested for eye damage/irritation and the test results are reflected in the assigned classification. A similar mixture has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification. May displace oxygen and cause rapid suffocation.

2.4. Other hazards which do not result in classification

Causes mild skin irritation. Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Acetone	67-64-1	15 - 25
Dimethyl Ether	115-10-6	15 - 25
Isobutane	75-28-5	10 - 20
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2- methylenebicyclo[3.1.1]heptane	31393-98-3	5 - 15
Non-hazardous components	Trade Secret	5 - 15
Pentane	109-66-0	7 - 13
Methyl acetate	79-20-9	3 - 7
Cyclohexane	110-82-7	1 - 5
Petroleum naphtha	64742-48-9	1 - 3
Toluene	108-88-3	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Condition
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

Hazchem Code: 2YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. WARNING ! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use

personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcinogen, Ototoxicant
Toluene	108-88-3	Australia OELs	TWA(8 hours):191 mg/m3(50	SKIN
			ppm);STEL(15 minutes):574	
			mg/m3(150 ppm)	
Pentane	109-66-0	ACGIH	TWA:1000 ppm	
Pentane	109-66-0	Australia OELs	TWA(8 hours):1770	
			mg/m3(600 ppm);STEL(15	
			minutes):2210 mg/m3(750	
			ppm)	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	Australia OELs	TWA(8 hours):350	
			mg/m3(100 ppm);STEL(15	
			minutes):1050 mg/m3(300	
			ppm)	
Dimethyl Ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	
Dimethyl Ether	115-10-6	Australia OELs	TWA(8 hours):760	
			mg/m3(400 ppm);STEL(15	
			minutes):950 mg/m3(500 ppm)	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human
				carcin
Acetone	67-64-1	Australia OELs	TWA(8 hours):1185	
			mg/m3(500 ppm);STEL(15	
			minutes):2375 mg/m3(1000	
			ppm)	
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
Natural gas	75-28-5	ACGIH	Limit value not established:	asphyxiant
Methyl acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl acetate	79-20-9	Australia OELs	TWA(8 hours):606	
			mg/m3(200 ppm);STEL(15	
			minutes):757 mg/m3(250 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full face shield. Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

Half facepiece or full facepiece supplied-air respirator.

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.	
Specific Physical Form:	Aerosol	
Colour	Orange	
Odour	Sweet Odour, Fruity Odour	
Odour threshold	No data available.	
рН	No data available.	
Melting point/Freezing point	No data available.	
Boiling point/Initial boiling point/Boiling range	[Details:Compressed gas]Not applicable.	
Flash point	-45.6 °C [Test Method: Tagliabue closed cup]	
Evaporation rate 1.9 [<i>Ref Std</i> :ETHER=1]		

Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapour pressure	[Details:Compressed gas]Not applicable.	
Vapor Density and/or Relative Vapor Density	2.97 [<i>Ref Std</i> :AIR=1]	
Density	0.718 g/ml	
Relative density	0.718 [<i>Ref Std</i> :WATER=1]	
Water solubility	Nil	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Viscosity/Kinematic Viscosity	Not applicable.	
Volatile organic compounds (VOC)	<=395 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]	
	[Details: Material VOC]	
Volatile organic compounds (VOC)	<=55 % [<i>Test Method</i> :calculated per CARB title 2]	
Percent volatile	No data available.	
VOC less H2O & exempt solvents	No data available.	
Molecular weight	No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability Stable.

10.3. Conditions to avoid Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>

None known.

<u>Condition</u>

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Dimethyl Ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Pentane	Dermal	Rabbit	LD50 3,000 mg/kg
Pentane	Inhalation-Vapour (4 hours)	Rat	LC50 > 18 mg/l
Pentane	Ingestion	Rat	LD50 > 2,000 mg/kg
2,6,6-Trimethylbicyclo[3.1.1]hept-2- ene, polymer with 6,6-dimethyl-2- methylenebicyclo[3.1.1]heptane	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,6,6-Trimethylbicyclo[3.1.1]hept-2-	Ingestion	Rat	LD50 > 2,000 mg/kg

Acute Toxicity

ene, polymer with 6,6-dimethyl-2- methylenebicyclo[3.1.1]heptane			
Non-hazardous components	Dermal	Rabbit	LD50 > 2,000 mg/kg
Non-hazardous components	Ingestion	Rat	LD50 > 2,000 mg/kg LD50 > 5,000 mg/kg
Methyl acetate	Dermal	Rat	LD50 > 3,000 mg/kg LD50 > 2,000 mg/kg
Methyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 49 mg/l
Methyl acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Petroleum naphtha	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Petroleum naphtha	Dermal	Rabbit	LD50 > 3,000 mg/kg
Petroleum naphtha	Ingestion	Rat	LD50 > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Isobutane	Professional judgement	No significant irritation
Acetone	Mouse	Minimal irritation
Pentane	Rabbit	Minimal irritation
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer	In vitro data	No significant irritation
with 6,6-dimethyl-2-		
methylenebicyclo[3.1.1]heptane		
Non-hazardous components	Professional judgement	No significant irritation
Methyl acetate	Rabbit	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Petroleum naphtha	Rabbit	Irritant
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Corrosive
Isobutane	Professional judgement	No significant irritation
Acetone	Rabbit	Severe irritant
Pentane	Rabbit	Mild irritant
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer	In vitro data	No significant irritation
with 6,6-dimethyl-2-		
methylenebicyclo[3.1.1]heptane		
Methyl acetate	Rabbit	Moderate irritant
Cyclohexane	Rabbit	Mild irritant
Petroleum naphtha	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
Pentane	Guinea pig	Not classified
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-	Multiple animal species	Not classified

methylenebicyclo[3.1.1]heptane		
Methyl acetate	Human	Not classified
Petroleum naphtha	Guinea pig	Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isobutane	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Pentane	In vivo	Not mutagenic
Pentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2- methylenebicyclo[3.1.1]heptane	In Vitro	Not mutagenic
Methyl acetate	In Vitro	Not mutagenic
Methyl acetate	In vivo	Not mutagenic
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Petroleum naphtha	In vivo	Not mutagenic
Petroleum naphtha	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Acetone	Not specified.	Multiple animal	Not carcinogenic
		species	
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
Petroleum naphtha	Dermal	Mouse	Some positive data exist, but the data
			are not sufficient for classification
Petroleum naphtha	Inhalation	Human and animal	Some positive data exist, but the data
			are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data
			are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data
			are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data
			are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Acetone	Ingestion	Not classified for	Rat	NOAEL	13 weeks
		male reproduction		1,700	
				mg/kg/day	
Acetone	Inhalation	Not classified for	Rat	NOAEL 5.2	during

		development		mg/l	organogenesis
Dimethyl Ether	Inhalation	Not classified for	Rat	NOAEL	during
		development		40,000 ppm	organogenesis
Pentane	Ingestion	Not classified for	Rat	NOAEL	during
	-	development		1,000	organogenesis
				mg/kg/day	
Pentane	Inhalation	Not classified for	Rat	NOAEL 30	during
		development		mg/l	organogenesis
Cyclohexane	Inhalation	Not classified for	Rat	NOAEL 24	2 generation
		female reproduction		mg/l	
Cyclohexane	Inhalation	Not classified for	Rat	NOAEL 24	2 generation
		male reproduction		mg/l	
Cyclohexane	Inhalation	Not classified for	Rat	NOAEL 6.9	2 generation
-		development		mg/l	-
Petroleum naphtha	Inhalation	Not classified for	Rat	NOAEL 2.4	during
_		development		mg/l	organogenesis
Toluene	Inhalation	Not classified for	Human	NOAEL Not	occupational
		female reproduction		available	exposure
Toluene	Inhalation	Not classified for	Rat	NOAEL 2.3	1 generation
		male reproduction		mg/l	-
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520	during gestation
		_		mg/kg/day	
Toluene	Inhalation	Toxic to development	Human	NOAEL Not	poisoning and/or
				available	abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes

Pentane	Inhalation	central nervous system	May cause drowsiness or	Multiple animal species	NOAEL Not available	not available
Pentane	Inhalation	depression respiratory	dizziness Some positive	Not available	NOAEL Not	not available
		irritation	data exist, but the data are not sufficient for classification		available	
Pentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	not available
Pentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	not available
Methyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Petroleum naphtha	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum naphtha	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum naphtha	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Petroleum naphtha	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ T	oxicity - repeated exposure
-------------------------	-----------------------------

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Dimethyl Ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Pentane	Inhalation	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Pentane	Inhalation	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 20 mg/l	13 weeks
Pentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
2,6,6- Trimethylbicy clo[3.1.1]hept -2-ene,	Ingestion	heart gastrointestinal tract hematopoietic	Not classified	Rat	NOAEL 331 mg/kg/day	90 days

1		· · · · ·	ſ	T	T	
polymer with 6,6-dimethyl-		system liver nervous system				
2-		eyes kidney				
methylenebic		and/or bladder				
yclo[3.1.1]hep tane						
Methyl	Inhalation	respiratory	Some positive	Rat	NOAEL 1.1	28 days
acetate		system	data exist, but the		mg/l	
			data are not			
			sufficient for classification			
Methyl	Inhalation	endocrine	Not classified	Rat	NOAEL 6.1	28 days
acetate	minaration	system	Not classified	Kat	mg/l	20 days
		hematopoietic			0	
		system liver				
		immune system				
		kidney and/or bladder				
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7	90 days
					mg/l	
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Petroleum naphtha	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Petroleum naphtha	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Petroleum naphtha	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Petroleum	Inhalation	bone, teeth,	Not classified	Rat	NOAEL 5.6	12 weeks
naphtha		nails, and/or hair blood liver			mg/l	
		muscles				
Petroleum	Inhalation	heart	Not classified	Multiple	NOAEL 1.3	90 days
naphtha				animal species	mg/l	5
Toluene	Inhalation	auditory system	Causes damage to	Human	NOAEL Not	poisoning and/or
		eyes olfactory	organs through		available	abuse
		system	prolonged or repeated exposure			
Toluene	Inhalation	nervous system	May cause	Human	NOAEL Not	poisoning and/or
			damage to organs		available	abuse
			though prolonged			
			or repeated			
T.1	Tabatatian		exposure	Det		15
Toluene	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL 2.3 mg/l	15 months
		system	data are not		iiig/i	
			sufficient for			
			classification			
Toluene	Inhalation	heart liver	Not classified	Rat	NOAEL 11.3	15 weeks
		kidney and/or bladder			mg/l	
Toluene	Inhalation	endocrine	Not classified	Rat	NOAEL 1.1	4 weeks
		system			mg/l	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth,	Not classified	Mouse	NOAEL 1.1	8 weeks

		nails, and/or hair			mg/l	
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Pentane	Aspiration hazard
Cyclohexane	Aspiration hazard
Petroleum naphtha	Aspiration hazard
Toluene	Aspiration hazard

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard: GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Acetone	67-64-1	Algae or other	Experimental	96 hours	EC50	11,493 mg/l
		aquatic plants				
Acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l

Acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
Dimethyl Ether	115-10-6	Bacteria	Experimental	N/A	EC10	>1.600 mg/l
	115-10-6			96 hours	LC50	,
Dimethyl Ether Dimethyl Ether		Guppy	Experimental	48 hours		>4,100 mg/l
	115-10-6	Water flea	Experimental		EC50	>4,400 mg/l
Isobutane	75-28-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2,6,6- Trimethylbicyclo[3 .1.1]hept-2-ene, polymer with 6,6- dimethyl-2- methylenebicyclo[3 .1.1]heptane	31393-98-3	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
2,6,6- Trimethylbicyclo[3 .1.1]hept-2-ene, polymer with 6,6- dimethyl-2- methylenebicyclo[3 .1.1]heptane	31393-98-3	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
2,6,6- Trimethylbicyclo[3 .1.1]hept-2-ene, polymer with 6,6- dimethyl-2- methylenebicyclo[3 .1.1]heptane	31393-98-3	Water flea	Endpoint not reached	21 days	EL10	>100 mg/l
Non-hazardous components	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Pentane	109-66-0	Green algae	Experimental	72 hours	EC50	10.7 mg/l
Pentane	109-66-0	Rainbow trout	Experimental	96 hours	LC50	4.26 mg/l
Pentane	109-66-0	Water flea	Experimental	48 hours	EC50	2.7 mg/l
Pentane	109-66-0	Green algae	Experimental	72 hours	NOEC	2.04 mg/l
Methyl acetate	79-20-9	Bacteria	Experimental	16 hours	EC50	6,000 mg/l
Methyl acetate	79-20-9	Green algae	Experimental	72 hours	ErC50	>120 mg/l
Methyl acetate	79-20-9	Water flea	Experimental	48 hours	EC50	1,026.7 mg/l
Methyl acetate	79-20-9	Green algae	Experimental	72 hours	NOEC	120 mg/l
Cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
Cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
2	64742-48-9	Fathead minnow	Estimated	96 hours	LL50	8.2 mg/l
	64742-48-9	Green algae	Estimated	72 hours	EL50	3.1 mg/l
Petroleum naphtha	64742-48-9	Water flea	Estimated	48 hours	EL50	4.5 mg/l
Petroleum naphtha	64742-48-9	Green algae	Estimated	72 hours	NOEL	0.5 mg/l
	64742-48-9	Water flea	Estimated	21 days	NOEL	2.6 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Loluene	100-00-5	Bacteria	Experimental	2-T 110413	12030	6
Toluene Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 %BOD/ThOD	OECD 301D - Closed bottle test
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Dimethyl Ether	115-10-6	Experimental Biodegradation	28 days	BOD	5 %BOD/ThOD	OECD 301D - Closed bottle test
Dimethyl Ether	115-10-6	Experimental Photolysis		Photolytic half-life (in air)	12.4 days (t 1/2)	
Isobutane	75-28-5	Experimental Photolysis		Photolytic half-life (in air)	13.4 days (t 1/2)	
2,6,6- Trimethylbicyclo[3 .1.1]hept-2-ene, polymer with 6,6- dimethyl-2- methylenebicyclo[3 .1.1]heptane	31393-98-3	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test
Non-hazardous components	Trade Secret	Data not available- insufficient	N/A	N/A	N/A	N/A
Pentane	109-66-0	Experimental Biodegradation	28 days	BOD	87 %BOD/ThOD	OECD 301F - Manometric respirometry
Pentane	109-66-0	Experimental Photolysis		Photolytic half-life (in air)	8.07 days (t 1/2)	
Methyl acetate	79-20-9	Experimental Biodegradation	28 days	BOD	70 %BOD/ThOD	OECD 301D - Closed bottle test
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 %BOD/ThOD	OECD 301F - Manometric respirometry
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.14 days (t 1/2)	
Petroleum naphtha	64742-48-9	Estimated Biodegradation	28 days	BOD	10 %BOD/ThOD	OECD 301D - Closed bottle test
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	
Acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	
Dimethyl Ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Isobutane	75-28-5	Experimental Bioconcentration		Log Kow	2.76	
2,6,6- Trimethylbicyclo[3 .1.1]hept-2-ene, polymer with 6,6- dimethyl-2- methylenebicyclo[3 .1.1]heptane	31393-98-3	Experimental Bioconcentration		Log Kow	7.41	
Non-hazardous components	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

Pentane	109-66-0	Estimated Bioconcentration		Bioaccumulation factor	26	
Methyl acetate	79-20-9	Experimental Bioconcentration		Log Kow	0.18	
Cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	129	OECD305-Bioconcentration
Petroleum naphtha	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1950 Proper shipping name: AEROSOLS Class/Division: 2.1 Sub Risk: Not applicable. Packing Group: Not applicable. Special Instructions: Limited quantity may apply Hazchem Code: 2YE IERG: 49

International Air Transport Association (IATA) - Air Transport UN No.: UN1950 Proper shipping name: AEROSOLS, FLAMMABLE Class/Division: 2.1 Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport UN No.: UN1950 Proper shipping name: AEROSOLS Class/Division: 2.1 Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable. Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au