Document Control

3M™ Tire Restorer

Data Sheet

3M Part No.(s) 3M Part Descriptor(s)

39042 16 ounce bottle with spray trigger

Detailed Product Description

3M[™] Tire Restorer restores a deep black, long-lasting, natural appearance to tires. Rejuvenates tires and avoids slinging.

Features, Advantages, Benefits

Features Advantages Benefits Fine mist sprayer

Natural shine is long lasting and avoids slinging

Typical Physical Properties

Container 16 ounce bottle with spray trigger

Color White emulsion

Flash Point N/A

Viscosity @ 72F, Shell cup #1 19-25 seconds

ConsistencyliquidpH7.0 - 8.0Weight per gallon8.2 - 8.6

Product Uses

3M[™] Tire Restorer is used to restore tires to a natural shine that is long lasting and avoids slinging, can also be used on moldings and rubber bumpers.

Performance Properties

Handling and Application Information

Directions for Use

- **Note: Remove overspray from wheels, hub caps or painted surfaces using a clean, soft, dry cloth.
- ** DO NOT USE on motorcycles, bicycles or other two-wheeled vehicles' tires or seats. Avoid spraying onto brake rotors or brake drums.

Tires

Printed 01/27/2010 Page 1

- 1. Spray a thin and uniform coating onto a clean and dry tire.
- 2. Wipe tire to ensure uniform application.
- 3. Allow dressing to dry before driving the vehicle.

Moldings and Rubber Bumpers

- 1. Spray onto a clean, soft, cotton terry cloth towel.
- 2. Wipe a thin and uniform coating onto a clean and dry molding or bumper.

Applications

3MTM Tire Restorer is recommended for use to restore natural shine to tires when detailing new or used vehicles.

Storage and Handling

Refer to Material Safety Data Sheet for storage and handling information.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product DO NOT USE on motorcycles, bicycles or other two-wheeled vehicles' tires or seats. Avoid spraying onto brake rotors or brake drums.

Warranty and Limited Remedy

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product

in a particular application Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating

the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

For Additional Health and Safety Information 3M Automotive Aftermarket Division 3M Center, Building 223-6N-01 Saint Paul, MN 55144-1000

Printed 01/27/2010 Page 2

3M™ Tire Restorer (BJLH-7YQMHG: Issue 1 - Active - Effective 01/25/2010)

1-877-666-2277 (1-877-MMM-CARS)

This is the last page

<< End of Document >>

Printed 01/27/2010 Page 3