

Seam Sealer and Coating Removal

1



Pre-Cleaning

Prewash/clean vehicle prior to disassembly (power wash undercarriage area at repair).

2



Method A

Use Scotch-Brite™ Clean and Strip Disc to remove seam sealer and coatings where accessible.

3



Method B

Use CRS Scotch-Brite™ Belt to remove coatings and seam sealers in hard to reach areas.

Visit 3MCollision.com for more SOPs and videos

Product List

Meguiar's® Shampoo Plus,
1 gallon, PN D11101



Meguiar's® Citrus Power
Cleaner Plus, 1 gallon,
PN D10701



Scotch-Brite™ Roloc™+
Clean and Strip XT
Pro Disc, PN 21552



Scotch-Brite™ Roloc™+
Clean and Strip XT
Pro Extra Cut Disc,
PN 21555



3M™ File Belt Sander,
18 in., PN 33575



Scotch-Brite™
Durable Flex Belt,
CRS, PN 64475



Think About Your Health

3M™ E-A-R™ Skull Screws™
Ear Plug, PN P1300



3M™ Half Facepiece
Respirator, PN 07182



3M™ Virtua™ Protective
Eyewear, PN 11326



Individual Product Instruction and Safety Information

For individual product instructions and applicable precautions see product labels and associated literature for the individual product at **3MCollision.com**

For product material safety data sheets see **3MCollision.com**

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Automotive Aftermarket Division
3M Center, Building 223-6S-07
St. Paul, MN 55144-1000
U.S.A.

3M, Accuspray, Cubitron, E-A-R, Hookit, Platinum, PPS, Rocker Gard, Roloc, Scotch, Scotchblok, Scotch-Brite, Skull Screws, Trizact and Virtua are trademarks of 3M Company.
All other trademarks are property of their respective owners.