








Anti-Chip Coating		
1		Pre-Cleaning Pre-wash/clean vehicle prior to disassembly (power wash undercarriage area at repair).
2		Removal of Heavy Surface Contaminates Clean to remove heavy contaminants from repair area.
3		OEM Coating Removal Remove OEM coating as needed using Scotch-Brite™ Clean N Strip disc. Featheredge using grade 80 abrasive on DA sander. Blow off surface with clean, dry air. Clean surface with 3M™ All Purpose Cleaner and Degreaser.
4		Filling/Leveling Surface Use polyester glaze to fill the repair area, bringing it the same level as the surrounding coating.
5		Sanding and Primer Sand glaze using P150 on a hand block. Final featheredge area using P320 abrasive on a DA sander. Blow off with clean, dry air. Final clean with VOC compliant wax and grease remover. Apply primer following paint company recommendations.
6		Sanding Primer Apply 3M™ Dry Guide Coat to primed surface. Sand primer using P320 on a DA sander with an interface pad. Blow off with clean, dry air. Final clean with VOC compliant wax and grease remover.
7		Masking Apply soft edge foam masking tape following existing coating edge. Final mask the area using tape and paper to protect from overspray.
8		Coating Test Panel Apply the coating to a test panel. Always apply a light coat first, allow it to flash, and adjust the spray equipment to deliver the texture required to match the OEM appearance.
9		Apply Coating Apply anti chip coating to the repair area using settings from test panel, blending the material into surrounding area as needed.
10		Blend Sanding Use P1000 3M™ Trizact™ Disc on a DA sander to smooth the blend edges. This operation produces a smooth transition without removing chip coating profile.

Visit www.3MCollision.com for more SOPs and videos

Product List

3M™ Car Wash Soap Concentrate, 1 gallon, PN 38377

3M™ All Purpose Cleaner and Degreaser Concentrate, 1 gallon, PN 38350

3M™ General Purpose Adhesive Cleaner, aerosol, PN 08987; Adhesive Remover, PN 38983

Scotch-Brite™ Roloc™+ Clean N Strip Disc, XT Disc, PN 07470; TR Disc, PN 07466

3M™ Cubitron™ II Clean Sanding Hookit™ Abrasive Disc, 6 in., 80+ grade, PN 31371

3M™ Platinum™ Plus Finishing Glaze, 30 oz., PN 31180; Glaze for DMS, PN 05862

3M™ Hookit™ Sanding Block Dust Free, 70mm x 127mm, PN 05207

3M™ Cubitron™ II Hookit™ Clean Sanding Sheet Roll, 70mm x 12m, 150+ grade, PN 34445;

3M™ Purple Clean Sanding Hookit™ Disc, 6 in., P320, PN 01812

3M™ Dry Guide Coat, 50 gram applicator kit, PN 05861

Festool D150 Thin Interface Pad, PN 29939

3M™ Soft Edge Foam Masking Tape PLUS, 21mm (.8 in.), PN 06293

3M™ Smooth Transition Tape, 1/4 in. (6.4mm), PN 06800

3M™ Scotchblok™ Masking Paper, 18 in. x 750 ft., PN 06718

Scotch® Performance Green Masking Tape 233+, width (.47 in.), PN 26332

3M™ Accuspray™ HGP Pressure Spray Gun, PN 16587

3M™ Rocker Protector Pouch, 3 ft. oz. (US), PN 08733; 5.5 ft. oz. (US), PN 08734

3M™ Waterbased Paintable Undercoating Pouch, 5.5 ft. oz. (US), PN 08744

3M™ Trizact™ Hookit™ Blending Disc, 6 in., P1000 grit, PN 02090

Think About Your Health

3M™ E-A-R™ Skull Screws™ Ear Plug, PN P1300

3M™ Respirator Assembly/Organic Vapor N95 Dual Cartridge, PN 07192

3M™ Lexa™ Protective Eyewear, PN 15200

Individual Product Instruction and Safety Information

For individual product instructions and applicable precautions see product labels and associated literature for the individual product at www.3MCollision.com

For product material safety data sheets see www.3MCollision.com

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

IMPORTANT NOTE: There are of course many factors and variables that can affect an individual repair, so the technician and repair facility need to evaluate each specific application and repair process, including relevant vehicle, part and OEM guidelines, and determine what is appropriate for that repair.



3M Automotive Aftermarket Division
3M Center, Building 223-6N-01
St. Paul, MN 55144-1000
U.S.A.

3M, Accuspray, Body Schutz, Cubitron, E-A-R, Green Corps, Hookit, Lexa, Perfect-It, Platinum, PPS, Roloc, Scotch, Scotchblok, Scotch-Brite, Skull Screws, SUN GUN and Trizact are trademarks of 3M. All other trademarks are property of their respective owners.

Web: www.3MCollision.com

Please recycle. Printed in U.S.A. © 3M 2016. All rights reserved. (Rev 5/2016)