

General Masking

1



Clean Area

Clean the area with water based cleaner. Wipe area with a VOC compliant solvent prep cleaner. Dry the area. The preferable surface temperature for masking is 60°–80°F.

2



Critical Edge Masking

Mask the areas that require fineline tape first. Mask the rest of the repair and backup the fineline with creped tape. Protect any nearby moldings with trim masking tape.

3



Overspray Protection

Ensure that the car is completely dry prior to applying plastic sheeting. Mask entire vehicle with plastic sheeting. Cut out the repair area with a razor blade. Tape the plastic sheeting directly to critical masking edge.

4



Masking Removal

After painting, remove the masking tape at a 90° angle to the vehicle's surface.

Visit 3MCollision.com for more SOPs and videos

Product List

Scotch® Performance Green Masking Tape 233+, 18mm x 55m (3/4 in. applications), PN 26334; 36mm x 55m (1-1/2 in. applications), PN 26338; 48mm x 55m (2 in. applications), PN 26340



3M™ Vinyl Tape 471+, 1/4 in. width (6.4mm), PN 06405



3M™ Perforated Trim Masking Tape, 5mm, PN 06345; 7mm, PN 06347; 10mm, PN 06349; 15mm, PN 06348



3M™ Overspray Protective Sheeting, 12 ft. x 400 ft. roll, PN 06727; 16 ft. x 350 ft. roll, PN 06728; 20 ft. x 250 ft. roll, PN 06742



Think About Your Health

3M™ E-A-R™ Skull Screws™ Ear Plug, PN P1300



3M™ Half Facepiece Respirator, PN 07182



3M™ Virtua™ Protective Eyewear, PN 11326



Individual Product Instruction and Safety Information

For individual product instructions and applicable precautions see product labels and associated literature for the individual product at **3MCollision.com**

For product material safety data sheets see **3MCollision.com**

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Automotive Aftermarket Division
3M Center, Building 223-6S-07
St. Paul, MN 55144-1000
U.S.A.

3M, Accuspray, Cubitron, E-A-R, Hookit, Perfect-It, Platinum, PPS, Roloc, Scotch, Scotchblok, Scotch-Brite, Skull Screws, SUN GUN, Trizact, Versaflo and Virtua are trademarks of 3M. All other trademarks are property of their respective owners.