





Paint Finish Full Panel Process		
1		<p>Initial Defect Removal Texture Match</p> <p>DA sand the repair area with a P1500/P2000 3M™ Purple Finishing Film Hookit™ Disc or P1500 3M™ Trizact™ Clearcoat Sanding Disc used damp. Remove all paint defects and match texture to adjacent OEM panels. Wipe panel clean.</p>
2		<p>Scratch Refinement 3000</p> <p>Refine the P1500/P2000 scratches with a DA and a 3000 3M™ Trizact™ Hookit™ Foam Disc used damp with a 3M™ Hookit™ Soft Interface Pad. Wipe panel clean.</p>
3		<p>Scratch Refinement 5000 (Optional)</p> <p>To reduce your buffing time refine the 3000 scratches with a DA and a 5000 grit 3M™ Trizact™ Hookit™ Foam Disc used damp with a 3M™ Hookit™ Soft Interface Pad. Wipe panel clean. The use of 3000 is required prior to 5000 for best results.</p>
4		<p>Compound</p> <p>Compound the repair area with a high speed polisher set between 1200–2000 RPM. For faster results, use a foam compounding pad and the appropriate rubbing compound. To insure all sand scratches have been removed, inspect the surface by spraying with an Inspection Spray and wipe clean with a yellow microfiber cloth.</p>
5		<p>Machine Polish</p> <p>Polish the repair area with a high speed polisher set between 1200–2000 RPM. Use a black foam polishing pad and the appropriate machine polish. Wipe the panel clean with a yellow microfiber cloth.</p>
6		<p>Ultrafine Machine Polish</p> <p>Polish the repair area with a high speed polisher with the speed set between 1200–2000 RPM. Use a blue foam polishing pad and the appropriate ultrafine machine polish. Leave a light film of the polish on the panel and wipe clean with a blue microfiber cloth.</p>
7		<p>Final Detail</p> <p>Remove any masking material from the repair area and clean any residual sling from adjacent panels and door jamb areas. Cleaning the panel immediately after compounding and polishing will greatly improve the ease of cleaning. Inspect the surface using the 3M™ SUN GUN™ II Light Kit.</p>

Visit www.3MCollision.com for more SOPs and videos

Product List

- 3M™ Purple Finishing Film Hookit™ Disc, 6 in., P1500, PN 30667; P2000, PN 30666 
- 3M™ Trizact™ Hookit™ Clearcoat Sanding Disc, 6 in., P1500, PN 02088 
- Festool D150 Thin Interface Pad, PN 29939 
- 3M™ Trizact™ Hookit™ Foam Disc, 6 in., 3000, PN 02085; 6 in., 5000 grit, PN 30662 
- 3M™ Perfect-It™ EX Rubbing Compound, 1 qt., PN 36060 
- 3M™ Perfect-It™ Foam Compounding Pad, Double Sided, Quick Connect, 9 in., PN 05706 
- 3M™ Perfect-It™ Low Linting 100% Wool Compound Pad, Double Sided, Quick Connect, PN 33279 
- 3M™ Quick Connect Adaptor, 14mm. Thread, PN 33271 
- 3M™ Perfect-It™ EX Machine Polish, 1 qt., PN 06094 
- 3M™ Perfect-It™ Foam Polishing Pad, Double Sided, Quick Connect, 9 in., PN 05707 
- 3M™ Inspection Spray, 1 gallon, PN 06082 
- 3M™ Perfect-It™ EX Ultrafine Machine Polish, 1 qt., PN 06068 
- 3M™ Perfect-It™ Ultrafine Foam Polishing Pad, Double Sided, Quick Connect, 9 in., PN 05708 
- 3M™ Perfect-It™ Detail Cloth, PN 06016; PN 06020 
- 3M™ SUN GUN™ II Light Kit, PN 16550 
- 3M™ Perfect-It™ Clean and Shine, 16 fl. oz. bottle, PN 06084 

Think About Your Health

- 3M™ E-A-R™ Skull Screws™ Ear Plug, PN P1300 
- 3M™ Particulate Respirator N95, PN 07185 
- 3M™ Lexa™ Protective Eyewear, PN 15200 

Individual Product Instruction and Safety Information

For individual product instructions and applicable precautions see product labels and associated literature for the individual product at www.3MCollision.com

For product material safety data sheets see www.3MCollision.com

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



**3M Automotive
Aftermarket Division**
3M Center
Building 223-6N-01
St. Paul, MN 55144-1000
U.S.A.
www.3MCollision.com

Please recycle. Printed in U.S.A.
© 3M 2015. All rights reserved.
(Rev 9/2015)

3M, Accuspray, Body Schutz, Cubitron, E-A-R, Hookit, Lexa, Platinum, PPS, Rocker Gard, Roloc, Scotch, Scotchblok, ScotchBlue, Scotch-Brite, Skull Screws and Trizact are trademarks of 3M Company