# **Standard Operating Procedures Sealing and Coating**

**Product List** 

# Pre-Made LASD Replacement (Off Body)

#### **Pre-Cleaning**

Pre-wash/clean vehicle prior to disassembly (power wash undercarriage area at repair).

### LASD Removal

Remove sound deadening material from affected repair area using a scraper or chisel. Blow off area with compressed air and clean with APCD.

## Pre-Make Patch

Apply packaging tape to smooth bench top surface as a release liner. Mask out desired patch size and shape over the top of packaging tape.

#### Pre-Make Patch

Dispense seam sealer material onto prepared surface.

#### **Pre-Make Patch**

Re-create desired appearance and texture of NVH material using tools of the trade (e.g., brushes, scuff pads, compressed air, etc.). Remove perimeter masking following the tooling process and prior to final cure.


#### Surface Prep

Scuff surface with a maroon Scotch-Brite<sup>™</sup> hand pad. Blow off area with compressed air and clean with APCD.

#### Install Replica (on body)

After material cures, remove the LASD replica from the release liner, scuff with maroon Scotch-Brite<sup>™</sup> hand pad, apply NVH material to the bottom of the replica. Bond in place at the correct location.

Visit 3MCollision.com for more SOPs and videos





Scotch<sup>®</sup> Performance Green Masking Tape 233+ 18mm x 55m (.75 in.), PN 26334



3M<sup>™</sup> Heavy-Bodied Seam Sealer, 200mL, PN 08308; 600mL DMS, PN 58308

3M<sup>™</sup> NVH Dampening

Material, PN 04274

Scotch-Brite<sup>™</sup> Durable Flex Hand Pad, MX-HP, Very Fine, 4-1/2 in. x 9 in., PN 64659



Scotch-Brite<sup>™</sup> 7447 PRO Hand Pads, Very Fine, 6 in. x 9 in., PN 64926

3M<sup>™</sup> Performance Manual Applicator. 200mL, PN 08117



3M<sup>™</sup> Dynamic Mixing Applicator — Pneumatic. PN 05846

## **Think About Your Health**

3M<sup>™</sup> E-A-R<sup>™</sup> Skull Screws<sup>™</sup> Ear Plug, PN P1300

3M<sup>™</sup> Respirator Assembly/ Organic Vapor N95 Dual Cartridge, PN 07192



Note: Pre-made LASD replacement patches are typically created off body for panels with complex surfaces.

# Individual Product Instruction and Safety Information

For individual product instructions and applicable precautions see product labels and associated literature for the individual product at **3MCollision.com** 

For product material safety data sheets see 3MCollision.com

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Automotive Aftermarket Division 3M Center, Building 223-6S-07 St. Paul, MN 55144-1000 U.S.A.

Web 3MCollision.com

3M, Accuspray, Cubitron, E-A-R, Hookit, Perfect-It, Platinum, PPS, Roloc, Scotch, Scotchblok, Scotch-Brite, Skull Screws, SUN GUN, Trizact, Versaflo and Virtua are trademarks of 3M. All other trademarks are property of their respective owners.