3M Venture Tape[™] Line Set Tape 1507 & Venture Tape[™] Reflective Insulation Seaming Tape 1507


Technical Data					January, 2017	
Product Description	3M [™] Venture Tape [™] Line Set Tape 1507 and 3M [™] Venture Tape [™] Reflective Insulation Seaming Tape 1507 are a bi-axially oriented polypropylene (BOPP) tape coated with a cold weather solvent ac adhesive.					
Product Construction	Backing	Adhesive	Color		Standard Roll Length	
	Polypropylene (BOPP)	Acrylic	in White Reflectiv	Tape available or Black. e Insulation Tape available in	60 yds (55 m)	
Features	 UL 723 Classified [0/0 Flame/Smoke Rating] (ULC File# R10984) Strong, weatherproof and UV resistant 					
	 Applies easily at cold temperatures Linerless and self-wound for easy application					
Typical Physical Properties	Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.					
	Test	T	ypical Value	Typical Value (Metr	ic) Test Method	
	Total Tape Thi	ckness	3.0 mils	0.08 mm	ASTM-D3652	
	De alvin a Thialun	ess	1.6 mils	0.04 mm	ASTM-D3652	
	Backing Thickn					
	Peel Adhesion		34 oz/in	9 N/25 mm	ASTM-D3330	
	-	۱	34 oz/in 38 lb/in	9 N/25 mm 169 N/25 mm	ASTM-D3330 ASTM-D3759	

Application Ideas

- Taping line sets
- Foam pipe insulation used in line sets

3M[™] Venture Tape[™] Line Set Tape 1507 & 3M[™] Venture Tape[™] Reflective Insulation Seaming Tape 1507

Storage	Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended.
Shelf Life	To obtain best performance, use this product within 24 months from date of manufacture
Technical Information	The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.
Product Selection and Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.
Warranty, Limited Remedy, and Disclaimer	Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability	Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.
	[ISO 9001]
	This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards



3M Center, Building 225-3S-06 St. Paul, MN 55144-1000 800-362-3550 • 877-369-2923 (Fax) www.3M.com/construction