


3M™ Sun Control Window Film Prestige 50

Clearly superior.

Benefits

- ▶ High visible light transmission providing excellent aesthetics
- ▶ Patented design that significantly reflects the sun's energy in the Infrared range providing energy savings and enhanced comfort
- ▶ Low interior and exterior reflectivity enhances views while maintaining exterior appearance
- ▶ Non-metalized film with no signal interference and no chance for corrosion
- ▶ Helps extend the life of furnishings by significantly reducing harmful UV rays, the largest cause of fading
- ▶ Comprehensive warranty from 3M



3M
 Commercial Solutions Division
 3M Center, Building 235-2S-27
 St. Paul, MN 55144-1000
 3M.com/WindowFilm
 3M is a trademark of 3M Company.
 Used under license by 3M subsidiaries
 and affiliates. Please recycle.
 Printed in the U.S.A. © 3M 2022.
 All rights reserved. 98-0150-0767-1

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

LEED Certification
 Window films may be used toward the following LEED credits:

◀ SS-8	▶ EA-1
▶ MR 1.1-1.2	▶ EQ-7.1
▶ MR 5.1-5.2	▶ EQ-7.2
▶ EQ-8.1-8.2	▶ ID

Product Performance and Technical Data

Glass Type (All 1/4")	Film Type	Visible Light			Total Solar Energy Rejected 60 degree angle	Solar Heat Gain Coefficient (G Value)	Solar Heat Reduction		UV Light Rejected	Clare Reduction to Solar Heat Gain Ratio	
		Reflected (Interior)	Reflected (exterior)	Transmitted			U Value	W/m ²			
Clear	PR50	7%	8%	50%	0.44	0.99	5.6	46%	99.9%	44%	1.1
Double Tinted	PR50	6%	15%	30%	0.39	0.99	5.6	38%	99.9%	43%	0.8
Double Clear	PR50	9%	45%	47%	0.53	0.47	2.7	25%	99.9%	44%	0.8
Double Tinted	PR50	9%	27%	60%	0.40	0.47	2.7	22%	99.9%	44%	0.7