



Scotch™ Carry Handle Tape 8347 HP

Product Data Sheet

May 2022
Supersedes: October 2009

Product Description

8347 HP is a high performance tape featuring a durable ScotchPro™ film backing that is very strong in longitudinal direction and an aggressive hot melt solvent-free adhesive. The adhesive is specifically formulated to be suitable for high shear performance carrying tape handles. This high performing tape gives excellent adhesion to most plastic overwraps. It can be efficiently applied on automatic handle equipment and its availability in long yardage rolls and roll end indicator 15 m before end of roll increases productivity.

Key Features

The ScotchPro™ polypropylene backing provides excellent abrasion, moisture and scuff resistance. The adhesive is specially formulated to provide good adhesion to fibreboard surfaces.

Construction

Adhesive Type	Rubber Resin (Hot Melt)
Backing	MOPP
Total Thickness AFERA 5006	65 µm
Colour	Transparent

Performance Characteristics

Adhesion to Stainless Steel AFERA 5001	5,5 N/cm
Tensile Strength AFERA 5004	180 N/cm
Elongation at Break AFERA 5004	27 %
Static Shear AFERA 5012	4500+ minutes

Storage & Shelf Life

Store at 16 °C – 25 °C and 40 - 65 % relative humidity in its original box.
The product can be stored up to 18 months after production.

Note: The shelf life may be shortened if the original packaging is not properly sealed or stored in an environment with high temperatures or humidity

For Additional Information

To request additional product information, see address below.

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application.

All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.

3M United Kingdom Plc
3M Centre
Cain Road
Bracknell
Berkshire
RG12 8HT

3M Ireland Limited
The Iveagh Building
The Park
Carrickmines
Dublin 18
Ireland