



Installation and Use Instructions for Python Safety Tool Pouches

This manual is intended to be used as part of an employee training program. These products are not to be used for worker fall protection.



Model #	Width	Height	Retractors/Triggers
1500124	7.5 in (19.1cm)	11 in (27.9cm)	
1500125	7.5 in (19.1cm)	11 in (27.9cm)	2 Retractors
1500126	7.5 in (19.1cm)	11 in (27.9cm)	2 Triggers
1500127	8.75 in (22.2cm)	13 in (33.0cm)	
1500128	8.75 in (22.2cm)	13 in (33.0cm)	2 Retractors
1500129	8.75 in (22.2cm)	13 in (33.0cm)	2 Triggers

www.capitalsafety.com

Form: 5903842-A3 Rev: A © Copyright 2015, DB Industries, Inc.



EN Python Safety Tool Pouches

- Provide positive control of tools while working at height.
- Worn on user's belt. Standard and extra-deep models.
- Heavy-duty canvas exterior, inner lining prevents punctures.
- Inner pockets store tools. Tools up to 5 lb (2.3kg) can be tethered on D-Rings.
- Some models include Python Safety Retractors or Triggers to tether tools (see cover page for models).
- Standard sized pouch has lockable hook and loop closure system.
- Extra-deep tool pouch has magnetic closure system. Side-release buckle prevents pouch from accidentally opening during transport.

✓ When to use Tool Pouches

- For tool storage and for tethering of tools up to 5 lb. (2.3 kg).

✗ When NOT to use Tool Pouches

- Tethering of tools that exceed 5 lb (2.3 kg).

Warnings

- All warnings, warning labels and instructions should be read and understood before using this product. Failure to do so may result in property damage, serious injury or death.
- All procedures shown in this instruction are for Python Safety products only.
- Python Safety attachment points require the use of an appropriate Python Safety Lanyard, Tether or Retractor for safe connection of the tool or equipment to another Python attachment point, the user or an anchorage. See specific Python Safety instructions for product installation, connection and use procedures.
- Do not use for worker fall protection or for climbing.
- Do not use if fall protection for tool components will interfere with the safe working condition or operation of the connected tool or equipment.
- If a tool is dropped or a load is forced onto the connection point, **inspect the tool and fall protection for tool components connected to the tool for damage.** This includes the attachment point, the lanyard and the anchor point. (Anchor point examples: tool holster, tool belt, tool bag, worker safety harness or anchor point such as a rail.) Look for torn stitching and for deformities and damage to any material. If damage is found, remove the affected items from service immediately and replace them.
- Inspect before, during, and after use to ensure fall protection for tool components are in good working condition and free from defects, cuts, tears, etc. See "Inspect Before Use" in this instruction manual. Never modify Python Safety products.
- Never exceed the maximum load rating stated on the Python Safety product label.
- Never connect individual tools that weigh more than 5 pounds (2.26 kg) to a person.
- Never attach tool lanyards or attachment points to a tapered surface.
- Never wrap fall protection for tool components around rough or sharp edges.
- Never attach multiple fall protection for tool components together (daisy chain).
- Never make a modification to a connected tool or equipment that will cause it to deviate from the manufacturer's specification.
- Always use proper personal protective equipment (PPE).
- Use extreme caution while working around rotating or moving equipment.
- To avoid the danger of electrical shock, use extreme caution when working around power equipment and connections.
- Read and understand product information and warning labels for all connecting lanyards and adapters.
- All connected tools and equipment must be properly maintained and inspected for defects or deterioration before each use.

Inspect Before Use

Python Safety equipment and components must be thoroughly inspected before, during and after each use. Any fall protection for tools component that has deformities, unusual wear or deterioration must be immediately removed from service and replaced. Inspect the entire surface of the component, carefully rotating it while visually inspecting for damage or wear that might affect its usefulness and dependability. Inspect material and stitching, hardware, D-Rings and fasteners. Confirm that carabiners, trigger snaps, retractors and other connectors operate properly.

Tool Pouch Use (Figures 1 - 5):

1. Insert user's belt through the Tool Pouch loops.
2. Use multiple interior pockets to hold a variety of tools. Use interior and exterior D-rings with Python Safety Tethers to tether tools.
3. Where included, use Triggers to secure tools. Pull down on the trigger to open the dual-hooked connector, then release when connected to a tool.
4. Where included, use Python Safety Retractors to tether tools. Attach tool to the Retractor connection ring. Tool weight must not exceed 1.5 lbs (0.7 kg) when connected to the Retractor.
5. Use the lockable hook and loop closure system (a, standard size Tool Pouch) or magnetic closure system and side-release buckle (b, extra deep Tool Pouch) to secure contents.

After Use

After use, clean the Tool Pouch and connected tool or equipment to remove dirt, corrosives or contaminants. Remove surface dirt with a wipe that has been moistened with a mild solution of water and soap or detergent. Work into a thick lather and clean the item. Wipe with a clean cloth and hang to dry away from excessive heat, steam, or sunlight.

Store in a clean and dry environment, free from fumes or corrosive elements. Proper care of safety equipment helps to ensure that it will operate effectively and to extend its service life.

In Case of a Dropped Tool

- If a tool is dropped or a load is forced onto the connection point, **inspect the tool and fall protection for tool components connected to the tool for damage.** This includes the attachment point, the lanyard and the anchor point. (Anchor point examples: tool holster, tool belt, tool bag, worker safety harness or anchor point such as a rail.) Look for torn stitching and for deformities and damage to any material. If damage is found, remove the affected items from service immediately and replace them.
- Incidents should be reported to your safety coordinator.

