



Installation and Use Instructions for Python Safety Adjustable Radio Holster

This manual is intended to be used as part of an employee training program. These products are not to be used for worker fall protection.



Model #	
1500088	Adjustable Radio Holster
1500089	Adjustable Radio Holster, Clip2Loop Coil Tether and Micro D-Ring

www.capitalsafety.com

Form: 5903849-A3 Rev: A © Copyright 2015, DB Industries, Inc.

EN Python Safety Adjustable Radio Holster

- ✓ **When to use the Adjustable Radio Holster:**
 - Holds most small portable radios as well as other small devices such as cell phones and cameras while working at height.
 - Can be worn from user's belt or safety harness.
 - Model 1500089 includes a Micro D-Ring and Clip2Loop Coil Tether. The Micro D-Ring can be attached to the back of a device weighing 2 lbs (2.3 kg) or less. The device can then be tethered to a D-Ring on the front of the Adjustable Radio Holster with the included Clip2Loop Coil Tether.

- ✗ **When NOT to use an Adjustable Radio Holster:**
 - On tools or devices that weigh more than 2 lbs (2.3 kg).

Warnings

- All warnings, warning labels and instructions should be read and understood before using this product. Failure to do so may result in property damage, serious injury or death.
- All procedures shown in this instruction are for Python Safety products only.
- Python Safety attachment points require the use of an appropriate Python Safety Lanyard, Tether or Retractor for safe connection of the tool or equipment to another Python attachment point, the user or an anchorage. See specific Python Safety instructions for product installation, connection and use procedures.
- **Do not use for worker fall protection** or for climbing.
- Do not use if fall protection for tool components will interfere with the safe working condition or operation of the connected tool or equipment.
- If a tool is dropped or a load is forced onto the connection point, **inspect the tool and fall protection for tool components connected to the tool for damage.** This includes the attachment point, the lanyard and the anchor point. (Anchor point examples: tool holster, tool belt, tool bag, worker safety harness or anchor point such as a rail.) Look for torn stitching and for deformities and damage to any material. If damage is found, remove the affected items from service immediately and replace them.
- Inspect before, during, and after use to ensure fall protection for tool components are in good working condition and free from defects, cuts, tears, etc. See "Inspect Before Use" in this instruction manual. Never modify Python Safety products.
- Never exceed the maximum load rating stated on the Python Safety product label.
- Never connect individual tools that weigh more than 5 pounds (2.26 kg) to a person.
- Never attach tool lanyards or attachment points to a tapered surface.
- Never wrap fall protection for tool components around rough or sharp edges.
- Never attach multiple fall protection for tool components together (daisy chain).
- Never make a modification to a connected tool or equipment that will cause it to deviate from the manufacturer's specification.
- Always use proper personal protective equipment (PPE).
- Use extreme caution while working around rotating or moving equipment.
- To avoid the danger of electrical shock, use extreme caution when working around power equipment and connections.
- Read and understand product information and warning labels for all connecting lanyards and adapters.
- All connected tools and equipment must be properly maintained and inspected for defects or deterioration before each use.

Inspect Before Use

Python Safety equipment and components must be thoroughly inspected before, during and after each use. Any fall protection for tools component that has deformities, unusual wear or deterioration must be immediately removed from service and replaced. Inspect the entire surface of the component, carefully rotating it while visually inspecting for damage or wear that might affect its usefulness and dependability. Inspect material and stitching, hardware, D-Rings and fasteners. Confirm that carabiners, trigger snaps, retractors and other connectors operate properly.

Attachment to Belt or Harness:

Mounting system quickly attaches the Radio Holster to harnesses or tool belts.

1. Belt attachment: Insert user's belt through the Radio Holster belt loop.
2. Harness attachment: Wrap hook and loop straps around harness straps. Press straps together to secure Radio Holster to harness.
3. Connect radio's tether to the sewn-in D-Ring on the Radio Holster.
4. Insert radio or other device in the Radio Holster and secure the device in the Holster with the ergonomic cord lock.

Attachment to Python Micro D-Ring and Clip2Loop Tether

Model 1500089 includes a Micro D-Ring and Clip2Loop Tether.

5. Remove the adhesive backer from the Micro D-Ring and apply to the radio or other device surface. Hold the Micro D-Ring in place until the adhesive is firmly attached to the device.
6. Connect the Clip2Loop Tether to the Micro D-Ring. Insert the device in the Radio Holster and connect the Tether to the sewn-in D-Ring on the Radio Holster.

After Use

After use, clean the Holster and connected tool or equipment to remove dirt, corrosives or contaminants. Remove surface dirt with a wipe that has been moistened with a mild solution of water and soap or detergent. Work into a thick lather and clean the item. Wipe with a clean cloth and hang to dry away from excessive heat, steam, or sunlight.

Store in a clean and dry environment, free from fumes or corrosive elements. Proper care of safety equipment helps to ensure that it will operate effectively and to extend its service life.

In Case of a Dropped Tool

- If a tool is dropped or a load is forced onto the connection point, **inspect the tool and fall protection for tool components connected to the tool for damage.** This includes the attachment point, the lanyard and the anchor point. (Anchor point examples: tool holster, tool belt, tool bag, worker safety harness or anchor point such as a rail.) Look for torn stitching and for deformities and damage to any material. If damage is found, remove the affected items from service immediately and replace them.
- Incidents should be reported to your safety coordinator.



