

Commercial Solutions Division

# 3M™ Décor Overlaminates

## Series 8600M

### Product Description

3M™ Décor Overlaminates Series 8600M is designed to add texture to graphic films to be installed on smooth, interior walls. 3M recommends using 3M™ Print Wrap Film IJ180mC-10 and 3M™ Print Wrap Film IJ180mC-120 as base films.

#### Product Line

- 8600M-101 Classic Linen gives the underlying film/graphic a uniform pattern of linen.
- 8600M-102 Knit gives the underlying film/graphic the texture of fabrics.
- 8600M-201 White Fir gives the underlying film/graphic a deep woodgrain texture.
- 8600M-301 Riverbed gives the underlying film/graphic a versatile stone texture.
- 8600M-401 Plaster gives the underlying film/graphic a subtle leather texture.

#### Important Notice

This product is intended to be used for lamination over another film substrate. It has a permanent adhesive, if applied directly to substrate it will cause damage and removal will most likely leave a large amount of adhesive behind.

### Product Characteristics

These are indicative values for unprocessed products. Contact your 3M representative for a custom specification

#### Physical & Application

Material	cast vinyl
Surface finish	textured surface, matte
Thickness (film)	8600M-101: 89 µm (0.089 mm) All other: 64 µm (0.064 mm)
Adhesive type	acrylic, pressure sensitive, permanent

Adhesive appearance	Clear
Liner	Kraft paper
Lamination temperature	+15°C to +38°C
Service temperature	-54°C to +66°C

The values above are the results of illustrative lab test measurements and shall not be considered as commitment from 3M.

Storage	Shelf life	Use within two years from the date of manufacture on the sealed original box. Use within one year after opening the box
	Storage conditions	+4°C to +40°C, out of sunlight, original container in clean and dry area. Bring the overlaminate to room temperature before use.

The shelf life as defined above remains an indicative and maximum data, subject to many external and non-controllable factors. It may never be interpreted as warranty.

Flammability	Flammability standards are different from country to country. Ask your local 3M contact for details, please.
--------------	--

- Durability** The durability of products is influenced by:
- the combinations of graphics materials used
  - complete ink drying or curing
  - selection, condition and preparation of the substrate
  - surface texture
  - angle and direction of sun exposure
  - application procedures
  - environmental factors
  - the method and the frequency of cleaning

**MCS™ Warranty** 3M provides a warranty on a finished applied graphic within the framework of 3M™ MCS™ warranty programs.

For detailed graphic construction and application options along with specific Warranty periods, please see the Warranty matrices and Warranty information on 3M Graphic Solutions/Warranties.

Visit [www.3mgraphics.com/eu](http://www.3mgraphics.com/eu) for getting more details about 3M's comprehensive graphic solutions.

## Limitations of End Uses

3M specifically does not recommend or warrant the following uses, but please contact us to discuss your needs to recommend other products.

- Not for applications to substrates other than graphic films.
- Not for applications to substrate surface shapes other than specified in this section or recommended in the product bulletin of the base film used for graphic construction.
- Do not print on overlaminates.
- 3M Commercial Solutions Division products are not tested against automotive manufacturer specifications!
- Non vertical applications will have a significant decrease in durability.
- Do not use on textured films.

## Graphics Manufacturing

Use these products to enhance the appearance of printed graphics or colored films.

### Shipping Finished Graphics

Flat, or rolled film side out on 130 mm (5 inch) or larger core. These methods help to prevent the liner from wrinkling or application tape, if used, from popping off.

## Application

See product bulletin ATR 'application tape recommendations' for information about selection and use of suitable application tapes for this product, please.

[> Product Bulletin Application Tape Recommendations <](#)

Refer to Instruction Bulletin 5.1 'select and prepare substrates for graphic application', for general application information.

[> Instruction Bulletin 5.1 'select and prepare substrates for graphic application' <](#)

### Important notice

Stretching of graphics should be avoided in order to avoid shrinkage.

It is recommended to apply 8600M series in same direction on visually adjacent walls.

## Maintenance and Cleaning

Use a cleaner designed for high-quality painted surfaces. The cleaner must be wet, non-abrasive, without strong solvents, and have a pH value between 3 and 11 (neither strongly acidic nor strongly alkaline).

Refer to Instruction Bulletin 6.5 'storage, handling, maintenance and removal of films and sheetings', for general maintenance and cleaning information.

[> Instruction Bulletin 6.5 'Storage, Handling, Maintenance and Removal of Films and Sheetings' <](#)

## Remarks

This bulletin provides technical information only.

### Important Notice

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law. Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

### Additional Information

Visit the web site [www.3mgraphics.com/eu](http://www.3mgraphics.com/eu) for getting:

- additional instruction bulletins
- a complete product overview about materials 3M is offering.

Responsible for this technical product bulletin

3M Deutschland GmbH  
Safety & Graphics Laboratory  
Carl-Schurz-Str. 1  
41453 Neuss, Deutschland

3M, Controltac, Comply, Envision, Fasara, Panagraphics, Scotchcal, and MCS are trademarks of 3M Company. All other trademarks are the property of their respective owners.

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.



### Commercial Solutions Division

Hermeslaan 7  
1831 Diegem, Belgium  
[www.3mgraphics.com/eu](http://www.3mgraphics.com/eu)

© 3M 2017  
All rights reserved.