



Automotive Aftermarket Division

3M™ 401Q Wetordry™ Paper

1) Part Numbers

09546 - P2000
09545 - P1500

2) Description and end uses

A premium wet sanding product producing a consistent fine finish.

3) Physical Properties

230 mm x 138 mm sheets

Grit range: P1500-P2000

Backing : 115 gsm latex impregnated waterproof paper

Mineral : Silicon Carbide

Coating : Closed Coat

Bonding : Resinbond

Features	Advantages	Benefits
High quality backing	Flexible and conformable	Good handling with max performance
Silicon Carbide mineral	Fast initial cut	Defect removed and finish achieved quickly
P-graded	Uniform finish	Consistent high-quality finish

4) Directions for Use

Nib and defect removal on painted panels and other synthetic materials where a fine consistent finish is required.



Technical Data Sheet

Effective: 18/08/2020 Supersedes: 15/06/2006

5) Storage

It is recommended that all Coated Abrasive products should be stored at constant levels of temperature and humidity within the ranges of 18-22°C, 50-65% RH. They should be kept away from damp (or cold) walls, windows or floors to avoid possible absorption. Equally storage adjacent to heat sources, e.g. steam pipes, radiators, hot air ducts, ovens, etc, should be avoided.

Product is best stored in original packaging until ready for use. Shelf life indefinite under these conditions.

6) Safety

Use product in accordance with normal wet sanding.

Whenever possible, sanding should be carried out in a well-ventilated area and it is strongly recommended that suitable goggles, dust mask and gloves are worn.

3M™ 401Q Wetordry™ Paper is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.



Technical Data Sheet

Effective: 18/08/2020 Supersedes: 15/06/2006

For Additional Health and Safety Information

<p>3M United Kingdom plc Automotive Aftermarket 3M Centre, Cain Road, Bracknell, RG12 8HT Tel: +44 (0)161 237 6391 aadukenquiries@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Ireland Limited Automotive Aftermarket The Iveagh Building Carrickmines Park Carrickmines , Dublin 18 Tel: +353 12160301 aadukenquiries@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Denmark a/s Automotive Aftermarket Hannemanns Allé 53 2300 København S Tel: +45 43480100 aadukenquiries@mmm.com www.3MAuto.dk</p>
<p>3M Finland, Suomen 3M Oy Automotive Aftermarket Keilaranta 6 02150 Espoo Tel: 09 5252 1 aadukenquiries@mmm.com www.3M.fi/autotuotteet</p>	<p>3M Svenska AB Automotive Aftermarket Herrjärva torg 4 170 67 Solna Tel: 08-922100 aadukenquiries@mmm.com www.3M.se/bileftermarkad</p>	<p>3M Norge AS Automotive Aftermarket Kanalveien 2 2004 Lillestrøm Tel: 06384 aadukenquiries@mmm.com www.3m.no/auto</p>
<p>3M Latvija K.Ulmana 5 Riga, LV-1004 Tel: +371 67066120 aadukenquiries@mmm.com www.3m.lv</p>	<p>3M Eesti OU Pärnu mnt. 158 11317 Tallinn Tel: +372 6 115 902 aadukenquiries@mmm.com www.3m.ee</p>	<p>3M Lietuva A.Goštauto str. 40 A LT-01112 Vilnius Tel: +370 5 2160780 aadukenquiries@mmm.com www.3m.lt</p>

© 3M 2020. 3M and Wetordry are trademarks of the 3M company. All rights reserved