



Automotive Aftermarket Division

3M™ 443SA Trizact™ Blending Discs

1) Part Numbers

50341- 150 mm discs
50413 - 75mm discs

2) Description and end uses

3M 443SA Trizact™ Blending Discs are revolutionary structured abrasives for use keying paint for the preparation of paint prior to the blending process. The discs have pyramid or triangular block structures which contain multiple layers of fine grade abrasive mineral. As the abrasive wears, sharp mineral is continuously exposed. The result is a consistent smooth finish and exceptional life. The finish obtained is approx. 2 microns, allowing paint to adhere to the keyed surface without scratches showing through.

Application areas

- 1) Preparation of clear coat around a repair for large areas by machine and smaller areas by hand.
- 2) Keying of awkward areas and bumpers by hand.
- 3) For use in polishing applications as a large area flattening product before use of P3000 Trizact™.
- 4) For hand use to denib base coat imperfections in the painting process when after application of base coat imperfections need removing.

3) Physical Properties

Foam backed abrasive disc with Hookit™ facing in 150 mm diameter.

Use with a Hookit™ pad for machine application or for hand applications the full size Hookit™ or half round hand pads.

Product highlights:

- 2 micron finish
- Foam backing conforms to texture or orange peel without removing the original texture
- Structured abrasive provides consistent uniform finish



Technical Data Sheet

Effective: 31/07/2019 Supersedes: 08/02/2010

- Excellent life seen-often product will sand several panels
- Eliminates rework caused by incorrectly prepared panels

4) Directions for Use

- For machine use-use a fine action D/A sander (5 or 3 mm orbit) fitted with a soft Hookit™ back-up pad.
- Use a soft interface pad (PN 05774) to allow more even matting.
- Use with a little water wetting the area with a pump spray bottle, also wet the disc face. The disc should not be allowed to run dry.
- Do not use solvent or water-based degreaser.
- Do not leave soaking in water bucket.
- Using medium pressure sand over the area to matt the surface.
- Seeing if complete matting has taken place can only be seen by cleaning and drying the surface.
- For Hand use- assisted by use of either interface pad part nos. 05791/05792
- Again use damp, matting surface with even pressure.

5) Storage

It is recommended that all Coated Abrasive Products should be stored at constant levels of temperature and humidity within the ranges of 18-22°C, 50-65% RH. They should be kept away from damp (or cold) walls, windows or floors to avoid possible moisture absorption. Equally, storage adjacent to heat sources, e.g. steam pipes, radiators, hot air ducts, ovens, etc., should be avoided.

Product is best stored in original packaging until ready for use Shelf life indefinite under these conditions.

6) Safety

Whenever possible, sanding should be carried out in a well-ventilated area and it is strongly recommended that suitable goggles, dust mask and gloves are worn.

Discs should be used only on machines with a suitable support pad designed for the purpose and maintained in good condition at all times.

The abrasive discs should extend symmetrically to no more than 2 mm beyond the outer rim of the support pad.

Damaged or misshapen abrasive discs or support pads should not be used.



Technical Data Sheet

Effective: 31/07/2019 Supersedes: 08/02/2010

Discs and pads should not be modified in any way. They should be used only in their original size and shape, as supplied.

It is recommended that discs be used only on support pads that are clearly marked with maximum permitted running speed. The speed stated should not be exceeded.

Machines should be operated with the disc making the shallowest angle possible with the work piece.

Care should be taken to ensure that discs without a centre hole are mounted centrally on the support pad.

When not in use disc sanding machine should be placed in a stand designed for the purpose or, alternatively, positioned on their backs. They must not be placed with the disc or pad face in contact with the floor or workbench.

3M™ 443SA Trizact™ Blending Discs is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.



Technical Data Sheet

Effective: 31/07/2019 Supersedes: 08/02/2010

For Additional Health and Safety Information

<p>3M United Kingdom plc Automotive Aftermarket 3M Centre, Cain Road, Bracknell, RG12 8HT Tel: +44 (0)161 237 6391</p> <p>aadenquiries.uk@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Ireland Limited Automotive Aftermarket The Iveagh Building The Park Carrickmines Dublin 18 Tel: +353 12160301</p> <p>aadenquiries.uk@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Denmark a/s Automotive Aftermarket Hannemanns Allé 53 2300 København S Tel: +45 43480100</p> <p>3mkundeservicedk@mmm.com www.3MAuto.dk</p>
<p>3M Finland, Suomen 3M Oy Automotive Aftermarket Keilaranta 6 02150 Espoo Tel: 09 5252 1</p> <p>tilaukset@mmm.com www.3M.fi/autotuotteet</p>	<p>3M Svenska AB Automotive Aftermarket Bileftermarknad 19189 Sollentuna Tel: 08-922100</p> <p>kundservice@mmm.com www.3M.se/bileftermarkad</p>	<p>3M Norge AS Automotive Aftermarket Kanalveien 2 2004 Lillestrøm Tel: 06384</p> <p>kundeservice@mmm.com www.3m.no/auto</p>
<p>3M Latvija K.Ulmana 5 Riga, LV-1004 Tel: +371 67066120</p> <p>www.3m.lv</p>	<p>3M Eesti OU Pärnu mnt. 158 11317 Tallinn Tel: +372 6 115 902</p> <p>www.3m.ee</p>	<p>3M Lietuva A.Goštauto str. 40 A LT-01112 Vilnius Tel: +370 5 2160780</p> <p>www.3m.lt</p>

© 3M 2019. 3M, Hookit and Trizact are all trademarks of the 3M company. All rights reserved.