



Automotive Aftermarket Division

3M™ 08901 Inner Cavity Wax, Brown

1) Part Numbers

3M™ 08901 / 500 ml aerosol

2) Description and end uses

Light brown low grade inner cavity wax designed to penetrate seams and coat surfaces. It gives a protective flexible coating after drying with excellent rust preventive properties.

3M™ 08901 inner cavity wax can be applied to internal cavities requiring rust proofing e.g. inside:

- Doors
- Boots
- Rear wing panels
- Sills
- Chassis legs

Major features:

- Easy to use aerosol
- Water repellent: It can be applied to wet surfaces as it will push water away.
- Capillary attraction: It seeps by capillarity into gaps and along joints.
- Sealant/coating: when dry, the 3M™ 08901 forms a protective film over joints and panels.
- Good adhesion properties

3) Physical Properties

Base	Waxes and Oils
Solvent	Aliphatic
Solids content (typical)	55%
Specific gravity	0.87
V.O.C	Approx. 213 g solvent
Colour	Translucent light brown
Service Temperature range	- 20 to 90°C



Technical Data Sheet

Effective: 19/08/2020 Supersedes: 26/04/2000

Tack free time	2-3 hours
Storage conditions	Cool dry place. Best results are obtained when material is stored and applied at room temperature, 5 to 30°C. Storage temperature must not exceed 50°C.
Shelf life	2 years from date of manufacture under normal storage conditions. Refer “Lot Number” and “Best Before Date” on can.

4) Directions for Use

- Shake can well before use.
- Use normal actuator for accessible areas and special flexible extension tube for difficult to reach areas.
- Apply generously.
- After spraying, clean valve by inverting can and press button until clear.

CAUTION: Do not attempt to paint on top of 3M™ 08901.

5) Storage

Store at room temperature in flammables storage area. Rotate stock on a “first-in-first-out” basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life see container for details. Use in a well-ventilated area.

6) Safety

Please refer to the Material Safety Data Sheet or contact your local 3M™ Toxicology Department.

3M™ 08901 Inner Cavity Wax, Brown is designed FOR PROFESSIONAL USE ONLY.



Technical Data Sheet

Effective: 19/08/2020 Supersedes: 26/04/2000

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information

For Additional Health and Safety Information

3M United Kingdom plc Automotive Aftermarket 3M Centre, Cain Road, Bracknell, RG12 8HT Tel: +44 (0)161 237 6391 aadukenquiries@mmm.com www.3Mbodyshop.co.uk	3M Ireland Limited Automotive Aftermarket The Iveagh Building Carrickmines Park Carrickmines , Dublin 18 Tel: +353 12160301 aadukenquiries@mmm.com www.3Mbodyshop.co.uk	3M Denmark a/s Automotive Aftermarket Hannemanns Allé 53 2300 København S Tel: +45 43480100 aadukenquiries@mmm.com www.3MAuto.dk
3M Finland, Suomen 3M Oy Automotive Aftermarket Keilaranta 6 02150 Espoo Tel: 09 5252 1 aadukenquiries@mmm.com www.3M.fi/autotuotteet	3M Svenska AB Automotive Aftermarket Herrjärva torg 4 170 67 Solna Tel: 08-922100 aadukenquiries@mmm.com www.3M.se/bileftermarkad	3M Norge AS Automotive Aftermarket Kanalveien 2 2004 Lillestrøm Tel: 06384 aadukenquiries@mmm.com www.3m.no/auto
3M Latvija K.Ulmana 5 Riga, LV-1004 Tel: +371 67066120 aadukenquiries@mmm.com www.3m.lv	3M Eesti OU Pärnu mnt. 158 11317 Tallinn Tel: +372 6 115 902 aadukenquiries@mmm.com www.3m.ee	3M Lietuva A.Goštauto str. 40 A LT-01112 Vilnius Tel: +370 5 2160780 aadukenquiries@mmm.com www.3m.lt

© 3M 2020. 3M is a trademark of the 3M company. All rights reserved