



Automotive Aftermarket Division

3M™ 08909 - Inner Cavity Wax, Transparent

1) Part Numbers

3M™ 08909 / 500 ml aerosol

2) Description and end uses

Transparent inner cavity wax designed to penetrate seams and coat surfaces. It gives a protective flexible coating after drying with excellent rust preventive properties.

Major product features:

- Easy to use aerosol
- Good seeping properties: It seeps by capillarity into gaps and along joints
- Good adhesion properties
- Good coverage

3M™ 08909 inner cavity wax can be applied to internal cavities requiring rust proofing e.g. inside:

- Doors
- Boots
- Rear wing panels
- Sills
- Chassis legs

3) Physical Properties

Colour	Transparent
Base	Wax
Propellant	Propane-butane
Flash point	23°C
Boiling point	135°C
Solids content	14 %
Service T° range	-20 to +90°C
Specific gravity	0.86
Tack free time	Approx. 2 hours
Storage conditions	+ 5 to 30°C
Practical life	18 months under normal storage conditions



Technical Data Sheet

Effective: 19/08/2020 Supersedes: 28/10/1994

4) Directions for Use

- Shake can well before use.
- Use normal actuator for accessible areas and special flexible extension tube for difficult to reach areas.
- Apply generously.
- After spraying, clean valve by inverting can and press button until clear.

CAUTION: Do not attempt to paint on top of 3M™ 08909.

5) Storage

Pressurised container. Protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material.

6) Safety

Please refer to the Material Safety Data Sheet or contact your local 3M™ Toxicology Department.

3M™ 08909 - Inner Cavity Wax, Transparent is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information



Technical Data Sheet

Effective: 19/08/2020 Supersedes: 28/10/1994

For Additional Health and Safety Information

<p>3M United Kingdom plc Automotive Aftermarket 3M Centre, Cain Road, Bracknell, RG12 8HT Tel: +44 (0)161 237 6391 aadukenquiries@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Ireland Limited Automotive Aftermarket The Iveagh Building Carrickmines Park Carrickmines , Dublin 18 Tel: +353 12160301 aadukenquiries@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Denmark a/s Automotive Aftermarket Hannemanns Allé 53 2300 København S Tel: +45 43480100 aadukenquiries@mmm.com www.3MAuto.dk</p>
<p>3M Finland, Suomen 3M Oy Automotive Aftermarket Keilaranta 6 02150 Espoo Tel: 09 5252 1 aadukenquiries@mmm.com www.3M.fi/autotuotteet</p>	<p>3M Svenska AB Automotive Aftermarket Herrjärva torg 4 170 67 Solna Tel: 08-922100 aadukenquiries@mmm.com www.3M.se/bileftermarkad</p>	<p>3M Norge AS Automotive Aftermarket Kanalveien 2 2004 Lillestrøm Tel: 06384 aadukenquiries@mmm.com www.3m.no/auto</p>
<p>3M Latvija K.Ulmana 5 Riga, LV-1004 Tel: +371 67066120 aadukenquiries@mmm.com www.3m.lv</p>	<p>3M Eesti OU Pärnu mnt. 158 11317 Tallinn Tel: +372 6 115 902 aadukenquiries@mmm.com www.3m.ee</p>	<p>3M Lietuva A.Goštauto str. 40 A LT-01112 Vilnius Tel: +370 5 2160780 aadukenquiries@mmm.com www.3m.lt</p>

© 3M 2020. 3M is a trademark of the 3M company. All rights reserved