



Automotive Aftermarket Division

3M™ Scotch™ Brand Trim Masking Tapes

1) Part Numbers

06345, 06347, 06348, 06349

Size: 50 mm x 10m

Plastic strip: 5, 7, 10, 15 mm

2) Description and end uses'

3M™ Trim Masking Tapes are special purpose automotive masking tapes, designed to lift and protect the rubber moulding from overspray. These mouldings found around the glass on modern vehicles with direct bonded windows, can be difficult and costly to remove. The unique design of 3M™ Trim Masking Tape eliminates the need to remove the glass enabling the perfect finish saving time and money.

Available in 4 sizes its applications include front and rear screens, side windows and rear lights. It works by lifting the rubber away from the painted surfaces to prevent “bridging” of the paint between the body and the moldings.

Features	Advantages	Benefits
Blue film backing	<ul style="list-style-type: none">• Conformability• Smoothness• Solvent & moisture resistance• Bright Colour	<ul style="list-style-type: none">• Virtually no recovery and lift on curves/reduces rework• Minimises chance of imprint damage/fewer rejects• Prevents paint bleed through/reduces rework• Easily seen on the job
Balanced heat resistant rubber resin adhes	<ul style="list-style-type: none">• Instant adhesion• Good holding power• Adhesive transfer resistance• Temperature performance	<ul style="list-style-type: none">• Adheres easily/reduces labour involved• Resists lifting or curling/reduces rework• Clean removal/reduces labour• Permits removal after bake cycle/reduces labour



Technical Data Sheet

Effective: 31/07/2019 Supersedes: 28/04/2008

Removable liner	• Easy handling	• Saves time and labour
-----------------	-----------------	-------------------------

The Trim Masking Tape's unique construction allows the paint to be applied under mouldings providing a factory finished appearance. This tape is readily dispensed from the conveniently designed box with graphic instructions.

Trim Masking Tape will withstand a bake cycle up to 121°C for 40 minutes with clean removal.

3) Physical Properties

Thickness:	0.120 mm	AFERA 4006
	0.260 mm	AFERA 4006
Adhesion to steel:	13N/25 mm	AFERA 4001
Temperature performance:	121°C	

4) Directions for Use

1. Make sure the area to be masked with the trim masking tape is clean, dry and free from any contaminants.
2. To make the product easier to handle cut into lengths of approx. 150mm to 200mm. Feed the first length between the paint and the moulding using the clear plastic strip as the leading edge. Ensure the release paper is facing the glass.
3. Keep inserting to all of the plastic strip is behind the moulding, carefully remove the liner paper from the product taking care not to pull the strip back out again.
4. Gently pull the blue plastic backing towards the glass to generate a gap between the paint work and the moulding.
5. Once a small gap can be seen between the paint and the moulding, stick the adhesive face onto the glass to hold in place.
6. Using the gap generated by the first strip of TMT, insert the next strip behind the first sliding it along the aperture until it just overlaps the first strip by 2-3mm.
7. Repeat step 6 until the required area is masked.



Technical Data Sheet

Effective: 31/07/2019 Supersedes: 28/04/2008

Tip: To help to identify the appropriate size that is best suited to the job, cut a short length (approx. 50mm) from each roll size and insert behind the rubber.

5) Storage

Store in clean dry place. Temperature of 21°C and 50 percent relative humidity are recommended.

6) Safety

1. When using solvents etc. for cleaning the surface prior to the application of the Trim masking tape, care must be taken to avoid contact with the skin and eyes. The correct PPE must be worn at all times.

2. After removing the TMT from the vehicle, as it may now be contaminated with paint waste it should be disposed of in accordance to local authority / country legislation.

3M™ Automotive Aftermarket Products are designed FOR PROFESSIONAL USE ONLY

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, 3M expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.



Technical Data Sheet

Effective: 31/07/2019 Supersedes: 28/04/2008

For Additional Health and Safety Information

<p>3M United Kingdom plc Automotive Aftermarket 3M Centre, Cain Road, Bracknell, RG12 8HT Tel: +44 (0)161 237 6391</p> <p>aadenquiries.uk@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Ireland Limited Automotive Aftermarket The Iveagh Building The Park Carrickmines Dublin 18 Tel: +353 12160301</p> <p>aadenquiries.uk@mmm.com www.3Mbodyshop.co.uk</p>	<p>3M Denmark a/s Automotive Aftermarket Hannemanns Allé 53 2300 København S</p> <p>Tel: +45 43480100</p> <p>3mkundeservicedk@mmm.com www.3MAuto.dk</p>
<p>3M Finland, Suomen 3M Oy Automotive Aftermarket Keilaranta 6 02150 Espoo</p> <p>Tel: 09 5252 1</p> <p>tilaukset@mmm.com www.3M.fi/autotuotteet</p>	<p>3M Svenska AB Automotive Aftermarket Bileftermarknad 19189 Sollentuna</p> <p>Tel: 08-922100</p> <p>kundservice@mmm.com www.3M.se/bileftermarkad</p>	<p>3M Norge AS Automotive Aftermarket Kanalveien 2 2004 Lillestrøm</p> <p>Tel: 06384</p> <p>kundeservice@mmm.com www.3m.no/auto</p>
<p>3M Latvija K.Ulmana 5 Riga, LV-1004</p> <p>Tel: +371 67066120</p> <p>www.3m.lv</p>	<p>3M Eesti OU Pärnu mnt. 158 11317 Tallinn</p> <p>Tel: +372 6 115 902</p> <p>www.3m.ee</p>	<p>3M Lietuva A.Goštauto str. 40 A LT-01112 Vilnius</p> <p>Tel: +370 5 2160780</p> <p>www.3m.lt</p>

© 3M 2019. 3M and Scotch are trademarks of the 3M company. All rights reserved