

Far beyond speed

3M™ Direct Attach Copper Twin Axial Cable Assemblies

External twin axial cable solutions from 3M.
The flexible, foldable future of data centers,
high-performance computing and AI.

Higher speed. Better cable management.

To help you keep servers, switches, storage and other high-speed components performing at the levels your customers demand, you'll need interconnect solutions with plenty of speed. 3M™ Direct Attach Copper Twin Axial Cable Assemblies deliver it, with channel rates up to 100 Gbps and aggregate data rates up to 800G.

But that's just the start. These cable assemblies feature flexible, foldable, fully-shielded cable that can be folded back on itself at an extremely tight bend radius. That means more cable can be installed in smaller spaces, with little to no signal loss. The result: Better cable management. Smoother airflow. Simplified deployment and serviceability. It's the future of high-speed data transfer, and it's available now.

Rack configurations made smarter and simpler

3M Twin Axial Cable technology allows for:

- Excellent rack cable management
- Efficient routing of cable with tight bends and folds
- Extremely tight bend radius reduces required space in front of the port, allowing rack doors to close
- Simplified serviceability with light, flexible cables




3M™ Direct Attach Copper Twin Axial Cable Assemblies, compared to competitive cable

Competitive cable




3M




Foldable, flexible cable

Competitive cable




3M




Thin cable

Competitive cable



3M




Tight bends at connector

Competitive cable



3M



Minimized airflow

Available form factors:

- OSFP
- QSFP-DD
- QSFP28
- SFP28
- QSFP+
- SFP+



3M™ 800G OSFP AEC Cable Assembly, 10Y Series

- Delivers aggregate bandwidth up to 800G (8x 100Gbps) with active electrical cable assemblies:
 - Up to 3 meters with 32 AWG
 - Up to 4 meters with 30 AWG
 - Up to 5 meters with 28 AWG
- Meets the following industry-standard protocols:
 - IEEE 802.3ck; OSFP MSA
 - 800G Ethernet applications
- Standard CMIS EEPROM mapping, custom is available
- OSFP to OSFP & OSFP to 2xQSFP Breakout assemblies available
- RoHS 2011/65/EU compliant*



3M™ 800G OSFP Direct Attach Copper Cable Assemblies, 9Y Series

- Delivers aggregate bandwidth up to 800G (8x 100Gbps) with passive copper assemblies:
 - 0.5 to 0.75 meters with 32 AWG
 - 0.75 to 1.2 meters with 30 AWG
 - 1.2 to 1.5 meters with 28 AWG
 - 1.5 to 2.0 meters with 26 AWG
- Meets the following industry-standard protocols:
 - IEEE 802.3ck; OSFP MSA
 - 800G Ethernet applications
- Custom EEPROM mapping available
- OSFP to 2xQSFP/4xQSFP and 8xSFP breakout assemblies available
- RoHS 2011/65/EU compliant*



3M™ 400G QSFP-DD Direct Attach Copper Cable Assemblies, 9V Series

- Up to 400G Ethernet applications
- IEEE 802.3cd
- QSFP-DD MSA
- Signal wire size 30A WG and 26 AWG
- Standard lengths available up to 3 m
- Custom EEPROM mapping available
- QSFP-DD to 2xQSFP56 Y-Cable assemblies available
- QSFP-DD to 4xQSFP28/4xQSFP56 and 8xSFP56 breakout assemblies available


Typical Applications: Network Interface Card (NIC) to switch



3M™ External QSFP28 Cable Assembly, 9Q Series

- 100G Ethernet applications
- IEEE 802.3bj
- SFF-8665, -8661, -8662
- Signal wire size 30 AWG and 26 AWG
- Standard lengths available up to 4 m
- Custom EEPROM mapping available
- QSFP28 (100G) to 4xSFP28 (25G) break out assemblies available
- QSFP28 (100G) to 2xQSFP28 (50G) Y-cable assemblies available

Typical Applications: Network Interface Card (NIC) to switch



3M™ External QSFP+ Cable Assembly, 9Q Series

- 40G Ethernet applications
- IEEE 802.3bd
- SFF-8436
- Signal wire size 30 AWG
- Standard lengths available up to 3 m
- Custom EEPROM mapping available
- InfiniBand DDR (4x5Gbps), QDR (4x10Gbps) and FDR (4x14Gbps) applications
- Tested at Open Network Systems Interoperability PlugFest (UNH IOL)

Typical Applications: Network Interface Card (NIC) to switch



3M™ External SFP28 Cable Assembly, 1422 Series

- 25G Ethernet applications
- IEEE 802.3by
- SFF-8431
- Signal wire size 30 AWG and 26 AWG
- Standard lengths available up to 4 m
- Custom EEPROM mapping available
- Available in black (red or blue PVC jacket options available)
- Tested at Open Network Systems Interoperability PlugFest (UNH IOL)

Typical Applications: Network Interface Card (NIC) to switch



3M™ External SFP+ Cable Assembly, 1410/1412 Series

- 10G Ethernet applications
- IEEE 802.3ae
- SFF-8431 and SFF-8432
- Signal wire size 30 AWG and 26 AWG
- Standard lengths available up to 7 m
- Custom EEPROM mapping available
- Available in black, red or blue PVC jacket options

Typical Applications: Network Interface Card (NIC) to switch



3M™ External miniSAS Cable Assembly, 8G26 Series

- x4 configuration
- SAS 2.0 and 2.1 (100 ohm) applications
- SFF-8086, 8088
- Signal wire size 30 AWG and 28 AWG
- Standard lengths available up to 6 m
- Various keying options and custom cable lengths available

Typical Applications: Network Interface Card (NIC) to switch

Over 50 years of interconnect innovation

3M™ Direct Attach Copper Twin Axial Cable Assemblies are part of a long line of 3M firsts in electronics cabling technology. 3M developed the first known mass-termination interconnect system; the first 64-wire termination; color-coded flat cabling; the first IDC solution for I/O applications; foldable twin-ax cable and more – all to help manufacturers improve their device performance, streamline their assembly and add more value to their solutions.

*** RoHS 2011/65/EU Compliant:** “RoHS 2015/863” means that the product or part does not contain any of the substances in excess of the maximum concentration values (“MCVs”) in EU RoHS Directive 2011/65/EU, as amended by EU 2015/863. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

Safety Data Sheet: Consult Safety Data Sheet before use.

Regulatory: For regulatory information about this product, contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specifications on the Certificate of Analysis, which is established when the product is manufactured and deemed commercially available and is provided at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.** If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: For industrial use only. Not intended, labeled or packaged for consumer sale or use.



Electronics Materials Solutions Division

3M Center, Building 223-3S-23
St. Paul, MN 55144-1000 USA

Web 3M.com/twinax
Phone 1-800-810-8513

Please recycle. Printed in USA.
©3M 2024. All rights reserved.
Issued: 3/24 16663HB
60-5005-0048-7 Rev. B

3M is a trademark of 3M.
Used under license by 3M subsidiaries and affiliates.