Science. Applied to Life.™

Technical Data | October 2026

3M™ Lined Low-Static Polyimide Film Tape 7419L

Product Description

3M™ Lined Low-Static Polyimide Film Tape 7419L features an industry-leading polyimide film backing with an acrylic adhesive that is used for PCB solder masking and other high-temperature applications up to 260°C (500°F). This product is amber in color and has a thickness of 1.8 mil (46 microns). This is a lined version of 3M™ Low-Static Polyimide Film Tape 7419.

Key Features

- Specially formulated acrylic adhesive is resistant to typical solder mask temperatures for short periods of time
- Stays firmly in place during processing and removes cleanly from typical electronic substrates even after 10 minutes at 260°C (500°F)
- Specially formulated acrylic adhesive formulation does not rely on silicone, which lessens the potential for silicone contamination which can interfere with subsequent bonding or conformal coating operations
- The high-temperature acrylic adhesive also has excellent chemical resistance and should be considered for demanding chemical masking applications
- Product is wound on a polyethylene tape core

Product Construction

Polyimide Film Backing: 1.0 mil
Acrylic Adhesive: 0.8 mil
Non-Silicone PET Release Liner

Material Description

Note: The following preliminary technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Lined Low-Static Polyimide Film Tape 7419L	
Property	**Value**
Backing	Industry-Leading Polyimide Film
Adhesive	Acrylic
Color	Amber
Liner	Non-Silicone Polyester (PET)
Standard Roll Length	33 meters (36 yards)

3M™ Lined Low-Static Polyimide Film Tape 7419L

Applications

- Masking or protecting residue-sensitive areas on printed circuit boards (PCBs) during high-temperature operations, such as wave soldering and solder reflow
- Release surface in fabrication of parts cured at elevated temperatures

Typical Physical Properties and Performance Characteristics

Note: The following preliminary technical information and data should be considered representative or typical only and should not be used for specification purposes. Final product specifications and testing methods will be outlined in the product's Certificate of Analysis (COA) that is shipped with the commercialized product.

3M™ Lined Low-Static Polyimide Film Tape 7419L		
Property	**Test Method***	**Value**
Adhesion to Steel Initial 72 hours at 25°C 10 minutes at 260°C	ASTM D3330	4 oz/in width (4.5 N/100 mm) 5 oz/in width (5.6 N/100 mm) 17 oz/in width (19 N/10 mm)
Adhesion to Copper Initial 72 hours at 25°C 10 minutes at 260°C	ASTM D3330	4 oz/in width (4.5 N/100 mm) 5 oz/in width (5.6 N/100 mm) 10 oz/in width (11 N/10 mm)
Static Discharge**	3M Internal Test Method	< 180 volts
Dielectric Strength	ASTM D149	6,000 Volts
Surface Resistivity	ESD Method S-11	5 X 10^6 ohms/sq
Backing Thickness	ASTM D3652	1.0 mil (0.025 mm)
Total Tape Thickness	ASTM D3652	1.8 mil (0.046 mm)
Temperature Use Range***	3M Internal Test Method	10 minutes at 260°C (500°F)
Outgassing	ASTM E595	%TML = 0.71, %CVCM = <0.01

*Methods listed as ASTM are tested in accordance with the ASTM method noted
**Static discharge during removal from roll
***Temperature use range is defined as the maximum time at the stated temperature after which the tape may be removed cleanly, without staining, from a copper substrate

Application Techniques

- Substrates should be smooth, clean, dry, and oil-free to help ensure good wet-out and adequate adhesion.
- Tape may not bond or conform to low surface energy, rough, or sharply curved surfaces.

Storage and Shelf Life

The shelf life of 3M™ Lined Low-Static Polyimide Film Tape 7419L is 18 months from the date of manufacture when stored in original packaging materials and stored at 21°C (70°F) and 50% relative humidity.

Certificate of Analysis (COA)

The 3M Certificate of Analysis (COA) for this product is established when the product is manufactured and deemed commercially available from 3M. The COA contains the 3M specifications, test methods, and test results for the product's performance attributes that the product will be supplied against. Contact your local 3M representative for this product's COA.

3M™ Linered Low-Static Polyimide Film Tape 7419L

Regulatory: For regulatory information about this product, contact your 3M representative.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third-party intellectual property rights is granted or implied with this information.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specifications on the Certificate of Analysis, which is established when the product is manufactured and deemed commercially available and is provided at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.** If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: For industrial use only. Not intended, labeled or packaged for consumer sale or use.

3M

3M Display & Electronics
3M Center, Building 223-3S-32
St. Paul, MN 55144-1000 U.S.A.

Phone 1-800-3M HELPS
Web 3M.com/Electronics

3M is a trademark of 3M Company.
All other trademarks herein are the property of their respective owners.
©3M 2026. All rights reserved.
60-5005-0026-3