





LASD Replacement (On Body)




1		<p>Pre-Cleaning Pre-wash/clean vehicle prior to disassembly (power wash undercarriage area at repair).</p>
2		<p>LASD Removal Remove sound deadening material from affected repair area using a scraper or chisel.</p>
3		<p>Surface Prep Scuff surface with a maroon Scotch-Brite™ hand pad. Blow off area with compressed air and clean with APCD.</p>
4		<p>Application Mask area and apply seam sealer. Re-create desired appearance and texture of NVH material using tools of the trade (e.g., notched spreaders, brushes, scuff pads, compressed air, etc.). Remove perimeter masking following the tooling process and prior to final cure.</p>

Visit 3MCollision.com for more SOPs and videos

Product List

<p>3M™ Car Wash Soap Concentrate, 1 gallon, PN 38377</p>	
<p>3M™ All Purpose Cleaner and Degreaser Concentrate, 1 gallon, PN 38350</p>	
<p>Scotch-Brite™ Durable Flex Hand Pad, MX-HP, 4-1/2 in. x 9 in., Very Fine, PN 64659</p>	
<p>Scotch-Brite™ 7447 PRO Hand Pads, Very Fine grade, 6 in. x 9 in., PN 64926</p>	
<p>3M™ Heavy-Bodied Seam Sealer, 200mL, PN 08308; 600mL DMS, PN 58308</p>	
<p>3M™ Urethane Seam Sealer, PN 08361</p>	
<p>3M™ MSP Seam Sealer, PN 08370</p>	
<p>3M™ NVH Dampening Material, PN 04274</p>	

Think About Your Health

<p>3M™ E-A-R™ Skull Screws™ Ear Plug, PN P1300</p>	
<p>3M™ Respirator Assembly/ Organic Vapor N95 Dual Cartridge, PN 07192</p>	
<p>3M™ Lexa™ Protective Eyewear, PN 15200</p>	
<p>Not a complete list. Select protective eyewear, appropriate gloves, hearing protection, respirator and protective clothing based on your job and exposure assessment.</p>	

Individual Product Instruction and Safety Information

For individual product instructions and applicable precautions see product labels and associated literature for the individual product at 3MCollision.com

For product material safety data sheets see 3MCollision.com

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

IMPORTANT NOTE: There are of course many factors and variables that can affect an individual repair, so the technician and repair facility need to evaluate each specific application and repair process, including relevant vehicle, part and OEM guidelines, and determine what is appropriate for that repair.



3M Automotive Aftermarket Division
3M Center, Building 223-6N-01
St. Paul, MN 55144-1000
U.S.A.

3M, Accuspray, Dynatron, E-A-R, Green Corps, Highland, Hookit, Lexa, Perfect-It, Platinum, Roloc, Scotch, Scotchblok, Scotch-Brite, Skull Screws, Trizact and Virtua are trademarks of 3M Company. Marson is a trademark of Alcoa, Inc. Metton is a trademark of Metton America, Inc.

3MCollision.com

Please recycle. Printed in U.S.A. © 3M 2017. All rights reserved.