



# Double Lined Adhesive Transfer Tape

## FF002702-10

Technical Data

July 2017

**Product Description** 3M™ Double Lined Adhesive Transfer Tape FF002702-10, with 3M™ High Performance Tackified Acrylic Adhesive P1650, is typically used for demanding environments, including automotive applications.

Product Construction	Liner	Adhesive	Liner
	.0015 in. Clear Polyester Liner (38 microns)	P1650 Perm. 40 PAT	50# SC Remoist Liner

### Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.  
Peel adhesion was performed off stainless steel substrates with 2.0 mil PET backing. No dwell time.

Peel Adhesion(180°)	20 oz/in to 140 oz/in
Application Temperature	40°F to 120°F (5°C to 49°C)
Service Temperature	-40°F to 302°F (-40°C to 150°C)

### Features

- Designed to meet difficult automotive underhood specifications
- Good moisture and humidity resistance
- Excellent thermal stability
- Resistance to many automotive and industrial fluids

### Application Ideas

- Automotive underhood
- Harsh environments
- Durable goods

# 3M™ Double Lined Adhesive Transfer Tape

## FF002702-10

---

Storage	Store under normal conditions of 70°F (21°C) and 50% R.H.
Shelf Life	To obtain best performance, use this product within 24 months from date of manufacture.
Technical Information	The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.
Product Selection and Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.
Warranty, Limited Remedy, and Disclaimer	Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability	Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

---

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



Industrial Adhesives and Tapes Division  
3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (Fax)  
[www.3M.com/converter](http://www.3M.com/converter)

3M is a trademark of 3M Company.  
©3M 2017 E70-0713-4665-7 (7/17)