


3M™ Interam™ Mat Mount 1650HTG

Technical Data Sheet



Product Description

3M™ Interam™ Mat Mount 1650HTG is a non-intumescent, high temperature, needled polycrystalline fiber mat with low organic binder. Interam Mat Mount 1650HTG is a high-performance solution that can be used in a wide range of gap designs, temperature conditions and applications.

Features

- Wide range of operating temperatures (ambient to 1100°C)
- Single layer mat solution for small to large gap designs
- Excellent fiber resiliency for substrate retention
- Excellent erosion resistance
- Moderate peak compression force
- Low thermal conductivity
- Low organic binder content
- Color coating on mat monolith interface surface enables easy visual control during assembly

Applications:

- Ultra-thin wall monoliths
- Close coupled or manifold mounted converters
- Light-duty and commercial vehicle applications, including gasoline and diesel particulate filters

Application Density (varies by application)

Target	0.366 g/cm ³
Design Range	0.25 - 0.50 g/cm ³

Physical Properties

Weight/Areas Available (g/m ²) *	1130	1250	1355	1435	1580	1745	1845	2200
Weight/Area Range (g/m ²)	1017 – 1243	1125 – 1375	1120 – 1579	1292- 1579	1422 - 1738	1571 – 1920	1661 – 2030	1980 – 2420
Nominal Thickness (mm)	7.5	7.9	8.3	8.7	9.2	10.0	10.6	12.5
Thickness Range (mm)	6.5 – 8.5	6.9 – 8.9	7.3 – 9.3	7.7 – 9.7	8.2 – 10.2	8.8 – 11.2	8.8 – 12.4	10.5 – 14.5
Application Gap Area (mm)	3.1	3.4	3.7	3.9	4.3	4.8	5.0	6.0
Composition Information	Organic (%)	0.5 – 2.0						
	Fiber (%)	98.0 – 99.5						

* Actual target and design ranges vary by application. Please contact your technical service representative for guidance with your specific application

Regulatory Information

Please refer to the product label and Safety Data Sheet (SDS) for health and safety information before using.

Contact Information

The information provided in this technical document is intended as a guide for these products. For more information or help in selecting a 3M product for an application, please contact your 3M technical service representative or call 1-800-328-1684.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Automotive Aerospace Solutions Division

3M Center, Building 224-6NE-45
St. Paul, MN 55144-1000
Phone: 1-800-328-1684
Web: www.3M.com/emission

3M and Interam are trademarks of 3M Company
Please recycle. Printed in USA © 3M 2022
All rights reserved.