

3M Science.
Applied to Life.™

Automotive Painting Simplified.

It's about achieving the highest quality finish in the least amount of time. That's what 3M™ Tapes offer automotive painters. Plus, the broadest selection available in the market.

3M™ Masking Tapes for surface protection, sharp paint lines and easy removal.

3M™ Vinyl Tapes stretch, conform and hold to curves, then lift off cleanly.

3M™ E XPP Washi Tapes provide a thin paint ridge and clean removing acrylic adhesive.

3M™ Paint Masking Films are highly conformable for fiber free and power wash processes.

3M.com/masking



	Image	Description
Masking Tapes		3M™ Specialty High Temperature Purple Masking Tape 501+ Super-sharp paint lines for high temperature masking jobs. Ultra-high strength holding power to prevent paint blow-by on a variety of surfaces.
		3M™ High Performance Green Masking Tape 401+ For critical paint masking applications requiring a strong hold. Conformable for easy masking around corners, over contours, and irregular surfaces.
		3M™ Premium High Temperature Masking Tape 2393 This high heat resistant, mini crepe paper tape is made to lift off cleanly after high temperature paint-bake operations.
		Scotch® Ultimate Paint Edge Masking Tape 2460 The ultra-thin backing produces a virtually undetectable low paint ridge that results in sharp, smooth paint lines, yet this tape is strong enough to pull through paint and caulk without ripping. Unique acrylic adhesive technology offers good, instant adhesion.
		3M™ EXPP Washi Tape Thin backing provides a low paint ridge and clean removing acrylic adhesive. Slightly thicker and stronger than 2460; provides better sliver and tear resistance.
Fine Line Tapes		Scotch® Fine Line Tape 218 The polypropylene backing is stiffer than vinyl fine line tapes, while conforming easily around corners. Good moisture and solvent resistance. Used as a layout tape for high value, multi-color and custom painted graphics.
		Scotch® High Temperature Fine Line Tape 4737 Smooth, vinyl backing provides conformability for sweeping curves and straight lines. Removes cleanly. Available in: opaque blue (4737S), translucent blue (4737T) and with a liner (4737TL, 4737SL).
		Scotch® High Temperature Fine Line Tape 4735 A highly conformable tape used to achieve sharp contrast and color separation while painting on highly contoured, curved and shaped surfaces. Holds in depressions, and around corners and edges. Also available with a liner (4735L).
		3M™ Vinyl Tape 471+ A conformable tape with a semi-translucent backing. This durable tape is flexible and removes cleanly even after bake cycles, without adhesive build-up or ghosting. Provides some visual clarity for alignment during application.
Extreme Temp. Tapes		3M™ Polyester Tape 875 This thin, high strength film provides a degree of conformability while meeting low caliper requirements. Coated with a non-silicone adhesive, this tape works in demanding conditions.
		3M™ Polyester Tape 8992 A general purpose tape that excels in high temperature masking operations such as powder coat painting. Pressure-sensitive silicone adhesive performs in temps from -60° to 400°F (-50° to 204°C).
		3M™ High Temperature Aluminum Foil/Glass Cloth Tape 363 A strong and flexible tape with high tensile strength; puncture and tear resistance. Adheres well to silicone surfaces and over irregular or uneven substrates.
Specialty Products		3M™ Aluminum Foil Tape 425 Withstands a variety of moisture, weathering, UV and solvents in order to provide an excellent work life, indoors or out.
		3M™ High Temperature Protective Bags & Sheets 7260M For masking jobs in high-heat bake cycles. Excellent conformability with easy handling. Best for covering large surfaces. Available in translucent bags and perforated or continuous sheets.
		3M™ High Temperature Paint Masking Film 7300 Designed for soft flexing. Provides good drape and conformability. Eliminates fiber that can occur with masking papers. Protects where bleed-through of solvents and paints may occur.

		FEATURES							APPLICATIONS		
	Conformability	Bake Cycle temps up to	Chemical Resistance	Clean Removal	Sharp Paint Lines	OEM High Temperature	OEM Wet-pull	OEM Final Repair	Automotive Fascia	Specialty Vehicles	Key Features
M	•	300°F 149°C	•	•	•	•	•	•	•	•	Strong holding power in high temperature processes
M	•	250°F 121°C	•	•	•	•	•	•	•	•	High performance crepe for medium temp bake processes
M	•	325°F 163°C	•	•	•	•	•	•	•	•	Easy removal after baking
L	•	300°F 149°C	•	•	•	•	•	•	•	•	Thin paint ridge
L	•	300°F 149°C	•	•	•	•	•	•	•	•	Thin paint ridge, strong backing, highly visible color
M	•	250°F 121°C	•	•	•	•	•	•	•	•	Balanced conformability
M	•	300°F 149°C	•	•	•	•	•	•	•	•	Balanced conformability
H	•	300°F 149°C	•	•	•	•	•	•	•	•	Highly conformable and resists lifting
H	•	250°F 121°C	•	•	•	•	•	•	•	•	Excellent for conforming to surface contours
M	•	400°F 204°C	•	•	•	•	•	•	•	•	For thin paint ridge or higher bake temp
M	•	400°F 204°C	•	•	•	•	•	•	•	•	Excels in powder coat painting/anodizing
M	•	600°F 316°C	•	•	•	•	•	•	•	•	Puncture and tear resistance
L	•	300°F 149°C	•	•	•	•	•	•	•	•	Ideal for heat shielding and de-paint operations
H	•	315°F 157°C	•	•	•	•	•	•	•	•	Large (vehicle sized) masking film bags
H	•	310°F 154°C	•	•	•	•	•	•	•	•	Soft flexing film with excellent drape and conformability

3M
Industrial Adhesives and Tapes Division
 3M Center, Bldg 220-5E-06
 St. Paul, MN 55144
 1-866-513-4026
 3M.com/masking

Limited Warranty & Limitation of Liability: 3M warrants this product will meet 3M specifications at the time of 3M shipment. Except as required by law, 3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If there is a breach of this warranty, your exclusive remedy shall be product replacement or refund of purchase price. 3M will not be liable for any direct, indirect, special, incidental, or consequential damage related to the product.

3M and 3M Science Applied to Life are trademarks of 3M Company. Scotch is a registered trademark of 3M Company. © 3M 2017. All rights reserved. 70-0710-0490-0 (Janz)