

3M Science.
Applied to Life.™

CAUTION
AUTOMATIC VEHICLE
NO RIDING

3M™ Ultra Durable Floor Marking Tape 971

**Fast, flexible and durable
for no compromises.**

**Unbeatable toughness.
Unparalleled flexibility.**

You need to do your job faster than ever before without sacrificing safety or standards. And you need to be able to rely on your floor marking to change with you — and to stand up to heavy traffic and tough conditions. That's where we come in. Our tapes go down quickly and come up easily, so changes are no sweat. When you're facing new regulations, new equipment, new products — you have the power to adapt your facility to ever changing conditions. No compromises.



3M™ Ultra Durable Floor Marking Tape 971 stands up to your ever changing conditions. The flexible floor marking you need for tough, high-traffic conditions.



Fast and easy to apply with clean removal

Requires minimal tools or production downtime to apply — no dripping paint, drying, fumes, or clean-up. Just peel, apply, and get to work.

Superior durability

Thick backing provides excellent abrasion resistance and withstands lifting, curling and peeling from forklift traffic and dragging pallets.

Maximize your efficiency

Using the 5S visual management system helps make it easier to ensure your workplace is more organized, efficient, productive and safer.

Make your facility more flexible

Change your layout whenever you like, with no grinding off old paint or masking for new — saving you time and money.



Unique Polylactic Acid (PLA) Backing

The key ingredient in 971 backing is made from an environmentally-conscience, plant-based material versus petroleum-based, traditional, vinyl tapes. The thick PLA backing provides top-tier durability while using less fossil fuels.

3M™ Ultra Durable Floor Marking Tape 971					
SKU	UPC	Size	Case Qty	Color	
70-0075-1073-1	0-00-76308-14104-2	2 in x 36 yd			
70-0075-1074-9	0-00-76308-14105-9	3 in x 36 yd	1/case	White	
70-0075-1075-6	0-00-76308-14107-3	4 in x 36 yd			
70-0075-1064-0	0-00-76308-14095-3	2 in x 36 yd			
70-0075-1065-7	0-00-76308-14096-0	3 in x 36 yd	1/case	Yellow	
70-0075-1066-5	0-00-76308-14097-7	4 in x 36 yd			
70-0075-1067-3	0-00-76308-14098-4	2 in x 36 yd			
70-0075-1068-1	0-00-76308-14099-1	3 in x 36 yd	1/case	Blue	
70-0075-1069-9	0-00-76308-14100-4	4 in x 36 yd			
70-0075-1070-7	0-00-76308-14101-1	2 in x 36 yd			
70-0075-1071-5	0-00-76308-14102-8	3 in x 36 yd	1/case	Red	
70-0075-1072-3	0-00-76308-14103-5	4 in x 36 yd			
70-0075-1830-4	0-06-38060-14345-2	2 in x 36 yd			
70-0075-1831-2	0-06-38060-14346-9	3 in x 36 yd	1/case	Green	
70-0075-1832-0	0-06-38060-14347-6	4 in x 36 yd			
70-0075-1827-0	0-06-38060-14342-1	2 in x 36 yd			
70-0075-1828-8	0-06-38060-14343-8	3 in x 36 yd	1/case	Orange	
70-0075-1829-6	0-06-38060-14344-5	4 in x 36 yd			



Resists lifting from forklift traffic.



Excellent pallet drag resistance.



3M Industrial Adhesives & Tapes
3M Center, Bldg 225-3S-06
St. Paul, MN 55144-1000 USA

Phone 1-800-362-3550
Web 3M.com/IATD
3M.com/floormarking

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.

3M is a trademark of 3M. Please recycle. Printed in U.S.A.
 © 3M 2019. All rights reserved. 70-0716-9854-5
 v3, January 2019