



# Aluminum Foil Tape 437

Technical Data

October 2017

## Product Description

3M™ Aluminum Foil Tape features a dead soft aluminum foil backing combined with an acrylic pressure-sensitive adhesive on a poly-coated kraft paper liner.

## Product Construction

Backing	Adhesive	Colour	Liner
Aluminum Foil	Acrylic	Silver	Poly-coated Kraft Paper

## Typical Physical Properties

Note: The following technical information and data is based upon limited 3M testing and should not be used for specification purposes.

		ASTM Test Method
<b>Adhesion to Steel:</b>	(164 N/100 mm width) 150 oz/in width	D-3330
<b>Tensile Strength:</b>	(525 N/100 mm width) 30 lbs/in. width	D-3759
<b>Elongation at Break:</b>	8%	D-3759
<b>Backing Thickness:</b>	0.07 mm (3.0 mils)	D-3652
<b>Liner Thickness:</b>	0.11 mm (4.2 mils)	D-3652
<b>Total Tape Thickness:</b>	0.20 mm (8.0 mils)	D-3652
<b>Temperature Use Range:</b>	-40°C to 100°C (-40°F to 212°F)	

## Features

- Utilizes a high-tack acrylic adhesive to meet automotive OEM requirements
- High initial tack for quick and easy application on assembly lines
- Durable aluminum foil backing offers ideal properties for long serviceable life indoors and outdoors

## Application Ideas

- Heat shielding
- Moisture barrier
- Thermal conducting

# 3M™ Aluminum Foil Tape

## 437

---

<b>Storage</b>	Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging material.
<b>Shelf Life</b>	To obtain best performance, use this product within 24 months from date of manufacture.
<b>Important Notice</b>	<p>The statements and technical information contained herein are based on tests and data that 3M believes to be reliable, but the accuracy or completeness of such statements and technical information is not guaranteed. User is responsible for determining whether a specific 3M product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.</p>
<b>Limitation of Remedies and Liability</b>	<p>If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty or condition, or strict liability.</p>
<b>No Warranty</b>	<p>3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.</p>

---



### 3M Industrial Adhesives and Tapes Division

#### 3M Canada

300 Tartan Drive

P.O. Box 5757

London, ON N6A 4T1

Phone 1-800-364-3577

Web 3M.ca

3M is a trademark of 3M. Used under license in Canada.

© 2017, 3M. All rights reserved. Printed in Canada. Please recycle. 1707-09258 E BA-17-24260