

3M™ Disposable Respirator 1870+, N95

Technical Data Sheet



Description

The 1870+ healthcare respirator is designed to help provide respiratory protection for the wearer against certain airborne particles. As a disposable particulate respirator, it is intended to reduce wearer exposure to certain airborne particles including those generated by electrocautery, laser surgery, and other powered medical instruments. As a surgical mask, it is designed to be fluid resistant to splash and spatter of blood. The 1870+ particulate respirator is a personal protective equipment (PPE) that is primarily intended to protect the health care workers by reducing exposure to harmful airborne particles which are small enough to be inhaled – typically particles less than 100 microns in size.

Features

- NIOSH approved N95 rating
- FDA cleared for use as a surgical mask
- Fluid Resistant Level 3 160 mmHg
- Flammability Rating Class I
- Adjustable nose clip
- 3-Panel, flat-fold style
- Stapled headbands
- Individually packed

Materials

The following materials are used in the production of 1870+ respirators:

Component	Material
Straps	Polyisoprene
Staples	Steel
Nose Clip	Aluminium
Nose Foam	Polyurethane
Filter	Polypropylene
Coverweb	Polypropylene

This respirator does not contain components made from natural rubber latex.

Maximum mass of products = 10g



Use For

- Intended to be worn by operating room personnel during surgical procedures to help protect both the surgical patient and the operating room personnel from transfer of microorganisms, body fluids, and particulate material.
- Always follow User Instructions and use in manners as indicated

Do Not Use for

- DO NOT use in industrial settings
- DO NOT use for gases or vapours (i.e. anesthetic gases such as isoflurane or vapours from sterilants such as glutaraldehyde.)
- DO NOT use in any manner not indicated in the User Instructions

Approvals and Standards

- NIOSH approved N95 respirator
- Meets NIOSH 42 CFR 84 N95 requirements for a minimum 95% filtration efficiency against solid and liquid aerosols that do not contain oil.
- NIOSH approval number: TC-84A-5726
- FDA cleared for use as a surgical mask
- Health Canada Class I medical device
- Bacterial Filtration Efficiency F2101 >99% BFE
- OSHA Assigned Protection Factor (APF) 10
- 1870+ is entered in the ARTG 255656

Storage and Transportation

Shelf life of the unopened product is five (5) years from date of manufacture when stored within temperature range of -20°C to +30°C and at less than 80% relative humidity. End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Fitting Instructions


Must be followed each time the respirator is worn. Before fitting device, ensure hands are clean.

See Figure 1 below.

All respirator components should be inspected for damage prior to each use.

1. With reverse side up and using the tab, separate top and bottom panels to form a cup shape. Bend slightly at centre of the nose clip.
2. Ensure both panels are fully unfolded.
3. Cup respirator in one hand with open side towards face. Take both straps in other hand. Hold respirator under chin, with nose piece up, and pull straps over head.
4. Locate the upper strap across the crown of the head and the lower strap below the ears. Straps must not be twisted. Adjust top and bottom panels for comfortable fit, ensuring panels and chin tab are not folded in.
5. Using both hands, mould nose clip to the shape of the lower part of the nose to ensure a close fit and good seal. Pinching the nose clip using only one hand may result in less effective respirator performance - use two hands.
6. Place one or both hands completely over the middle panel. Inhale and exhale sharply. Be careful not to disturb the position of the respirator. If air leaks around your nose, re-adjust the nosepiece as described in Step 5. If air leaks around respirator edges, adjust panels and position of straps and make certain respirator edges fit snugly against the face. If you cannot achieve a proper seal, do not enter the contaminated area. See your supervisor.

Figure 1



Warnings and Use Limitations

Always be sure that the complete product is:

- Suitable for the application;
 - Fitted correctly;
 - Worn during all periods of exposure;
 - Replaced when necessary.
- It is recommended that fit testing be conducted before assigning a respirator to an individual. If you cannot achieve a proper fit then do not enter contaminated area. See your supervisor.
 - Inspect respirator before each use to ensure it is in good working condition. Examine all the respirator parts for signs of damage including the two straps, noseclip, nose foam and staples. The respirator should be disposed of immediately upon observation of damaged or missing parts. The respirator should be disposed of immediately upon observation of damaged or missing parts.
 - Leave the contaminated area immediately and contact supervisor if dizziness, irritation or other distress occurs.
 - Dispose of used product in accordance with applicable regulations.
 - All respirators should be used in accordance with local regulations.
 - Do not alter, repair, wash, and abuse or misuse the respirator.
 - Do not use with beards or other facial hair or conditions that prevent a good seal between the face and the sealing edge of the respirator.
 - The respirator can help protect the wearer's lungs against certain airborne contaminants; however, it will not prevent entry through other routes such as the skin or eyes, which would require additional personal protective equipment (PPE).
 - The respirator is designed for occupational/professional use by adults who are properly trained in its use and limitations. The respirator is not designed to be used by children.
 - Individuals with a compromised respiratory system, such as asthma or emphysema, should consult a physician and complete a medical evaluation prior to use.
 - Maximum Operating Temperature: +50 degrees Celsius.
 - The filtration efficiency of the respirator may decrease in the presence of oily mists.

Ordering Information

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100250447	XA010033554	•	•	1870+	3M™ Aura™ Health Care Particulate Respirator and Surgical Mask 1870+, N95, 240 ea/Case

Warning

Respirators must not be used until your employer has determined whether usage will be in accordance with manufacturer's instructions. The wearer must be trained in the proper fitting and use of this product. Failure to follow all instructions and warnings on the use of this product and/or failure to wear this respirator during all times of exposure can reduce respirator effectiveness and result in illness or death. All respirators should be used in accordance with Australia/New Zealand standard AS/NZS 1715. It is recommended that fit testing be conducted before assigning a respirator to an individual. If you cannot achieve a proper fit, do not enter contaminated areas. Do not use with beards or other facial hair or conditions that prevent a good seal between the face and the sealing surface of the respirator.

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

SCAN OR CLICK FOR:



QR-CAT-DR
Disposable
Respirator
Catalogue Section



QR-CAT-FULL
Full Personal
Safety Division
Catalogue



3M Australia Pty Ltd
Personal Safety Division
Bldg A, 1 Rivett Road
North Ryde NSW 2113
Customer Service: 1300 363 565
Email: 3msupport.safety.au@mmm.com
Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
94 Apollo Drive, Rosedale
Auckland 0632
Customer Service: 0800 252 627
Email: 3msupport.safety.nz@mmm.com
Web: www.3M.com/nz/ppesafety

3M & Aura are trademarks of 3M Company.
© 3M 2025. All rights reserved.