























This guide is intended to assist customers with proper product selection and floor preparation prior to applying Scotchgard™ Stone Protector (original or Plus).

Product	Scotchgard™ Stone Floor Protector (original)  	Scotchgard™ Stone Floor Protector Plus  
Bag Label Color	Purple or Gray	Green
Features	Suitable for daily cleaning with Scotch-Brite™ Clean & Shine Pad on terrazzo or concrete.	More durable, fewer installation steps, improved water resistance, chemically strippable. Suitable for daily cleaning with Scotch-Brite™ Clean & Shine Pad on concrete only.
Recommended Substrates	<ul style="list-style-type: none"> • Concrete • Terrazzo 	<ul style="list-style-type: none"> • Concrete • Marble • Terrazzo • Granite
Floor Preparation Prior to Installation <i>Guidance depends on coating previously applied to floor; if floor is bare, proceed to Installation</i>	Floors coated with Scotchgard™ Stone Floor Protector (discontinued green label):	
	Chemically strip floor.	Wet scrub floor for 6 passes with Scotch-Brite™ Purple Diamond Floor Pad Plus, or complete 6 passes with Blue Trizact™.
	Floors coated with Scotchgard™ Stone Floor Protector Plus (green label):	
	Chemically strip floor.	Wet scrub floor with Scotch-Brite™ Purple Diamond Floor Pad Plus.
	Floors coated with Scotchgard™ Stone Floor Protector (original purple/gray label):	
	Wet scrub floor with Scotch-Brite™ Purple Diamond Floor Pad Plus.	Wet scrub floor with Scotch-Brite™ Purple Diamond Floor Pad Plus.
Floors coated with traditional acrylic floor finish (wax):		
Chemically strip floor.	Chemically strip floor.	
Installation Steps <i>Refer to Technical Bulletin for full maintenance instructions</i>	1. Polish floor with Trizact™. 	1. Polish floor with Trizact™. 
	2. Burnish or wet scrub floor with Scotch-Brite™ Purple Diamond Floor Pad Plus. 	2. Burnish or wet scrub floor with Scotch-Brite™ Purple Diamond Floor Pad Plus. 
	3. Apply 1 st coat, allow to dry. 	3. Apply 1 st coat, allow to dry. 
	4. Burnish with Scotch-Brite™ Purple Diamond Floor Pad Plus. 	4. Apply 2 nd coat, allow to dry. 
	5. Apply 2 nd coat, allow to dry. 	5. Burnish with 3M™ Tan Burnish Pad 3400. 
	6. Burnish with Scotch-Brite™ Purple Diamond Floor Pad Plus. Keep coating dry for 24 hours. 	
Ongoing Maintenance <i>Refer to Technical Bulletin for full maintenance instructions</i>	Clean regularly with 3M™ Red Buffer Pad 5100 or Scotch-Brite™ Clean & Shine Pad.  	Wait 24 hours after installation, then clean regularly with 3M™ Red Buffer Pad 5100. If substrate is concrete, Scotch-Brite™ Clean and Shine Pad may be used. 
	Intermittently burnish with Scotch-Brite™ Purple Diamond Floor Pad Plus. 	Intermittently burnish with 3M™ Tan Burnish Pad 3400. 
		If needed, remove deep scratches by burnishing with Scotch-Brite™ Purple Diamond Floor Pad Plus followed by 3M™ Tan Burnish Pad 3400.  
Recoat when floor no longer responds to burnishing with gloss improvement.		

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to 3M.com/SDS, or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501. When using any equipment, always follow the manufacturers' instructions for safe operation.

Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the **Customer Service Department at 1-800-852-9722**.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty

3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.