



3M™ Cubitron™ II Cut-off Wheels

Product Description

3M™ Cubitron™ II cut-off wheels are *Type 1 and Type 27*, reinforced resin-bonded wheels containing 3M-proprietary ceramic *Precision Shaped Grain (PSG)* mineral. The result of this is a cut-off wheel that yields a fast cut and extended life superior to that of its competitors. 3M™ Cubitron™ II cut-off wheels are ideal for mild steel, stainless steel, nickel alloys, and cast iron.

Technical Data

Mineral: 3M-Proprietary Ceramic *Precision Shaped Grain (PSG)*, 36+ or 60+/40+ blend

Construction: Resin bonded wheels with a reinforced construction for added safety and durability; INOX formulation ($Fe < 0.1\%$, $S < 0.1\%$, and $Cl < 0.1\%$) for stainless applications

Dimensions: 3", 4", 4.5", 5", 6" and 7" diameter, with thicknesses from 0.035" to 0.125"

Safety:



3M™ Cubitron™ II cut-off wheels conform to the following safety and quality standards:

ISO 9001/14001

EN 12413:2007

ANSI Safety Code B7.1-2010

FEPA member

- Tool must not exceed the maximum operation speed (*MOS*) of the wheel.
- Always use appropriate protective glasses, face shields, and body protection.
- Appropriate guarding and mounting hardware specific to cut-off wheels must be used at all times as per ANSI B7.1.
- Do not apply side pressure to any cut-off wheel; the edge is only to be used for cutting
- If a wheel has been dropped or suspected of having been damaged, it should not be used; this includes out of balance and warped wheels.

- The shelf life of all resin bonded cut-off wheels is 3 years from the date of manufacture (*FEPA standard*).
- Store in a cool, dry place.

Products:

	Dimension
7" x 0.090" x 7/8" (Type 27)	(180 x 2 x 22.23)
7" x 0.090" x 5/8"-11 (Type 27)	(180 x 2 x 5/8"-11)
7" x 0.045" x 7/8"	(180 x 1.6 x 22.23)
6" x 0.045" x 7/8"	(150 x 1.6 x 22.23)
6" x 0.045" x 7/8" (Type 27)	(150 x 1.6 x 22.23)
6" x 0.045" x 5/8"-11 (Type 27)	(150 x 1.6 x 5/8"-11)
5" x 0.090" x 7/8" (Type 27)	(125 x 2 x 22.23)
5" x 0.090" x 5/8"-11 (Type 27)	(125 x 2 x 5/8"-11)
5" x 0.045" x 7/8"	(125 x 1.6 x 22.23)
5" x 0.045" x 7/8" (Type 27)	(125 x 1.6 x 22.23)
5" x 0.045" x 5/8"-11 (Type 27)	(125 x 1.6 x 5/8"-11)
4.5" x 0.125" x 7/8" (Type 27)	(115 x 3 x 22.23)
4.5" x 0.125" x 5/8"-11 (Type 27)	(115 x 3 x 5/8"-11)
4.5" x 0.090" x 7/8" (Type 27)	(115 x 2 x 22.23)
4.5" x 0.090" x 5/8"-11 (Type 27)	(115 x 2 x 5/8"-11)
4.5" x 0.045" x 7/8" (Type 27)	(115 x 1.6 x 22.23)
4.5" x 0.045" x 5/8"-11 (Type 27)	(115 x 1.6 x 5/8"-11)
4.5" x 0.045" x 7/8"	(115 x 1.6 x 22.23)
4" x 0.125" x 3/8"	(100 x 3 x 9.53)
4" x 0.060" x 5/8"	(100 x 2 x 16)
4" x 0.060" x 3/8"	(100 x 2 x 9.53)
4" x 0.045" x 5/8" (Type 27)	(100 x 1.6 x 16)
4" x 0.045" x 5/8"	(100 x 1.6 x 16)
4" x 0.035" x 5/8"	(100 x 0.8 x 16)
4" x 0.035" x 3/8"	(100 x 0.8 x 9.53)
4" x 0.035" x 1/4"	(100 x 0.8 x 6)
	Dimension
3" x 0.060" x 3/8"	(75 x 2 x 9.53)
3" x 0.060" x 1/4"	(75 x 2 x 6)
3" x 0.035" x 3/8"	(75 x 0.8 x 9.53)
3" x 0.035" x 1/4"	(75 x 0.8 x 6)

IMPORTANT NOTICE TO PURCHASER:

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Abrasive Systems Division
3M Center Building 240-1-01
Saint Paul, MN 55144 USA

1-866-279-1235
www.3M.com/abrasives

3M and Cubitron are trademarks of 3M.
Please recycle. © 3M 2018. All rights reserved.