






Seam Sealer Removal		
1		<p>Clean Prewash/clean vehicle prior to disassembly (power wash undercarriage area at repair).</p>
2		<p>Protect Protect surrounding areas with masking tape.</p>
3		<p>Method A Use a Scotch-Brite™ Clean N Strip Disc to remove seam sealer and coatings where accessible.</p>
4		<p>Method B Use CRS Scotch-Brite™ Belt to remove coatings and seam sealers in hard to reach areas.</p>
5		<p>Clean Blow off the surface with clean dry air and then use a VOC compliant surface cleaner to remove any remaining residue.</p>

Product List	
<p>3M™ Car Wash Soap Concentrate, 3.7L, PN 38377</p>	
<p>3M™ All Purpose Cleaner and Degreaser Concentrate, 3.7L, PN 38350</p>	
<p>Scotch® Performance Green Masking Tape 233+, 18mm width</p>	
<p>Scotch-Brite™ Roloc™ Clean N Strip XT Disc CX-DR</p>	
<p>3M™ Scotch-Brite™ Roloc™+ Clean N Strip TR Disc, PN 07466</p>	
<p>3M™ Mini File Belt Sander, 330mm, PN 33573</p>	
<p>3M™ Scotch-Brite™ Durable Flex Belt, CRS</p>	
<p>3M™ 700 Adhesive Cleaner & Spray</p>	

Think About Your Health	
<p>3M™ E-A-R™ Skull Screws™ Ear Plug, PN P1300</p>	
<p>3M™ Half Face Welding Respirator Kit, PN 6228</p>	
<p>3M™ Solus™ 1000 Series Scotchgard™ Anti-fog Eyewear, PN S1201SGAF</p>	
<p>Not a complete list. Select protective eyewear, appropriate gloves, hearing protection, respirator and protective clothing based on your job and exposure assessment.</p>	