

3M™ Protecta® Comfort Belt Style Fall Arrest Work Positioning Harness with 1 Attachment Point

Part number(s):

1161625 Medium/ Large (M/L)

1161624 Small (S)

1161626 X-Large (XL)

Description

Sub-brand:	Protecta®
Industry:	Construction, general industry, telecom, utility, mining, transportation, general manufacturing
Applications:	Fall arrest, work positioning

Features

Rear fall arrest attachment point:	<ul style="list-style-type: none"> • Large D-ring <ul style="list-style-type: none"> – Steel - zinc plated black electro-deposition paint
Work positioning attachment points:	<ul style="list-style-type: none"> • Large bent D-ring <ul style="list-style-type: none"> – Steel - zinc plated black electro-deposition paint
Buckles:	<ul style="list-style-type: none"> • Pass-through buckles <ul style="list-style-type: none"> – Steel - zinc plated black electro-deposition paint
Adjustment:	<ul style="list-style-type: none"> • Legs, chest, torso, waist • Torso: Spring adjuster <ul style="list-style-type: none"> – Steel - zinc plated black electro-deposition paint
Webbing:	45 mm polyester
Thread:	Polyester
Additional features:	<ul style="list-style-type: none"> • Rear fall indicator • Hip padding • Auto-resetting lanyard keeper • Hook and loop web ends • Protected labels
Weight capacity:	140 kg
Operating temperature:	-35°C +57°C
Standards:	CE EN361:2002; EN358:1999




Front



Back

3M Protecta® Fall Arrest Harness sizing chart



Weight

	◀-----▶	⚖️ kg
1161624	Small (S)	1.77
1161625	Medium / Large (M/L)	1.82
1161626	X-Large (XL)	1.87

Important notice

Product Selection and Use: Many factors beyond 3M’s control and uniquely within user’s knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer’s application, including conducting a workplace hazard assessment and reviewing all applicable national and/or European regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: A limitation of liability applies to the 3M product(s). For warranty statement and limitation of liability, refer to your supply agreement or the 3M terms & conditions of sale.

3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use.

3M Personal Safety Division

3M United Kingdom PLC

3M Centre
Cain Road
Bracknell
RG12 8HT
United Kingdom
t: 0870 60 800 60
www.3M.co.uk/ppesafety

3M Ireland Limited

The Iveagh Building
The Park, Carrickmines
Dublin 18
Ireland
www.3M.co.uk/ppesafety

