

# 3M™ Protecta® Standard Vest Style Fall Arrest Harness with Horizontal Leg Straps and 2 Attachment Points

## Part number(s):

1161640 Medium / Large (M/L)

1161639 Small (S)

1161641 X-Large (XL)

## Description

<b>Sub-brand:</b>	Protecta®
<b>Industry:</b>	Construction, general industry, mining, transportation, general manufacturing
<b>Applications:</b>	Fall arrest, vertical ladder climbing

## Features

<b>Rear fall arrest attachment point:</b>	<ul style="list-style-type: none"> <li>▶ Large D-ring                             <ul style="list-style-type: none"> <li>– Steel - zinc plated black electro-deposition paint</li> </ul> </li> </ul>
<b>Front fall arrest attachment point:</b>	<ul style="list-style-type: none"> <li>▶ Standard D-ring                             <ul style="list-style-type: none"> <li>– Steel - zinc plated black electro-deposition paint</li> </ul> </li> </ul>
<b>Buckles:</b>	<ul style="list-style-type: none"> <li>▶ Pass-through buckles                             <ul style="list-style-type: none"> <li>– Steel - zinc plated black electro-deposition paint</li> </ul> </li> </ul>
<b>Adjustment:</b>	<ul style="list-style-type: none"> <li>▶ Torso, legs</li> <li>▶ Torso: Spring adjuster                             <ul style="list-style-type: none"> <li>– Steel - zinc plated black electro-deposition paint</li> </ul> </li> </ul>
<b>Webbing:</b>	45mm polyester
<b>Thread:</b>	Polyester
<b>Additional features:</b>	<ul style="list-style-type: none"> <li>▶ Front and rear fall indicators</li> <li>▶ 2x Auto-resetting lanyard keepers</li> <li>▶ Hook and loop web ends</li> <li>▶ Protected labels</li> <li>▶ Articulated rings</li> </ul>
<b>Weight capacity:</b>	140 kg
<b>Operating temperature:</b>	-35°C +57°C
<b>Standards:</b>	CE EN 361:2002




Front



Back

## 3M Protecta® Fall Arrest Harness sizing chart



## Weight

	←····→	⚖️
1161639	Small (S)	1.27
1161640	Medium / Large (M/L)	1.32
1161641	X-Large (XL)	1.37

## Important notice

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable national and/or European regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** A limitation of liability applies to the 3M product(s). For warranty statement and limitation of liability, refer to your supply agreement or the 3M terms & conditions of sale.

3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use.

### 3M Personal Safety Division

#### 3M United Kingdom PLC

3M Centre  
Cain Road  
Bracknell  
RG12 8HT  
United Kingdom  
t: 0870 60 800 60  
www.3M.co.uk/ppesafety

#### 3M Ireland Limited

The Iveagh Building  
The Park, Carrickmines  
Dublin 18  
Ireland  
www.3M.co.uk/ppesafety

