

Product Description

Scotch-Brite™ Surface Preparation Pad Plus is a floor maintenance deep scrubbing pad made of nylon fiber in an open-textured, non-woven construction. Specialized abrasive particles are bonded to the non-woven construction with a durable resin system.

Scotch-Brite™ Surface Preparation Pad Plus provides aggressive deep scrubbing performance while leaving a smooth surface to recoat.

Unique abrasive and construction scuffs the surface to create optimal bonding of the finish and conform to uneven surfaces.

- Designed to remove soiled top layers of floor finish using water or neutral cleaner instead of harsh stripping chemicals
- For use on standard, low-speed (150 - 400 RPM) automatic scrubbers and rotary machines



Application

This product is for use with neutral cleaner or water to remove layers of soiled or damaged floor finish without the slippery surface and harsh chemicals associated with standard floor strippers.

For use on finish-coated flooring such as wood, sheet vinyl, vinyl tile, marble, terrazzo, or concrete.

Special Features

- Specialized manufacturing process reduces the number of knots and clumps, which eliminates scratching of floors while providing greater consistency and extended pad life.
- Pad will not be significantly affected by water, detergents, or cleaners normally used for floor maintenance.
- Unique design reduces clogging during use.
- Scotch-Brite™ Surface Preparation Pad Plus does not require the use of a backer pad.
- Exacting standards for quality mean thickness uniformity from edge to edge and pad to pad is exceptional, resulting in consistent performance without pad wobble or machine vibration. The precise center-hole placement and roundness of the pads also contribute to the smooth operation, which extends pad life and may help reduce operator fatigue.

Directions for Use

1. Dust mop the entire floor prior to scrubbing.
2. Install an appropriately sized Scotch-Brite™ Surface Preparation Pad Plus on cleaning equipment. Scotch-Brite™ Surface Preparation Pad Plus can be used on automatic scrubbers, rotary floor machines without a backer floor pad.
3. Wet the floor with water or neutral cleaner and scrub the floor to the desired result.
4. Both sides of the pad can be used.
5. When desired, the pad can be flipped.
6. Pick up dirty solution with a mop, wet vacuum, or automatic scrubber.
7. Rinse the floor and let it dry prior to recoating or opening to traffic.
8. Pads may be rinsed with water to clean if desired.

Maintenance and Cleaning

- Remove the floor pad from the machine after each use
- Wash and rinse under tap water
- Hang up to dry

Note: Do not machine wash!

Product Characteristics

The values displayed are the results of illustrative lab test measures and shall not be considered as a commitment from 3M.

Fiber Type:	Nylon
Weight:	1100 g/m ²
Thickness:	20 mm
Packaging:	Recycled Content: 50 - 100% post-consumer recycled material
Color:	Maroon
Printing:	No printing
Center hole:	Pre-cut at 85 mm
Durability:	2,000 sqm at 150 RPM in standard use with appropriate maintenance

Packaging

Each carton shall be labelled to identify the contents by product name, size, quantity, and manufacturer.

Standard Sizes

Circular discs are available in a variety of common sizes.

Storage Conditions and Shelf Life

Storage conditions: +4°C to +40°C, out of sunlight, original container in a clean and dry indoor area.

Precautionary Summary

Do not use on soft metal and plastic surfaces, painted surfaces, or other surfaces that are easily scratched.

Health and Safety

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information.

[Follow the link to obtain SDS sheets for 3M products on 3M.com/SDS.](https://www.3m.com/SDS)

[Follow the link to obtain information about substances of very high concern \(SVHC\).](#)

IMPORTANT!

- When using any equipment, always follow the manufacturer's instructions for safe operation.
- This floor pad is for professional or industrial use only.



DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:

DO NOT use this product on any asbestos-containing material.



WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

To reduce the risks associated with environmental contamination:

- Dispose of waste and slurries generated from wet polishing in accordance with all applicable local and government regulations.



CAUTION

The product is intended for wet floor maintenance processes only. DO NOT use this product in any dry application.

Warranty Information

Limited Remedy

This bulletin provides technical information only.

3M recommended product end uses are listed in each 3M product bulletin. End uses not listed in the applicable 3M Product Bulletins are typically not eligible for 3M Warranties. For non-recommended and/or non-warranted end uses or applications, users must test and approve the end uses or applications, assume any associated risks, and acknowledge that 3M has no liability for such end uses or applications. Please contact your 3M representative with any questions about applications, end uses, and warranties.

Limitations of liability

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

3M and Scotch-Brite are trademarks of 3M. All other trademarks are the property of their respective owners.

3M United Kingdom PLC

Commercial Branding and Transportation
Cain Road
Bracknell, RG12 8HT
UK

© 3M 2025. All rights reserved.