


# 3M™ Cold Shrink QS-III 3-Conductor Inline Splice Kits 5786A-MT, 5787A-MT and 5788A-MT

25/28 kV for use with Armored and Non-Armored 3/C Cable



Data Sheet

October 2019

## Description

3M™ Cold Shrink QS-III 3-Conductor Inline Splice Kits 5786A-MT, 5787A-MT and 5788A-MT are designed for splicing 3-conductor, armored and non-armored, shielded power cables. The kits are rated for use on 25/28 kV cables with conductor sizes from 1 AWG to 1000 kcmil (50 to 500 mm<sup>2</sup>). The kits are designed to be used with 3M™ Scotchlok™ Connectors 10000 and 20000 Series or other UL listed inline compression connectors that fit within the dimension limits listed in the Connector Dimensional Requirements Table.

The splice utilizes several technologies to accommodate the various functions of a 3-conductor shielded power cable; 3M™ Cold Shrink QS-III Splice Bodies, Scotch® Electrical Tapes for moisture sealing, Constant Force Springs for connecting ground braid jumpers and 3M™ Sheath Wrap for replacing the cable armor and/or jacket. The completed splice is designed for use in cable trays; weather exposed or direct burial locations.

## Kit Contents

Each kit contains the following materials:

- 3 3M™ Cold Shrink QS-III Splice Bodies
- 3 3M™ Cold Shrink Adapter Tubes (6 in 5786A-MT)
- 6 Tubes, 3M™ Red Compound P55/R
- 3 Metallic Shield Sleeves
- 6 Constant Force Springs (small)
- 1 Amor to Armor Continuity Braid (6 AWG)
- 2 Constant Force Springs (large) (not include in 5788A-MT Kit)
- 2 Cold Shrink Jacket Tubes (not included in 5788A-MT kit)
- 1 3M™ Cable Cleaning Preparation Kit CC-2
- 1 Roll, Scotch® Super 33+™ Vinyl Electrical Tape
- Rolls of Scotch® Vinyl Electrical Tape Super 88 (4 in 5786A-MT, 5 in 5787A-MT, 10 in 5788A-MT)
- Rolls of 3M™ Scotch-Seal™ Mastic Tape Compound 2229 (3 in 5786A-MT, 4 in 5787a-MT, 10 in 5788A-MT)
- 1 Roll, Scotch® Electrical Shielding Tape 24
- 1 Roll, Scotch® Rubber Mastic Tape 2228 (not included in 5788A-MT)
- Rolls of 3M™ Sheath Wrap (5 in 5786A-MT, 6 in 5787A-MT, 8 in 5788A-MT)
- 1 Instruction Sheet
- 6 Copper Foil Tape Strips
- Gloves

**Features**

- **Cold Shrink Splice Body Design** – for quick and easy installation; excellent for cable size transitions
- **Production Tested Splice Bodies** – partial discharge and A.C. withstand tests to provide reliability
- **Silicone Rubber Splice Bodies** – provide excellent high and low temperature performance; flexibility that allows the splice to bend with cable (prior to applying jacket materials)
- **Complete Kit** – everything included to make one 3-conductor splice (except connectors)
- **Solderless Ground Braid** – constant force spring connection (no soldering required)
- **3M™ Sheath Wrap** – easy to apply mechanical protection for the splice

---

**Applications**

To splice 3-conductor shielded power cables:

- For inline splicing
- For armored and non-armored cables
- For 25/28 kV rated cables
- For cable conductor size range 1 AWG to 1000 kcmil
- For use with solid dielectric cables: XLP, XLPE, EPR, etc.
- For indoor and outdoor applications:
  - Cable Tray
  - Cable Rack
  - Cable Hangers
  - Junction Box
  - Aerial
  - Wet or dry locations

---

**Installation**



**Caution**

Working around energized electrical systems may cause serious injury or death. Installation should be performed by personnel familiar with good safety practice in handling electrical equipment. De-energize and ground all electrical systems before installing product.

Detailed instructions for installing the 3M™ Cold Shrink QS-III 3-Conductor Inline Splice Kits 5786A-MT, 5787A-MT and 5788A-MT are included with the kit.

1. Prepare the cable according to standard practices.
2. Slide the cold shrink jacketing tubes onto the cables.
3. Slide a cold shrink splice body and shield sleeve on each conductor phase.
4. Install connector.
5. Apply red compound on the cable insulation and to fill the edge of the cable semi-con. **DO NOT USE SILICONE GREASE.**
6. Install the splice bodies.
7. Connect shields using shield sleeves and constant force springs.
8. Cover splice end with cold shrink jacket tubes.
9. Seal between the jacket tubes with mastic tape.
10. Cover entire splice area with Sheath Wrap.

**Typical Properties**

3M™ Cold Shrink QS-III 3-Conductor Inline Splice Kits 5786A-MT, 5787A-MT and 5788A-MT can be used on cables with a rated operating temperature up to 105°C (221°F), and in emergency overload rating of 140°C (284°F). A splice constructed from either of these kits is rated for 25/28 kV and meets or exceeds the requirements of IEEE Std. 404. The current rating of the splices meets or exceeds the current rating for the cables on which they are installed. BIL rating is 200kV, which exceeds the normal 150 kV BIL rating for 25/28 kV voltage class splice.

**A. Splice Selection Table**

Kit Number	Cable Insulation O.D. Range Inches (mm)	Conductor Size Range AWG or kcmil (mm <sup>2</sup> )
5786A-MT	0.84-1.36 (21,3-34,5)	1-250 (50-120)
5787A-MT	1.07-1.70 (27,2-43,2)	250-750 (120-325)
5788A-MT	1.24-2.07 (31,5-52,6)	500-1000 (240-500)

**Table 1**

**B. Connector Dimensional Requirements Table**

Kit Number	Minimum O.D. Inches (mm)	Maximum O.D. Inches (mm)	Maximum Length Inches (mm)	
			Aluminum (Al/Cu)	Copper (Cu)
5786A-MT	0.46 (11,7)	1.36 (34,5)	4.00 (102)	4.50 (114)
5787A-MT	0.75 (19,1)	1.70 (43,2)	5.75 (146)	6.50 (165)
5788A-MT	1.05 (26,7)	2.07 (52,6)	7.50 (191)	8.25 (210)

**Table 2**

**C. Typical Dimensions (Installed Splice)**



Kit Number	Typical Length (L) Inches (cm)	Typical Diameter (D) Inches (mm)
5786A-MT	57 (145)	7.50 (191)
5787A-MT	62 (158)	8.00 (203)
5788A-MT	66 (168)	8.50 (216)

**Table 3**

**Typical Properties,**  
*Continued*

Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.

**Silicone Rubber (Splice Body – Insulation)**

Physical Property (Test Method)	Typical Value US units (metric)
Hardness – Shore A (ASTM D-2240)	50
Tensile Strength (ASTM D-412)	1090 psi (7,5 N/mm <sup>2</sup> )
Elongation (ASTM D-412)	610%
Modulus @ 100% (ASTM D-412)	340 psi (2,3 N/mm <sup>2</sup> )
Permanent Set (3M TM 86) 100%, 100°C, 22 hrs	5%
Thermal Conductivity (ASTM D-518)	4 W/m K

Electrical Property (Test Method)	Typical Value US units (metric)
Dielectric Strength (ASTM D-149)	370 V/mil (14,6 kV/mm)
Dielectric Strength, Wet (ASTM D-149)	340 V/mil (13,4 kV/mm)
Dielectric Constant (ASTM D-150)	3.3
Dielectric Loss (ASTM D-150)	0.005
Volume Resistivity (3M TM 80)	6 x10 <sup>14</sup> Ohm-cm

**Silicone Rubber (Splice Body – Inner Electrode)**

Physical Property (Test Method)	Typical Value US units (metric)
Hardness – Shore A (ASTM D-2240)	43
Tensile Strength (ASTM D-412)	880 psi (6,1 N/mm <sup>2</sup> )
Elongation (ASTM D-412)	510%
Modulus @ 100% (ASTM D-412)	200 psi (1,4 N/mm <sup>2</sup> )
Permanent Set (3M TM 86) 100%, 100°C, 22 hrs	4%

Electrical Property (Test Method)	Typical Value US units (metric)
Volume Resistivity (3M TM 80)	50 Ohms

**Typical Properties,  
Continued**

Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.

**Silicone Rubber (Splice Body – Semi-Con Shell)**

Physical Property (Test Method)	Typical Value US units (metric)
Hardness – Shore A (ASTM D-2240)	43
Tensile Strength (ASTM D-412)	890 psi (6,1 N/mm <sup>2</sup> )
Elongation (ASTM D-412)	520%
Modulus @ 100% (ASTM D-412)	230 psi (1,6 N/mm <sup>2</sup> )
Permanent Set (3M TM 86) 100%, 100°C, 22 hrs	5%

Electrical Property (Test Method)	Typical Value US units (metric)
Volume Resistivity (3M TM 80)	150 Ohm-cm

**Ethylene Propylene Rubber (Jacketing Tubes)**

Physical Property (Test Method)	Typical Value US units (metric)
Color	Black
Hardness – Shore A (ASTM D-2240)	48
Ultimate Tensile Strength (ASTM D-412)	1680 psi (11,6 MPa)
Ultimate Elongation, orig. (ASTM D-412)	635%
Modulus @ 100% (ASTM D-412)	170 psi (1,17 MPa)
Fungus Resistance (ASTM G-21) 28 days	No Growth
Permanent Set 250% Strain 5 min. recovery, @ 40°F (4,4°C)	8.8% 14.6%

Electrical Property (Test Method)	Typical Value US units (metric)
Dielectric Strength, orig. (ASTM D-149)	490 (19,1 kV/mm)
Dielectric Strength, Wet ASTM D-149)	465 (18,1 kV/mm)
Dielectric Constant, orig. (ASTM D-150)	5.0
Dielectric Constant, wet (ASTM D-150)	5.6

NOTE: Data for Scotch® Electrical Shielding Tape 24, Scotch® Rubber Mastic Tape 2228, 3M™ Scotch-Seal™ Mastic Compound 2229, Scotch® Super 33+™ Vinyl Electrical Tape, Scotch® Vinyl Electrical Tape Super 88, and 3M™ Sheath Wrap that are included in the kits are available in separate “Product Data Sheets” from 3M Company.

**Performance Tests**      **A. IEEE Std. 404 25/28 kV Voltage Rating**

Design Test and Sequence	Test Requirement
Minimum partial discharge (corona) level	22 kV-rms @ < 3 pC
Alternating-current 1 minute withstand	58 kV-rms
Direct-current 15 minute withstand	112 kV-dc
Impulse with stand (BIL) at 25°C (77 °F)*	±150 kV-crest (200 kV)*
Impulse with stand (BIL) at 140°C (284 °F)*	±150 kV-crest (200 kV)*
Cyclic aging (in air and water)	48 kV - rms
Minimum partial discharge (corona) level	22 kV – rms @ < 3 pC
High voltage time: 5 hr. alternating-current withstand 5 min. alternating-current withstand	58 kV – rms 75 kV - rms
Short-time current: ICEA P-32 and ANSI/IEEE C37.09	250°C (482°F) conductor temp with no damage
Alternating-current 1 minute withstand	58 kV – rms
Shielding	IEEE Std. 592
Connector thermal and mechanical	ANSI C119.4

\*See Notes next page

**B. IEEE Std. 404 25/28 kV Voltage Rating, *continued***

Production Test	Test Requirement
Production splices tested	100%
Minimum partial discharge (corona) level	22 kV – rms @ < 3 pC
Alternating-current 1 minute withstand	58 kV – rms

- \*Notes: 1) BIL rating for 3M cold shrink QS-III splices 5786A-MT (5456A splice body), 5787A-MT (5457A splice body) and 5788A-MT (5458A splice body) are upgraded to ±200 kV – crest.  
2) Impulse test wave is 1.2 x 50 µsec. (ANSI/IEEE Std. 4).

**C. Operating Temperature - Reference: AEIC CS5 and AEIC CS6:**

**Normal Operation:** 105°C (221°F)      **Emergency Operation:** 140°C (284°F)

## 3M™ Cold Shrink QS-III 3-Conductor Inline Splice Kits 5786A-MT, 5787A-MT and 5788A-MT

---

**Product Specification**  
(Open Specification) 3M™ Cold Shrink QS-III 3-Conductor Inline Splice Kits 5786A-MT, 5787A-MT and 5788A-MT, armored or non-armored, shielded power cable splice shall meet the requirements of ANSI/IEEE Std. 404, for a 25/28 kV rating, and must be rated by the manufacturer for use on 3-conductor 25/28 kV class shielded power cable systems. It must be rated for continuous operation at 105°C (221°F), with an emergency overload temperature rating of 140°C (284°F). The splice shall be capable of splicing cables with copper or aluminum conductors sized from 1 AWG to 250 kcmil (50 to 120 mm<sup>2</sup>), 250 to 750 kcmil (120 to 325 mm<sup>2</sup>) and 500 to 1000 kcmil (240 to 500 mm<sup>2</sup>), or accommodate a conductor size transition within those size ranges. The splice shall be of a cold shrink design, which does not require any additional heat source for installation. The cold shrink splice body must be of a molded design made of silicone rubber. The splice jacketing system shall be comprised of at least two of the following items: cold shrink tubing made of EPDM rubber, mastic sealing tape, and a resin-impregnated fiberglass cloth. The color of the splice body and outer jacket shall be black.

---

**Engineering/  
Architectural**  
(Closed Specification) Splicing of all 25/28 kV rated, 3-conductor, armored or non-armored shielded power cables, sized from 1 AWG to 1000 kcmil (50 to 500 mm<sup>2</sup>) with copper or aluminum conductors shall be performed in accordance with the 3M Cold Shrink QS-III Splice Kits 5786A-MT, 5787A-MT and 5788A-MT 25/28.

---

**Maintenance** The installed splices can be field tested using standard cable testing procedures (reference ANSI-IEEE Std. 400, "Guide for Making High-Direct-Voltage Tests on Power Cable Systems in the Field").

---

**Shelf Life & Storage** This product has a 3-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

---

**Availability** Please contact your local distributor; available from [3M.com/electrical](http://3M.com/electrical) [Where to Buy] or call 1-800-245-3573.

---

**Connectors for QS-III Splices**

The 3M™ Cold Shrink QS-III 3-Conductor Inline Splice Kits 5786A-MT, 5787A-MT and 5788A-MT are designed to be used with 3M™ Scotchlok™ Connectors 10000, 11000, and 20000 Series, 3M™ CI-T Series, or other UL listed inline compression connectors that fit within the dimension limits listed in the Connector Dimensional Requirements Table 2. In addition, the following transition connectors may be used:

Kit Number	Conductor Sizes (AWG or kcmil)	Homac Connectors	Burndy Connectors	Mac Products	3M Connectors
5786A-MT	1 to 1/0				CI-T9
	1/0 to 3/0	SAC3/OR1/A	YRB27U26	MILCR E/0-1/0	
	2/0 to 1			MLCR 2/0-1	
	2/0 to 3/0		YRB27U26		
	1/0 to 4/0	SAC4/OR1/0			
	2/0 to 4/0	SAC4/OR2/0	YRB28U26	MLCR 4/0-2/0	
	3/0 to 4/0				CI-T7
	2/0 to 250	SAC250R2/0			
	3/0 to 250	SAC250R3/0		MLCR 250-3/0	
5787A-MT	4/0 to 250	SAC240R4/0			
	250 to 350	SAC50R250	YRB31U29		2000T 250-350 CU/AL
	350 to 500	SAC1000R500		MILCR 1000-750 plus AAR 750-500	2000T 350-500 CU/AL
5788A-MT	500 to 750		YRB39U34		
	500 to 750	SAC750R500	YRB39U34	MLCR 750-500	
	500 to 1000	SAC1000R500		MILCR 1000-750 plus AAR 750-500	
	750 to 1000	SAC1000R750		MLCR 1000-750	

3M, Scotch, Scotch-Seal, Scotchlok and Super 33+ are trademarks of 3M Company.

**Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

**Warranty; Limited Remedy; Limited Liability**

This product will be free from defects in material and manufacture at the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any direct, indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



**Electrical Markets Division**

Austin, TX  
 800.245.3573  
 Fax: 800.245.0329  
[www.3m.com/electrical](http://www.3m.com/electrical)

Please recycle  
 © 3M 2019. All rights reserved  
 78-8126-0910-1 Rev C