



# Marine Fast Cure UV Resistant Adhesive Sealant 4000UV

## Product Data Sheet

Date: September 2022  
Supersedes: February 2013

**Product Description** 3M™ Marine Fast Cure UV Resistant Adhesive Sealant 4000UV is a one-part sealant that cures to form a firm, rubbery waterproof seal. Its flexibility allows for the dissipation of stress caused by shock, vibration, swelling or shrinking. Designed for marine applications above and below the waterline. Its superior UV resistant properties make this an ideal cosmetic sealant.

- Key Features**
- Superior UV resistance
  - Exceptional sealing properties
  - < 1%VOC
  - Low odour
  - Non-shrinking
  - Non-sagging
  - Non-corrosive
  - Non-cracking
  - Caulkable at low temperatures (-40°C)
  - Fast curing
  - Paintable (test for suitability)

### Technical Data

Base	MS Polymer
Appearance	Pasty
Colour	White
Density (g/ml) (DIN EN ISO 2811-2)	Black: 1.14 ± 0.05
Sagging (mm) (ISO 7390)	None
Application temperature	5°C to + 35°C
Skin formation time (min) (ISO 291, 23°C, 50% RH)	30 to 60 min
Cure time, mm/24h (ISO 291, 23°C, 50% RH)	>3 mm/24 h
Service Temperature	-40°C to 90°C
Shore A Hardness (ISO 868-3 seconds)	40 to 60
Consistency	Pasty
Resistance to dilute acids and bases	Good
Water and salt spray resistance	Excellent
Consistency	Pasty
Elongation at Break (ISO 37)	>100 %
Modulus at 100% (ISO 37)	>0.6 MPa
Compatibility with paints	Water based : yes / Solvent based : carry out tests beforehand

---

<b>Heat Resistance:</b>	Long term exposure to temperatures greater than 80°C will decrease tensile strength over time. For this reason these products should not be used in applications where the temperatures will continuously exceed 80°C.
-------------------------	--

---

<b>Direction for use</b>	<p><b>Surface Preparation:</b> Surfaces to be sealed or bonded must be clean and dry. Surfaces should be free from grease, mould release, oil, water/condensation and other contaminants that may affect the adhesion of the sealant. Abrading with 180 to 220 grit abrasive followed by a solvent wipe will improve the bond strength. Suitable solvents include 3M™ Citrus Based Adhesive Remover, 3M™ Scotch-Weld™ Solvent No. 2 or methyl ethyl ketone (MEK).*</p> <p><b>*When using solvents, use in a well ventilated area. Extinguish all sources of ignition in the work area and observe product directions for use and precautionary measures. Refer to product label and MSDS for further precautions. Always pre-test solvent to ensure it is compatible with substrates.</b></p> <p><b>Local and federal air quality regulations may regulate or prohibit the use of this product or surface preparation and cleanup materials. Consult local and federal air quality regulations before using these products.</b></p> <p>Use of a primer is an extra step and cost and will depend on substrates and the final end use. Using primer can improve the corrosion resistance of certain metals as well as improve the durability of the bond when exposed to high humidity conditions. For most applications high strength bonds on metal can be achieved without the use of a primer. Pre-testing for adhesion is suggested to determine if a primer is needed. The 3M™ Scotch-Weld™ Structural Adhesive Primer EC-1945 B/A works well for most metals.</p>
--------------------------	---

---

<b>Application:</b>	Puncture seal in nozzle and knock out the thin seal at cartridge bottom before placing in caulking gun. Assemble tip and retaining ring on gun, cut tip to desired size. Product should be used within 24 hours after seal is punctured and should be pressed firmly into the joint to ensure adequate contact of the sealant with the substrate. Apply product when temperatures are between 5°C and 35°C. Do not apply on frozen surfaces or wet surfaces. Do not apply over silicones or in the presence of curing silicones. Avoid contact with alcohol and solvents during curing. Sealant can be tooled immediately after applying to give desired appearance.
---------------------	--

---

<b>Cleanup:</b>	While sealant is still soft cleaning can be done with the same solvents used for surface preparation. If sealant is already cured, removal is done mechanically with razor knife, piano wire, sanding or 3M™ Scotch-Brite™ Moulding Adhesive and Stripe Removal Disc. This disc is available from 3M Automotive Aftermarket Division.
-----------------	---

---

<b>Application Equipment Suggestions</b>	<b>Cartridge and Flex Pack:</b> For ease of dispensing an all metal, rod driven, friction feed manual applicator gun or an air operated applicator gun is suggested. Please contact your 3M sales representative for these items.
--	--

**Bulk Dispensing:**

For bulk dispensing a 46:1 ratio dual action piston pump with a ram is suggested. Actual equipment is dependent on the fluid flow desired, the number of guns to be supplied for each pump and distance product has to be pumped. It is best to consult with the equipment supplier to make sure the proper type and size of equipment is specified. Common suppliers of this type of pumping systems are Graco and Binks. It is best to work with a distributor for Graco or Binks located in your area. Our technical service group will be glad to work with you and your chosen supplier to ensure the proper equipment is selected.

---

<b>Shelf Life</b>	12 months in the original, hermetically sealed packaging between 5°C and 25°C after date of manufacture
<b>Precautionary Information</b>	Refer to product label and Material Safety Data Sheet for health and safety information before using the product. For information please contact your local 3M Office. <a href="http://www.3M.com">www.3M.com</a>
<b>For Additional Information</b>	To request additional product information or to arrange for sales assistance, go to <a href="http://www.3M.be/bonding">www.3M.be/bonding</a> or <a href="http://www.3M.nl/bonding">www.3M.nl/bonding</a>
<b>Automotive Disclaimer</b>	<p>Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by the Technical Director of 3M's Automotive Division. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer's use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product.</p>

NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

---

**Important Notice**

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

---

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

---

3M is a trademark of the 3M Company.



Industrial Adhesives & Tapes Division  
3M Belgium  
Hermeslaan 7  
1831 Diegem  
Belgium

Industrial Adhesives & Tapes Division  
3M Nederland  
Molengraafsingel 29  
2629 JD Delft  
Nederland