

8 U h Y d h Y a V Y f ' & S & &
) () ' ' ' H Y Z ` c b ` ' ; ` U g g
7 ` c h \ ` H U d Y `

| | | |
|------------------------|---|---|
| Application Techniques | Best results are attained when applied to a clean, dry and non dusty surface above 0°C. | To improve adhesion ensure firm and even application pressure is applied. |
|------------------------|---|---|

| | | |
|--------------|---|--|
| Applications | <p>Easy release surface on packaging and heat sealing machines, ironing and pressing equipment.</p> <p>Easy release surface coating on metal bonding tools.</p> | <p>Lining conveying chutes, troughs, ducts and baking equipment.</p> <p>Printing: hot-lead mat assembly, printing delivery boards, cover guides and idler rolls.</p> |
|--------------|---|--|

Applications

Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by the Technical Director of 3M's Automotive Division. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer's use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product.

NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

| FEATURES | ADVANTAGES | BENEFITS |
|----------------------------|--|--|
| Thick glass cloth backing. | Prolonged wear life. High impact and puncture resistance. | High productivity. Prolongs life of parts, tools and equipment. |
| | Excellent tensile and tear strength. | |
| Thick Teflon coating. | Exceptionally smooth surface. Provides non-stick, low friction surface. | Saves clean-up time. Long lasting. |
| | Resists most chemicals and corrosive action of solvents, salts and acids. | Protects surfaces. Prolongs parts and equipment life. |
| Silicone adhesive. | High temperature performance. Long ageing. | Higher productivity. |

3M is a trademark of the 3M Company.
"Teflon" is a trademark of DuPont.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



| | |
|--|---|
| <p>Industrial Adhesives & Tapes Division 3M Belgium Hermeslaan 7 1831 Diegem Belgium</p> | <p>Industrial Adhesives & Tapes Division 3M Nederland Molengraafsingel 29 2629 JD Delft Nederland</p> |
|--|---|