

Product Features and Benefits

- Micro-layered film designed for tear resistance
- Optically clear
- Applies to interior glass surfaces
- Helps protect from broken glass hazards
- Helps extend the life of furnishings by significantly reducing harmful UV rays

Applications

- Bomb Blast Mitigation
- Safety Glazing
- Helping to Deter Break & Entry
- Building Envelope Protection
- Spontaneous Glass Breakage
- Seismic Preparedness

Performance Testing

Method	Glass Substrate	Film Attachment	Rating	
Safety Glazing				
16 CFR 1201	¼" & 1/8" annealed	--	Category 2, 400 ft-lbs	
ANSI Z97.1			Class A (Unlimited), 400 ft-lbs	
Impact Resistance				
ASTMs E1886 / E1996	3/16" tempered	IPA	Missile Level A, +/- 80 psf	
ASTM E330			+/- 100 psf	
Blast Mitigation			Blast Load	Rating
GSA TS01-2003 / ASTM F1642	¼" annealed	IPA	6 psi, 42 psi*msec	GSA Level 2 / ASTM "Minimal Hazard"
		IPP	6 psi, 42 psi*msec	GSA Level 2 / ASTM "Minimal Hazard"
	¼" tempered	IPA	6 psi, 42 psi*msec	GSA Level 2 / ASTM "No Hazard"
		IPP	6 psi, 42 psi*msec	GSA Level 2 / ASTM "Minimal Hazard"
	1" double pane (annealed)	IPA	9 psi, 60 psi*msec	GSA Level 2 / ASTM "Minimal Hazard"
		IPP	8 psi, 60 psi*msec	GSA Level 2 / ASTM "Minimal Hazard"

*Glazing systems vary. Contact 3M for more information.

Film Properties (nominal)

Film Thickness	6 mils
Film Construction	Micro-layered
Tensile Properties (ASTM D882)	
Tensile Strength	32,000 psi
Break Strength	210 lbs/in
Elongation at Break	115%
Yield Strength	15,000 psi
Elongation at Yield	9%
Modulus	443 kpsi
Graves Area Tear Resistance (ASTM D1004)	900 lbs% (MD) / 1,100 lbs% (TD)
Puncture-Propagation-Tear Resistance (ASTM D2582)	6 lbf

Puncture Strength (ASTM D4830)	140 lbf
Abrasion Resistance (ASTM D1044)	3% Δ haze
Peel Strength (ASTM D3330)	8 lb/in
Flammability (ASTM E84)	Class A
Solar Properties – film applied to 1/4" clear glass	
Visible Light Transmitted	87%
UV Light Rejected	99.9%

IMPORTANT NOTICE:

This product is **not approved** in the State of Florida for use as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. In compliance with Florida Statute 553.842, this product may not be advertised, sold, offered, provided, distributed, or marketed in the State of Florida as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm.

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M

Commercial Solutions Division

3M Center, Building 220-12E-04 St. Paul, MN 55144
3M.com/windowfilm

© 3M 2019. All rights reserved.

3M is a trademark of 3M. Used under license in Canada.

All other trademarks are property of their respective owners. Revision A, April 2019. Please recycle.



Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to 3M.com/SDS, or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501. When using any equipment, always follow the manufacturers' instructions for safe operation.

Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the Customer Service Department at 1-800-852-9722.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty

3M warrants that each 3M product will be free from defects in material and manufacture for the length of the product warranty. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

IMPORTANT NOTICE:

This product is **not approved** in the State of Florida for use as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. In compliance with Florida Statute 553.842, this product may not be advertised, sold, offered, provided, distributed, or marketed in the State of Florida as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm.

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M

Commercial Solutions Division

3M Center, Building 220-12E-04 St. Paul, MN 55144
3M.com/windowfilm

© 3M 2019. All rights reserved.

3M is a trademark of 3M. Used under license in Canada.

All other trademarks are property of their respective owners. Revision A, April 2019. Please recycle.

