

LifeASSURE™ BNA020 Series

Log Reduction Grade Filters

0.2 µm rated filters for bottled water & beverage microbiological stability

The LifeASSURE™ BNA020 series filter helps bottled water and other beverage processors meet high standards for microorganism control. Combined with 3M Purification Inc.'s range of particle control and prefilters, LifeASSURE BNA020 series filters offer bottlers a complete solution for rigorous contaminant control while maintaining long service life and low operating costs

Durable Design

The LifeASSURE BNA020 a series filter membrane and cartridge design innovations result in a durable filter cartridge, capable of secure operation through numerous cycles of hot water sanitation, steam sterilization, and standard chemical based cleaning and sanitation.

Advanced Technologies

Highly Asymmetric Membrane

LifeASSURE series filters incorporate a novel single-layer with a high degree of asymmetry (Figure 1. on the next page). When viewed in cross-section, the membrane contains larger pores on the upstream surface that gradually taper to smaller pores towards the downstream surface. Compared to conventional membranes with a symmetric pore structure, this structure provides greater contaminant capacity, since it presents greater open spaces (void volume) in which to retain these contaminants. This increase in capacity leads directly to longer service life. In addition, the asymmetric structure provides less resistance to flow, resulting

in a lower pressure drop when compared at a constant flow rate to competitive filters, allowing a user to employ fewer LifeASSURE BNA020 series filters for any given flow rate.



Applications

LifeASSURE™ BNA020 Series filters are optimized for Food & Beverage applications requiring reduction of fine particles and microorganisms at the 0.2 micron level.

- Bottled Water
- Soft Drinks
- Process Water
- Intermediates & Ingredients
- Syrups
- Dyes & Flavors

Features & Benefits

0.2 µm rated membrane

- Reliable LRV microorganism control

Asymmetric polyether sulfone (PES) membrane

- Exceptionally high capacity and service life to help maximize economy

Advanced Pleat Technology Construction

- Allows superior fluid and contaminant access to filter surface area for greatest service life and flow rates

CFR 21 Listed Materials of Construction, filter cartridges are compliant with Regulation (EC) 1935/2004, USP Biological Reactivity for Plastics Test—Class VI, Technical Support Guide

- Eases regulatory concerns

Advanced Pleat Technology Design

LifeASSURE™ BNA020 series filters feature Advanced Pleat Technology (APT) design for extended service life. This design technology helps to maximize the useful surface area of the filter while maintaining open flow paths between the media pleats (refer to Figure 2.) By employing the APT design, the LifeASSURE BNA020 filter provides lower pressure drops, longer service life, and lower overall operational costs.




Figure 1. SEM Photograph Showing LifeASSURE™ BNA020 Series Filter Membrane Cross-Section




Figure 2. - Advanced Pleat Technology

Novel Media Support Design

LifeASSURE BNA020 series filter employ a design that results in higher beverage flow versus pressure drop compared to competitive filters. This 3M Purification development combines the high flowing PES membrane with special support layers upstream and downstream of the membrane. When combined with the previously mentioned APT, this feature greatly increases flow per cartridge, and results in lower overall operational costs.

Advanced Performance

Extended Service Life

In the majority of beverage applications, the final membrane filter is used in a continuous (as opposed to a batch) operation. Its service life is measured either by the volume filtered, or the number of days in service, before becoming permanently blocked. Filters that provide longer service life not only reduce direct operational costs, but also reduce indirect filter costs as well (filter change-out/installation labor, downtime between change-outs, filter flushing, etc.). The LifeASSURE BNA020 series filter's combination of highly asymmetric PES membrane, APT design, and novel upstream/downstream supports all work together to maximize the volume of beverage that can be processed.

Microbiological Control

The primary purpose of a membrane filter cartridge in bottled water and beverage processing is to effectively control even the smallest microorganisms. LifeASSURE BNA020 series 0.2 µm rated filters provide superior retention of common spoilage

microorganisms, even at challenge concentrations that far exceed those experienced by most beverage producers. LifeASSURE BNA020 series membrane has been shown to provide Log Reduction Values (LRV) in excess of 7 with *Brevundimonas diminuta* (*B. diminuta*) (ATCC 19146) and *Pseudomonas aeruginosa* (*Ps. aeruginosa*) at a concentration of 10⁷ CFU/cm² or greater.

LifeASSURE™ BNA020 Series Filters	Microorganism	Retention Level
BNA020	<i>B. diminuta</i>	LRV > 7
BNA020	<i>Ps. aeruginosa</i>	LRV > 7

Fast Flow Rates at Low Pressure Drops

3M Purification has combined three key technological advances to provide a fast flow rate per unit of pressure drop. These three technologies, APT design, a novel upstream and downstream support design, and a highly asymmetric microporous membrane, afford users with faster process flow rates using fewer filters as compared to alternative filters.

Initial Clean Pressure Drop* (water) for a 30" Filter Flowing at 20 gpm (76 lpm)	
LifeASSURE™ BNA020 Series Filter	2.2 psid (152 mbar)
Competitor A	3.7 psid (200 mbar)
Competitor B	5.8 psid (400 mbar)
Competitor C	4.5 psid (310 mbar)

As the example above illustrates, the pressure drop at a given flow rate for LifeASSURE BNA020 series filters can be significantly lower compared to competitive filters. Since filter change-out is usually tied to a terminal differential pressure drop (typically between 20 and 35 psid), employing filters that exhibit a lower initial pressure drop can result in longer filter service life.

Alternatively, in a system when determining the number of filters needed to provide a desired flow rate at a given pressure drop, faster flowing filters will result in smaller, more economical systems.

*Data from published product literature

LifeASSURE™ BNA020 Series Log Reduction Grade Filters

The number of 30" filters needed to provide a 45 gpm flow with a clean pressure drop of 1 psid (170 lpm flow @ 69 mbar)	
LifeASSURE™ BNA020 Series Filters	5 filters
Competitor A	8 filters
Competitor B	14 filters
Competitor C	8 filters

As the example above illustrates*, the nearest competitor requires significantly more 30" filters to provide the same flow rate and pressure drop.

Prefiltration Selections

Many bottling applications employ a prefilter and final filter in series to achieve maximum performance and economy. Prefilters are used to help protect and extend the life of more expensive final filters. 3M Purification offers a number of premium prefilter choices: Betafine™ XL series pleated filter cartridges, Betapure™ NT-T series depth filter cartridges and LifeASSURE™ BLA series membrane filter cartridges. Betafine XL series filter cartridges (Literature 70-0201-8686-5) feature 3M Purification's APT maximizing the accessible filter area and supplying exceptionally high flow rates. Those preferring depth-style filters can select from Betapure™ NT-T series prefilter family (Literature 70-0201-8720-2) which employs an advanced media design that enhances flow while extending service life. For additional bioburden control, LifeASSURE BLA series filter cartridges (Literature 70-0201-8712-9), featuring dual-zone membrane, are designed to deliver the ultimate in final membrane protection and bioburden reduction.

3M Purification Filter Housings

A specialized range of filter housings is available to meet the needs of the food & beverage industry. They provide easy access for filter change-out and afford a secure seal between filter and housing to help prevent fluid bypass. All housings are constructed using 316L stainless steel to help maximize corrosion resistance.

Materials of Construction	
Membrane	Polyether sulfone (PES)
Media Support Layers	Polypropylene
Inner Core, Outer Cage, End Cap Adapters	Polypropylene
Gasket & O-ring Options	Various polymers available
Encapsulated Adapter Reinforcing Ring	Polyether sulfone
Operating Conditions	
Typical Water Flow Rate at 25 °C	3.1 gpm/psid (17 lpm/100 mbar)
Maximum Forward Pressure Differential	80 psid @ 77 °F (5.5 bar @ 25 °C) 25 psid @ 176 °F (1.7 bar @ 80 °C)
Maximum Reverse Pressure Differential	10 psid @ 77 °F (0.69 bar @ 25 °C)
Maximum Forward Flow Diffusion at 25 °C per 10" filter	51 cc/min @ 35 psig (2.41 bar)
Maximum Hot Water Sanitation Temperature	85 °C
Maximum Peracetic Acid Exposure	1% (10,000 ppm)
Cartridge Dimensions	
Filtration Surface Area	8.5 ft ² (0.79 m ²)
Outer Diameter	2.75" (70 mm)
Nominal Length	10" (254 mm), 20" (508 mm), 30" (762 mm), 40" (1016 mm)

*Data from published product literature


LifeASSURE™ BNA020 Series Ordering Guide

Cartridge Code	Configuration Code	Length Length Code	End Modification Code	Gasket/O-ring Material Code
BNA020	F	01 - 10" 02 - 20" 03 - 30" 04 - 40"	B - 226 O-ring & Spear (Code 7) C - 222 O-ring & Spear (Code 8) F - 222 O-ring & Flat Cap (Code 3)	A - Silicone B-Fluorocarbon C - EPR


PLEASE NOTE: The Order Guide above is for reference only. Not all combinations are available. Please consult with your 3M representative to determine the appropriate part number for your application.

LifeASSURE™ BNA020 Series Filter Disc Ordering Guide

Part Number	Size	Quantity	Packaging
NM04708BNA020	47 mm	40	Box



NM04708BNA020



Technical Information
The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.
Product Selection and Use
Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.
Warranty, Limited Remedy, and Disclaimer
Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability
Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Purification Inc.
3M Separation and Purification Sciences Division
 400 Research Parkway
 Meriden, CT 06450 USA
 Phone 1-800-243-6894
 1-203-237-5541
 Fax 1-203-630-4530
 Web www.3Mpurification.com

Your local distributor:

Betafine, Betapure and LifeASSURE are trademarks of 3M Company.
 All other trademarks are the property of their respective owners.
 © 2018 3M Company. All rights reserved.
 70020210004 REV 0318sr