


3M™ Scotchlok™ Terminals

MNG18BC thru MNG10BC

Butt Connector, Nylon Insulated with Insulation Grip



Data Sheet

July 2010

Product Number	Wire Range (AWG)	L	Barrel I.D.	Max. Insulation Diameter
MNG18BC	22-18	1.08 in.	0.07 in.	0.14 in.
MNG14BC	16-14	1.10 in.	0.09 in.	0.17 in.
MNG10BC	12-10	1.23 in.	0.135 in.	0.25 in.

Agency Approvals & Self Certifications

UL Listed, Standard No. UL 486C, 3M File No. E23438

CSA Certified, Standard No. C22.2 No. 0.65, 3M File No. LR22190

RoHS 2002/95/EC




RoHS Compliant 2002/95/EC* means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2002/618/EC, unless the substance is in an application that is exempt under RoHS. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

Specifications

Wire Size:	See Table Above
Barrel Seam:	Butted with Insulation Grip
Max. Voltage Rating:	600 V Building Wire 1000 V Signs, Fixtures (Luminaires)
Max. Operating Temp:	221°F (105°C)
Max. Current:	Same as Wire
Insulator Material:	Nylon
Terminal Material:	Copper
Insulation Grip Material:	Brass
Plating:	Tin

3M™ Scotchlok™ Terminals MNG18BC thru MNG10BC

Installation Information



UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M™ Scotchlok™ Crimp Tool: TH-440, TH-450 (scissor style), or TR-482, TR-490 (ratchet style) hand tools.



Barrel Crimp (Electrical)

Insulation Crimp (Mechanical)

Engineering Specification

Crimp-type terminals shall connect, electrically and mechanically, to the pre-stripped end of two stranded copper wires.

The connector line shall offer barrel variations in wire (AWG) size (22-18, 16-14 and 12-10) and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated with insulation grip, etc.).

The insulator shall be color coded and sized for a specified (AWG) wire range (22-18, 16-14 and 12-10).

Shelf Life & Storage

This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

Availability

Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1-800-472-1190.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M and Scotchlok are trademarks of 3M Company.



Electrical Markets Division
6801 River Place Blvd.
Austin, TX 78726-9000
800 472.1190
FAX: 800.262.6329
www.3M.com/electrical

Please recycle
© 3M 2010 All rights reserved
78-8125-9662-1 B