

## Respiratory Protection for Wildfire Smoke Inhalation - California

The California Department of Industrial Relations' Occupational Safety and Health Standards Board (Cal/OSHA) has adopted regulation 8CCR5141.1 requiring employers to provide respiratory protection to all employees working outside for longer than one hour when the air quality index (AQI) reaches 151 or greater.

### What Is PM<sub>2.5</sub>?

PM<sub>2.5</sub> means particulate matter measuring 2.5 microns or less across. A micron is a very small unit of measure — one millionth of a meter.

- These particles are so small that they cannot be seen by the human eye.
- Particles this small can be easily inhaled and travel deep into the respiratory tract and have been associated with a variety of short-term and long-term health conditions.

Source: [United States Environmental Protection Agency](#)

### Where can I find AQI information?

The United States [AirNow system](#) contains current AQI data, which includes a clickable map for area-specific AQIs. Local resources, such as the [California Air Resources Board](#), local air pollution control district websites, or local air quality management district website may also be helpful. A direct-reading particulate monitor that meets all requirements of Appendix A of the [California Code of Regulation Title 8 section 5141.1](#) may also be used to determine the AQI.

### What does it mean for you?

Table 1: AQI Categories for PM<sub>2.5</sub>

Air Quality Index	Level of Health Concern
0 to 50	Good
51 to 100	Moderate
101 to 150	Unhealthy for Sensitive Groups
151 to 200	Unhealthy
201 to 300	Very Unhealthy
301 to 500	Hazardous

Source: <https://www.airnow.gov/aqi/aqi-basics/>

# 3M Personal Safety Division

## When the AQI reaches levels between 151 and 500:

According to the regulation, which is enforced by the California Division of Occupational Safety and Health (Cal/OSHA), employers shall provide respirators<sup>1</sup> approved by the National Institute for Occupational Safety and Health (NIOSH), such as the NIOSH-approved 3M™ Particulate Respirator 8210 N95 filtering facepiece, for voluntary use in accordance with [Section 5144](#) to help protect the worker from inhalation of PM<sub>2.5</sub>. Employers are required to provide training that covers the information contained in Appendix B of [California Code of Regulation Title 8 section 5141.1](#), which includes training on proper donning, use, storage, and maintenance of respirators. If the respirators provided are filtering facepiece respirators (such as the NIOSH-approved 3M models listed below), then fit testing and medical evaluations are not required under the regulation.

## When the AQI reaches levels between 501 and above:

Respirator use is required in accordance with Section 5144. The employer shall provide respirators, and employee use is mandatory. The employer shall maintain a fully compliant respiratory protection program—including medical evaluation, fit testing, training, and record keeping for all employees and all types of respirators. Specifically, the employer shall provide respirators with an appropriate assigned protection factor (APF), as listed in [Section 5144](#), such that the PM<sub>2.5</sub> levels inside the respirator correspond to an AQI less than 151.

Table 2: California Respiratory Protection Requirements for PM<sub>2.5</sub> levels

AQI ≤ 150	AQI 151 - 500	AQI ≥ 501
No employer requirement	Employer <b>shall</b> provide	Employer <b>shall</b> provide
No employee requirement	Employee use <b>voluntary</b>	Employee use <b>mandatory</b>

Source: [State of California Department of Industrial Relations](#)

## Why is this important? What risks are associated with inhaling wildfire smoke?

Although there can be many hazardous chemicals and other constituents in wildfire smoke, one of the most significant pollutants for people who are not very close to the fire is “particulate matter,” the tiny particles suspended in the air. According to the [United States Environmental Protection Agency](#), PM<sub>2.5</sub> can be easily, and often unknowingly, inhaled—and due to the small particle size, it can travel deep into the respiratory tract, potentially irritating the lungs and being accompanied by persistent coughing, wheezing, or difficulty breathing. These small particles can also enter the bloodstream from the lungs and have been associated with more serious long-term health problems such as reduced lung function, bronchitis, worsening of asthma, heart failure, and early death.





## What about employees in states other than California?

Although this regulation applies to California, employers in other states may choose to use this standard as a best practice and decide to help protect their employees similarly. Employers should follow the United States Occupational Safety and Health Administration (OSHA) [Respiratory Protection Standard 29 CFR 1910.134](#), or the Respiratory Protection standard in their state.

## How 3M can help

3M provides a variety of NIOSH-approved N95 filtering facepieces that can be used to help comply with this regulation.

<sup>1</sup> Respirators help protect against certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. Follow all local regulations. In the U.S., a written respiratory protection program must be implemented meeting all the requirements of OSHA 29 CFR 1910.134 including training, fit testing, and medical evaluation. Misuse may result in sickness or death. For correct use, consult supervisor and User Instructions, or call 3M Personal Safety Division Technical Service at 1-800-243-4630.

<p><b>3M™ Aura™ Particulate Respirator 9211+, N95</b></p> 	<p>Unique three-panel design fits a wide range of face shapes/sizes and accommodates facial movements while talking. Features the 3M™ Cool Flow™ Comfort Valve that opens 44% easier allowing 70% more airflow than the previous valve.*</p>	<p>3M ID 7100303148 UPC 58887862965589</p>
<p><b>3M™ Aura™ Particulate Respirator 9205+, N95</b></p> 	<p>Three-panel, flat-fold disposable respirator designed to help provide comfortable, reliable worker protection against non-oil based particles.</p>	<p>3M ID 7100232219 UPC 00638060430606</p>
<p><b>3M™ Particulate Respirator 8511, N95</b></p> 	<p>Premium protection with comfort and protection combined. Manufactured with 3M™ Cool Flow™ Exhalation Valve to help reduce heat buildup inside the respirator.</p>	<p>3M ID 7000002056 UPC 50051138543438</p>
<p><b>3M™ Particulate Respirator 8210V, N95</b></p> 	<p>Designed to provide convenient, reliable respiratory protection in situations where particulate respiratory protection is warranted and can provide protection from certain non-oil based particles</p>	<p>3M ID 7000002462 UPC 50051131497110</p>

\* Compared to the previous 3M™ Cool Flow™ Valve when exhaled air was measured at a 10 L/min breathing rate.

## Other 3M Resources

### Center for Respiratory Protection Program

If you are implementing a respiratory protection program for the first time, or would like more information on programs, consider visiting [3M's Center for Respiratory Protection](#) for a step-by-step guide.

### Medical Evaluations

The [3M™ Online Respirator Medical Evaluation](#) provides immediate medical evaluation of respirator wearers for compliance with OSHA's Respiratory Protection Standard 29 CFR 1910.134. It can be used for all brands of respirators and is available in English and Spanish.

# 3M Personal Safety Division

## Fit Testing

3M™ Qualitative Fit Test kits are designed to help your organization meet respirator fit testing requirements. The kits can be used to check face-to-respirator seal on any particulate respirator or gas/vapor respirator with a particulate prefilter. A free instructional video on [Qualitative Fit Testing](#) using saccharin and Bitrex™ can be found on our [YouTube channel](#).

<b>3M™ Qualitative Fit Test Apparatus, Sweet FT-10</b>	Uses a test solution of sodium saccharin that produces a sweet-tasting aerosol.	3M ID 70-0701-2151-5 UPC 00051138163587
<b>3M™ Qualitative Fit Test Apparatus, Bitter FT-30</b>	Uses a test solution of denatonium benzoate to produce a very bitter taste.	3M ID 70-0707-0964-0 UPC 00051138542030

For more information, please consult the [3M Personal Safety Division's wildfire resource webpage](#).



**Personal Safety Division**  
3M Center, Building 235-2W-70  
St. Paul, MN 55144-1000

3M PSD products are occupational use only.

**3M Canada**  
P.O. Box 5757  
London, Ontario  
N6A 4T1

**In United States of America**  
Technical Service 1-800-243-4630  
Customer Service 1-800-328-1667  
[3M.com/workersafety](http://3M.com/workersafety)

**In Canada**  
Technical Service 1-800-267-4414  
Customer Service 1-800-364-3577  
[3M.ca/Safety](http://3M.ca/Safety)

© 3M 2024. All rights reserved.  
3M, Aura, and Cool Flow are trademarks of 3M Company and affiliates.

Used under license in Canada. All other trademarks are property of their respective owners.  
Please recycle.